

### **0090.1008 Information**



For Reference Only

Part Number 0090.1008

Manufacturer Schurter Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 8A 1KVDC 5AG

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









| 0000 1008 | <b>Specifications</b> |
|-----------|-----------------------|
| ひひろひ すひひひ | Specifications        |

| Manufacturer Part Number         0090.1008           Manufacturer         Schurter Inc.           Category         Circuit Protection           Electrical, Specialty Fuses           Package         5AG, 10mm x 38.1mm           Series         ASO 10.3x38           Fuse Type         Cartridge           Current Rating         8A           Voltage Rating - AC         -           Voltage Rating - DC         1000V (1kV)           Response Time         -           Applications         Solar (Photovoltaic)           Features         -           Class         -           Approvals         UL, VDE           Operating Temperature         -50°C ~ 125°C           Breaking Capacity @ Rated Voltage         20kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.496" L (10.30mm x 38.00mm)    Report errors?  |                                   |   |
|--|-----------------------------------|---|
| Category         Circuit Protection           Electrical, Specialty Fuses           Package         5AG, 10mm x 38.1mm           Series         ASO 10.3x38           Fuse Type         Cartridge           Current Rating         8A           Voltage Rating - AC         -           Voltage Rating - DC         1000V (1kV)           Response Time         -           Applications         Solar (Photovoltaic)           Features         -           Class         -           Approvals         UL, VDE           Operating Temperature         50°C ~ 125°C           Breaking Capacity @ Rated Voltage         20kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.496" L (10.30mm x 38.00mm)   | Manufacturer Part Number          | 0090.1008                                 |
| Package         5AG, 10mm x 38.1mm           Series         ASO 10.3x38           Fuse Type         Cartridge           Current Rating         8A           Voltage Rating - AC         -           Voltage Rating - DC         1000V (1kV)           Response Time         -           Applications         Solar (Photovoltaic)           Features         -           Class         -           Approvals         UL, VDE           Operating Temperature         -50°C ~ 125°C           Breaking Capacity @ Rated Voltage         20kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.496" L (10.30mm x 38.00mm)  | Manufacturer                      | Schurter Inc.                             |
| Package         5AG, 10mm x 38.1mm           Series         ASO 10.3x38           Fuse Type         Cartridge           Current Rating         8A           Voltage Rating - AC         -           Voltage Rating - DC         1000V (1kV)           Response Time         -           Applications         Solar (Photovoltaic)           Features         -           Class         -           Approvals         UL, VDE           Operating Temperature         -50°C ~ 125°C           Breaking Capacity @ Rated Voltage         20kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.496" L (10.30mm x 38.00mm)  | Category                          | Circuit Protection                        |
| Series         ASO 10.3x38           Fuse Type         Cartridge           Current Rating         8A           Voltage Rating - AC         -           Voltage Rating - DC         1000V (1kV)           Response Time         -           Applications         Solar (Photovoltaic)           Features         -           Class         -           Approvals         UL, VDE           Operating Temperature         -50°C ~ 125°C           Breaking Capacity @ Rated Voltage         20kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.496" L (10.30mm x 38.00mm)   |                                   | Electrical, Specialty Fuses               |
| Fuse TypeCartridgeCurrent Rating8AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response Time-ApplicationsSolar (Photovoltaic)Features-Class-ApprovalsUL, VDEOperating Temperature-50°C ~ 125°CBreaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.496" L (10.30mm x 38.00mm)   | Package                           | 5AG, 10mm x 38.1mm                        |
| Current Rating  Voltage Rating - AC  Voltage Rating - DC  1000V (1kV)  Response Time  - Applications  Solar (Photovoltaic)  Features  - Class  - Approvals  UL, VDE  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  8A  1000V (1kV)  - 1000V (1kV)  Solar (Photovoltaic)  - 1000V (1 | Series                            | ASO 10.3x38                               |
| Voltage Rating - AC  Voltage Rating - DC  1000V (1kV)  Response Time  - Applications  Solar (Photovoltaic)  Features  - Class  - Approvals  UL, VDE  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  - 1000V (1kV)  ULVDE  - 1000V (1kV)  Solar (Photovoltaic)  - 1000V (1kV)  - 1000V (1kV)  - 1000V (1kV)  Solar (Photovoltaic)  - 1000V (1kV)   | Fuse Type                         | Cartridge                                 |
| Voltage Rating - DC  Response Time  - Applications  Solar (Photovoltaic)  Features  - Class  - Approvals  UL, VDE  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  1000V (1kV)  1000V (1k | Current Rating                    | 8A  |
| Response Time  Applications  Solar (Photovoltaic)  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  - Solar (Photovoltaic)  - Class  - Approvals  - UL, VDE  -50°C ~ 125°C  Breaking Capacity @ Rated Voltage  Holder  Holder  Size / Dimension  - Approvals  - Class   | Voltage Rating - AC               | -   |
| Applications  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  Solar (Photovoltaic)  - Solar (Photov | Voltage Rating - DC               | 1000V (1kV)                               |
| Features - Class - Approvals UL, VDE Operating Temperature -50°C ~ 125°C Breaking Capacity @ Rated Voltage 20kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.496" L (10.30mm x 38.00mm)  | Response Time                     | -   |
| Class - Approvals UL, VDE Operating Temperature -50°C ~ 125°C Breaking Capacity @ Rated Voltage 20kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.496" L (10.30mm x 38.00mm)   | Applications                      | Solar (Photovoltaic)                      |
| Approvals  UL, VDE  Operating Temperature  -50°C ~ 125°C  Breaking Capacity @ Rated Voltage  20kA  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  0.406" Dia x 1.496" L (10.30mm x 38.00mm)  | Features                          | -   |
| Operating Temperature  -50°C ~ 125°C  Breaking Capacity @ Rated Voltage  20kA  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  0.406" Dia x 1.496" L (10.30mm x 38.00mm)  | Class                             | -   |
| Breaking Capacity @ Rated Voltage 20kA  Mounting Type Holder  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.406" Dia x 1.496" L (10.30mm x 38.00mm)  | Approvals                         | UL, VDE                                   |
| Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.496" L (10.30mm x 38.00mm)  | Operating Temperature             | -50°C ~ 125°C                             |
| Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.496" L (10.30mm x 38.00mm)   | Breaking Capacity @ Rated Voltage | 20kA                                      |
| Size / Dimension 0.406" Dia x 1.496" L (10.30mm x 38.00mm)   | Mounting Type                     | Holder                                    |
|  | Package / Case                    | 5AG, 10mm x 38.1mm                        |
| Report errors?   | Size / Dimension                  | 0.406" Dia x 1.496" L (10.30mm x 38.00mm) |
|  |                                   | Report errors?                            |

### **0090.1008 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 0090.1008 Payment Methods



















## 0090.1008 Shipping Methods













If you have any question about 0090.1008, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com