

0201ZD272KAT2A

0201ZD272KAT2A Information

www.eiscer.co	 0201ZD272KAT2A AVX Corporation Capacitors Ceramic Capacitors CAP CER 2700PF 10V X5R 0201 0201 (0603 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



0201ZD272KAT2A Specifications

Manufacturer Part Number 0201ZD272KAT2A Manufacturer AVX Corporation Capacitors Capacitors Package 0201 (0603 Metric) Package 0201 (0603 Metric) Series - Capacitance 2700pF Tolerance ±10% Voltage - Rated 10V Parting Temperature Coefficient 05°C ~ 85°C Patings - Applications General Purpose Faiture Rate - Mounting Type General Purpose Package / Case 0201 (0603 Metric) Patings - Applications General Purpose Faiture Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Fickness (Max) 0.013" (0.33mm) Lead Spacing -		
Capacitors Package 0201 (0603 Metric) Series - Capacitance 2700pF Capacitance 2700pF Tolerance 210% Voltage - Rated 10% Tomperature Coefficient 010 Pactarge -55°C ~ 85°C Ratings - Applications -6neral Purpose Pailure Rate - Mounting Type Sufface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W 0.60mm x 0.30mm) Faight - Seated (Max) - Height - Seated (Max) - Lead Syle -	Manufacturer Part Number	0201ZD272KAT2A
Ceramic CapacitorsPackage0201 (0603 Metric)Series-Capacitance2700pFTolerance±10%Voltage - Rated10VTemperature CoefficientX5ROperating Temperature-55°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting Type001 (0603 Metric)Size / Dimension0.024" L x 0.012" W (0.60mm x 0.30mm)Fickness (Max)0.013" (0.33mm)Lead Spacing-Lead Style-	Manufacturer	AVX Corporation
Package0201 (0603 Metric)Series-Capacitance2700pFTolerance±10%Voltage - Rated10VTemperature CoefficientSSROperating Temperature-55°C ~ 85°CFeatures-Applications-ApplicationsGeneral PurposeFailure Rate-Mounting Type0201 (0603 Metric)Size / Dimension0.024" L x 0.012" W 0.60mm x 0.30mm)Height - Seated (Max)-Height - Seated (Max)-Height - Seated (Max)-Lead Spacing-Lead Style-Lead Style-	Category	Capacitors
Series-Capacitance2700pFTolerance±10%Voltage - Rated10VTemperature CoefficientX5ROperating Temperature-55°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case021 (0603 Metric)Size / Dimension0.024" L x 0.012" W (0.60mm x 0.30mm)Height - Seated (Max)-Thickness (Max)0.013" (0.33mm)Lead Spacing-Lead Style-Starle Style-		Ceramic Capacitors
Capacitance2700pFTolerance±10%Voltage - Rated10VTemperature CoefficientX5ROperating Temperature-55°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCSize / Dimension0.024" L x 0.012" W (0.60mm x 0.30mm)Height - Seated (Max)-Thickness (Max)0.013" (0.33mm)Lead Spacing-Lead Style-	Package	0201 (0603 Metric)
Tolerance±10%Voltage - Rated10VTemperature CoefficientX5ROperating Temperature-55°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0201 (0603 Metric)Size / Dimension0.024" L x 0.012" W (0.60mm x 0.30mm)Height - Seated (Max)-Lead Stufe0.013" (0.33mm)Lead Stufe-Stufe	Series	-
Voltage - RatedI0VTemperature CoefficientX5ROperating Temperature-5°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFaiture Rate-Mounting TypeSurface Mount, MLCCPackage / Case0201 (0603 Metric)Size / Dimension-Height - Seated (Max)-Thickness (Max)0.013" (0.33mm)Lead Spacing-Lead Style-State Style-State Style-State Style-State Style-State Style-State Style-Style<	Capacitance	2700pF
Temperature CoefficientX5ROperating Temperature-55°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0201 (0603 Metric)Size / Dimension0.024" L x 0.012" W (0.60mm x 0.30mm)Height - Seated (Max)-Lead Spacing-Lead Spacing-Lead Style-Street Component-Street Component <t< td=""><td>Tolerance</td><td>±10%</td></t<>	Tolerance	±10%
Operating Temperature-55°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0201 (0603 Metric)Size / Dimension0.024" L x 0.012" W (0.60mm x 0.30mm)Height - Seated (Max)-Thickness (Max)0.013" (0.33mm)Lead Spacing-Height Seated (Max)-State Spacing-State Spacing <t< td=""><td>Voltage - Rated</td><td>10V</td></t<>	Voltage - Rated	10V
Features.Ratings.ApplicationsGeneral PurposeFailure Rate.Mounting TypeSurface Mount, MLCCPackage / Case.0201 (0603 Metric)Size / Dimension.024" L x 0.012" W (0.60mm x 0.30mm)Height - Seated (Max).Thickness (Max).013" (0.33mm)Lead Spacing.Height - Seated (Max).	Temperature Coefficient	X5R
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0201 (0603 Metric)Size / Dimension0.024" L x 0.012" W (0.60mm x 0.30mm)Height - Seated (Max)-Thickness (Max)0.013" (0.33mm)Lead Spacing-Height - Seated (Max)-Height - Seated (Max)- </td <td>Operating Temperature</td> <td>-55°C ~ 85°C</td>	Operating Temperature	-55°C ~ 85°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0201 (0603 Metric)Size / Dimension0.024" L x 0.012" W (0.60mm x 0.30mm)Height - Seated (Max)-Thickness (Max)0.013" (0.33mm)Lead Spacing-Lead Style-	Features	-
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0201 (0603 Metric)Size / Dimension0.024" L x 0.012" W (0.60mm x 0.30mm)Height - Seated (Max)-Thickness (Max)0.013" (0.33mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case0201 (0603 Metric)Size / Dimension0.024" L x 0.012" W (0.60mm x 0.30mm)Height - Seated (Max)-Thickness (Max)0.013" (0.33mm)Lead Spacing-Lead Style-	Applications	General Purpose
Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.013" (0.33mm)Lead Spacing-Lead Style-	Package / Case	0201 (0603 Metric)
Thickness (Max)0.013" (0.33mm)Lead Spacing-Lead Style-	Size / Dimension	0.024" L x 0.012" W (0.60mm x 0.30mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.013" (0.33mm)
· · · · · · · · · · · · · · · · · · ·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

0201ZD272KAT2A Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

0201ZD272KAT2A Payment Methods



0201ZD272KAT2A Shipping Methods



If you have any question about 0201ZD272KAT2A, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com