



0208.750DRT1P Information

www.heisener.com

For Reference Only

Part Number 0208.750DRT1P
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

Description FUSE GLASS 750MA 350VAC 2AG

Package 2AG, 5mm x 15mm (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0208.750DRT1P Specifications

Manufacturer Part Number0208.750DRT1PManufacturerLittelfuse Inc.CategoryCircuit ProtectionFusesPackagePackage2AG, 5mm x 15mm (Axial)Series208Fuse TypeCartridge, GlassCurrent Rating750mAVoltage Rating - AC350VVoltage Rating - DC-Response TimeFastPackage / Case2AG, 5mm x 15mm (Axial)Mounting TypeHolderBreaking Capacity @ Rated Voltage100AMelting 12t1.05ApprovalsCE, cURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.185" Dia x 0.570" L (4.70mm x 14.48mm)Report errors?	•	
Category Circuit Protection Fuses Package 2AG, 5mm x 15mm (Axial) Series 208 Fuse Type Cartridge, Glass Current Rating 750mA Voltage Rating - AC 350V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 1.05 Approvals CE, cURus Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Manufacturer Part Number	0208.750DRT1P
Package 2AG, 5mm x 15mm (Axial) Series 208 Fuse Type Cartridge, Glass Current Rating 750mA Voltage Rating - AC 350V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting 12t 1.05 Approvals CE, cURus Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Manufacturer	Littelfuse Inc.
Package 2AG, 5mm x 15mm (Axial) Series 208 Fuse Type Cartridge, Glass Current Rating 750mA Voltage Rating - AC 350V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 1.05 Approvals CE, cURus Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Category	Circuit Protection
Series 208 Fuse Type Cartridge, Glass Current Rating 750mA Voltage Rating - AC 350V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 1.05 Approvals CE, cURus Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)		Fuses
Fuse TypeCartridge, GlassCurrent Rating750mAVoltage Rating - AC350VVoltage Rating - DC-Response TimeFastPackage / Case2AG, 5mm x 15mm (Axial)Mounting TypeHolderBreaking Capacity @ Rated Voltage100AMelting I2t1.05ApprovalsCE, cURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Package	2AG, 5mm x 15mm (Axial)
Current Rating 750mA Voltage Rating - AC 350V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 1.05 Approvals CE, cURus Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Series	208
Voltage Rating - AC Voltage Rating - DC Response Time Fast Package / Case Package / Case Description Package / Case Pa	Fuse Type	Cartridge, Glass
Voltage Rating - DC Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 1.05 Approvals CE, cURus Operating Temperature -55°C ~ 125°C Color - Size / Dimension Dia x 0.570" L (4.70mm x 14.48mm)	Current Rating	750mA
Response Time Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 1.05 Approvals CE, cURus Operating Temperature -55°C ~ 125°C Color - Size / Dimension Fast 2AG, 5mm x 15mm (Axial) Holder - 50A CE, cURus -55°C ~ 125°C -125°C -125°C -125°C -125°C -125°C -125°C -125°C -125°C -125°C	Voltage Rating - AC	350V
Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 1.05 Approvals CE, cURus Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Voltage Rating - DC	-
Mounting TypeHolderBreaking Capacity @ Rated Voltage100AMelting I2t1.05ApprovalsCE, cURusOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Response Time	Fast
Breaking Capacity @ Rated Voltage Melting I2t Approvals CE, cURus Operating Temperature -55°C ~ 125°C Color Size / Dimension 100A CE, cURus -55°C ~ 125°C 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Package / Case	2AG, 5mm x 15mm (Axial)
Melting I2t 1.05 ApprovalsCE, cURusOperating Temperature -55° C ~ 125° CColor-Size / Dimension $0.185''$ Dia x $0.570''$ L $(4.70 \text{mm x } 14.48 \text{mm})$	Mounting Type	Holder
Approvals CE, cURus Operating Temperature -55°C ~ 125°C Color - Size / Dimension CE, cURus -55°C ~ 125°C 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Breaking Capacity @ Rated Voltage	100A
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Melting I2t	1.05
Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Approvals	CE, cURus
Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Operating Temperature	-55°C ~ 125°C
· · · · · · · · · · · · · · · · · · ·	Color	-
Report errors?	Size / Dimension	0.185" Dia x 0.570" L (4.70mm x 14.48mm)
*		Report errors?

0208.750DRT1P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0208.750DRT1P Payment Methods





















0208.750DRT1P Shipping Methods













If you have any question about 0208.750DRT1P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com