

0215001.MRET1SPP

0215001.MRET1SPP Information

Heisener.com

Part Number 0215001.MRET1SPP

Manufacturer Littelfuse Inc.

Category Circuit Protection

Fuses

Description FUSE CERAMIC 1A 250VAC 5X20MM

Package 5mm x 20mm (Axial)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0215001.MRET1SPP Specifications

| Manufacturer Part Number 0215001.MRET1SPP Manufacturer Littelfuse Inc. Category Circuit Protection Package 5mm x 20mm (Axial) Series 215SP Fuse Type Cartridge, Ceramic Current Rating 1A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 1.52 Approvals CE, CQC, CSA, KC, PSE, UR, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm) | • | |
|--|-----------------------------------|--|
| Category Circuit Protection Fuses Package 5mm x 20mm (Axial) Series 215SP Fuse Type Cartridge, Ceramic Current Rating 1A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 1.52 Approvals CE, CQC, CSA, KC, PSE, UR, VDE Operating Temperature -55° C ~ 125° C Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm) | Manufacturer Part Number | 0215001.MRET1SPP |
| Fuses Package 5mm x 20mm (Axial) Series 215SP Fuse Type Cartridge, Ceramic Current Rating 1A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 1.52 Approvals CE, CQC, CSA, KC, PSE, UR, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm) | Manufacturer | Littelfuse Inc. |
| Package 5mm x 20mm (Axial) Series 215SP Fuse Type Cartridge, Ceramic Current Rating 1A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 1.52 Approvals CE, CQC, CSA, KC, PSE, UR, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm) | Category | Circuit Protection |
| Series 215SP Fuse Type Cartridge, Ceramic Current Rating 1A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 1.52 Approvals CE, CQC, CSA, KC, PSE, UR, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm) | | Fuses |
| Fuse Type Current Rating 1A Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature Color Size / Dimension Cartridge, Ceramic Cartridge, | Package | 5mm x 20mm (Axial) |
| Current Rating Voltage Rating - AC 250V Voltage Rating - DC Response Time Slow Package / Case Smm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 1.52 Approvals CE, CQC, CSA, KC, PSE, UR, VDE Operating Temperature -55°C ~ 125°C Color Size / Dimension 1.4 1.4 1.5 250V Color 1.5 250V Color 250V Col | Series | 215SP |
| Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting I2t Approvals CE, CQC, CSA, KC, PSE, UR, VDE Operating Temperature -55°C ~ 125°C Color Size / Dimension 250V Slow - Slow 5mm x 20mm (Axial) Through Hole 1.5kA 1.52 CE, CQC, CSA, KC, PSE, UR, VDE -55°C ~ 125°C 0.205" Dia x 0.787" L (5.20mm x 20.00mm) | Fuse Type | Cartridge, Ceramic |
| Voltage Rating - DC Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 1.52 Approvals CE, CQC, CSA, KC, PSE, UR, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm) | Current Rating | 1A |
| Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting I2t Approvals CE, CQC, CSA, KC, PSE, UR, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension Slow 5mm x 20mm (Axial) Through Hole 1.5kA 1.52 1.52 0.20°C CSA, KC, PSE, UR, VDE -55°C ~ 125°C 0.205" Dia x 0.787" L (5.20mm x 20.00mm) | Voltage Rating - AC | 250V |
| Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 1.52 Approvals CE, CQC, CSA, KC, PSE, UR, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm) | Voltage Rating - DC | - |
| Mounting Type Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 1.52 Approvals CE, CQC, CSA, KC, PSE, UR, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension Through Hole 1.5kA 1.52 1.52 CE, CQC, CSA, KC, PSE, UR, VDE -55°C ~ 125°C -55°C ~ 125°C | Response Time | Slow |
| Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 1.52 Approvals CE, CQC, CSA, KC, PSE, UR, VDE Operating Temperature -55°C ~ 125°C Color Size / Dimension 1.5kA 1.52 CE, CQC, CSA, KC, PSE, UR, VDE -55°C ~ 125°C -55°C ~ 125°C 0.205" Dia x 0.787" L (5.20mm x 20.00mm) | Package / Case | 5mm x 20mm (Axial) |
| $\begin{tabular}{lllllllllllllllllllllllllllllllllll$ | Mounting Type | Through Hole |
| Approvals CE, CQC, CSA, KC, PSE, UR, VDE Operating Temperature -55°C ~ 125°C Color Size / Dimension CE, CQC, CSA, KC, PSE, UR, VDE -55°C ~ 125°C 0.205" Dia x 0.787" L (5.20mm x 20.00mm) | Breaking Capacity @ Rated Voltage | 1.5kA |
| Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm) | Melting I2t | 1.52 |
| Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm) | Approvals | CE, CQC, CSA, KC, PSE, UR, VDE |
| Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm) | Operating Temperature | -55°C ~ 125°C |
| | Color | - |
| Report errors? | Size / Dimension | 0.205" Dia x 0.787" L (5.20mm x 20.00mm) |
| | | Report errors? |

0215001.MRET1SPP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0215001.MRET1SPP Payment Methods





















0215001.MRET1SPP Shipping Methods













If you have any question about 0215001.MRET1SPP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com