



0216.080MXEP Information

www.heisener.com

For Reference Only

Part Number0216.080MXEPManufacturerLittelfuse Inc.CategoryCircuit Protection

Fuses

Description FUSE CERAMIC 80MA 250VAC 5X20MM

Package 5mm x 20mm (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0216.080MXEP Specifications

Manufacturer Part Number0216.080MXEPManufacturerLittelfuse Inc.CategoryCircuit ProtectionFusesFusesPackage5mm x 20mm (Axial)Series216Fuse TypeCartridge, CeramicCurrent Rating80mAVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastPackage / Case5mm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAMelting 12t0.00084ApprovalsCCC, CE, CSA, SEMKO, UR, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.236" Dia x 0.886" L (6.00mm x 22.50mm)	•	
Category Circuit Protection Fuses Package 5mm x 20mm (Axial) Series 216 Fuse Type Cartridge, Ceramic Current Rating 80mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 0.00084 Approvals CCC, CE, CSA, SEMKO, UR, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.236" Dia x 0.886" L (6.00mm x 22.50mm)	Manufacturer Part Number	0216.080MXEP
Fuses Package 5mm x 20mm (Axial) Series 216 Fuse Type Cartridge, Ceramic Current Rating 80mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting 12t 0.00084 Approvals CCC, CE, CSA, SEMKO, UR, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.236" Dia x 0.886" L (6.00mm x 22.50mm)	Manufacturer	Littelfuse Inc.
Package5mm x 20mm (Axial)Series216Fuse TypeCartridge, CeramicCurrent Rating80mAVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastPackage / Case5mm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage1.5kAMelting I2t0.00084ApprovalsCCC, CE, CSA, SEMKO, UR, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.236" Dia x 0.886" L (6.00mm x 22.50mm)	Category	Circuit Protection
Series 216 Fuse Type Cartridge, Ceramic Current Rating 80mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 0.00084 Approvals CCC, CE, CSA, SEMKO, UR, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.236" Dia x 0.886" L (6.00mm x 22.50mm)		Fuses
Fuse Type Cartridge, Ceramic Current Rating 80mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 0.00084 Approvals CCC, CE, CSA, SEMKO, UR, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.236" Dia x 0.886" L (6.00mm x 22.50mm)	Package	5mm x 20mm (Axial)
Current Rating Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature CCC, CE, CSA, SEMKO, UR, VDE Operating Temperature -55°C ~ 125°C Color Size / Dimension 80mA	Series	216
Voltage Rating - AC Voltage Rating - DC Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting I2t Approvals CCC, CE, CSA, SEMKO, UR, VDE Operating Temperature -55°C ~ 125°C Color Size / Dimension 250V - 250M - 250M	Fuse Type	Cartridge, Ceramic
Voltage Rating - DC Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 0.00084 Approvals CCC, CE, CSA, SEMKO, UR, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.236" Dia x 0.886" L (6.00mm x 22.50mm)	Current Rating	80mA
Response Time Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 0.00084 Approvals CCC, CE, CSA, SEMKO, UR, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.236" Dia x 0.886" L (6.00mm x 22.50mm)	Voltage Rating - AC	250V
Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 0.00084 Approvals CCC, CE, CSA, SEMKO, UR, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.236" Dia x 0.886" L (6.00mm x 22.50mm)	Voltage Rating - DC	-
Mounting Type Breaking Capacity @ Rated Voltage 1.5kA Melting I2t 0.00084 Approvals CCC, CE, CSA, SEMKO, UR, VDE Operating Temperature -55°C ~ 125°C Color Size / Dimension Through Hole 1.5kA 0.00084 CCC, CE, CSA, SEMKO, UR, VDE -55°C ~ 125°C 0.236" Dia x 0.886" L (6.00mm x 22.50mm)	Response Time	Fast
Breaking Capacity @ Rated Voltage Melting I2t O.00084 Approvals CCC, CE, CSA, SEMKO, UR, VDE Operating Temperature -55°C ~ 125°C Color Size / Dimension 0.236" Dia x 0.886" L (6.00mm x 22.50mm)	Package / Case	5mm x 20mm (Axial)
Melting I2t 0.00084 ApprovalsCCC, CE, CSA, SEMKO, UR, VDEOperating Temperature -55° C ~ 125° CColor-Size / Dimension $0.236''$ Dia x $0.886''$ L $(6.00\text{mm x } 22.50\text{mm})$	Mounting Type	Through Hole
Approvals CCC, CE, CSA, SEMKO, UR, VDE Operating Temperature -55°C ~ 125°C Color Size / Dimension 0.236" Dia x 0.886" L (6.00mm x 22.50mm)	Breaking Capacity @ Rated Voltage	1.5kA
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.236" Dia x 0.886" L (6.00mm x 22.50mm)	Melting I2t	0.00084
Color -	Approvals	CCC, CE, CSA, SEMKO, UR, VDE
Size / Dimension 0.236" Dia x 0.886" L (6.00mm x 22.50mm)	Operating Temperature	-55°C ~ 125°C
, , , , , , , , , , , , , , , , , , ,	Color	-
Report errors?	Size / Dimension	0.236" Dia x 0.886" L (6.00mm x 22.50mm)
*		Report errors?

0216.080MXEP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0216.080MXEP Payment Methods





















0216.080MXEP Shipping Methods













If you have any question about 0216.080MXEP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com