



0216016.MXEP Information

www.heisener.com

For Reference Only

Part Number0216016.MXEPManufacturerLittelfuse Inc.CategoryCircuit Protection

Fuses

Description FUSE CERAMIC 16A 250VAC 5X20MM

Package 5mm x 20mm (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0216016.MXEP Specifications

Manufacturer Part Number0216016.MXEPManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackage5mm x 20mm (Axial)Series216Fuse TypeCartridge, CeramicCurrent Rating16AVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastPackage / Case5mm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage750AMelting 12t462.5ApprovalsCE, CSA, PSE, SEMKO, UR, TUVOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.228" Dia x 0.886" L (5.80mm x 22.50mm)Report errors?	•	
Category Circuit Protection Fuses Package 5mm x 20mm (Axial) Series 216 Fuse Type Cartridge, Ceramic Current Rating 16A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 750A Melting I2t 462.5 Approvals CE, CSA, PSE, SEMKO, UR, TUV Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Manufacturer Part Number	0216016.MXEP
Fuses Package 5mm x 20mm (Axial) Series 216 Fuse Type Cartridge, Ceramic Current Rating 16A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 750A Melting 12t 462.5 Approvals CE, CSA, PSE, SEMKO, UR, TUV Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Manufacturer	Littelfuse Inc.
Package5mm x 20mm (Axial)Series216Fuse TypeCartridge, CeramicCurrent Rating16AVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastPackage / Case5mm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage750AMelting I2t462.5ApprovalsCE, CSA, PSE, SEMKO, UR, TUVOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Category	Circuit Protection
Series 216 Fuse Type Cartridge, Ceramic Current Rating 16A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 750A Melting I2t 462.5 Approvals CE, CSA, PSE, SEMKO, UR, TUV Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)		Fuses
Fuse Type Current Rating 16A Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 462.5 Approvals CE, CSA, PSE, SEMKO, UR, TUV Operating Temperature -55°C ~ 125°C Color Size / Dimension Cartridge, Ceramic 16A Cartridge, Ceramic 16A 250V CHANA 462.5 Color -100.228" Dia x 0.886" L (5.80mm x 22.50mm)	Package	5mm x 20mm (Axial)
Current Rating Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 750A Melting I2t 462.5 Approvals CE, CSA, PSE, SEMKO, UR, TUV Operating Temperature -55°C ~ 125°C Color - Size / Dimension 16A 250V 250V - Color 16A 250V 250V - Color 250V 250V	Series	216
Voltage Rating - AC Voltage Rating - DC Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 750A Melting I2t 462.5 Approvals CE, CSA, PSE, SEMKO, UR, TUV Operating Temperature -55°C ~ 125°C Color Size / Dimension 250V - Color - Size / Dimension Past CE, CSA, PSE, SEMKO, UR, TUV 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Fuse Type	Cartridge, Ceramic
Voltage Rating - DC Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 750A Melting I2t 462.5 Approvals CE, CSA, PSE, SEMKO, UR, TUV Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Current Rating	16A
Response Time Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 750A Melting I2t 462.5 Approvals CE, CSA, PSE, SEMKO, UR, TUV Operating Temperature -55°C ~ 125°C Color Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Voltage Rating - AC	250V
Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 750A Melting I2t 462.5 Approvals CE, CSA, PSE, SEMKO, UR, TUV Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Voltage Rating - DC	-
Mounting Type Breaking Capacity @ Rated Voltage 750A Melting I2t 462.5 Approvals CE, CSA, PSE, SEMKO, UR, TUV Operating Temperature -55°C ~ 125°C Color Size / Dimension Through Hole 750A 462.5 462.5 CE, CSA, PSE, SEMKO, UR, TUV -55°C ~ 125°C - 125°C	Response Time	Fast
Breaking Capacity @ Rated Voltage 750A Melting I2t 462.5 Approvals CE, CSA, PSE, SEMKO, UR, TUV Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Package / Case	5mm x 20mm (Axial)
Melting I2t 462.5 Approvals CE, CSA, PSE, SEMKO, UR, TUV Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Mounting Type	Through Hole
Approvals CE, CSA, PSE, SEMKO, UR, TUV Operating Temperature -55°C ~ 125°C Color Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Breaking Capacity @ Rated Voltage	750A
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Melting I2t	462.5
Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Approvals	CE, CSA, PSE, SEMKO, UR, TUV
Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Operating Temperature	-55°C ~ 125°C
, , , , , , , , , , , , , , , , , , ,	Color	-
Report errors?	Size / Dimension	0.228" Dia x 0.886" L (5.80mm x 22.50mm)
		Report errors?

0216016.MXEP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0216016.MXEP Payment Methods

































If you have any question about 0216016.MXEP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com