



0217.040MXEP Information

Manufactu Category Heisener.com

Part Number 0217.040MXEP
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

Description FUSE GLASS 40MA 250VAC 5X20MM

Package 5mm x 20mm (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0217.040MXEP Specifications

Manufacturer Part Number 0217.040MXEP Manufacturer Littelfuse Inc. Category Circuit Protection Fuses Fuses Package 5mm x 20mm (Axial) Series 217 Fuse Type Cartridge, Glass Current Rating 40mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 0.00008 Approvals CCC, CE, CSA, KC, SEMKO, UL, VDE Operating Temperature -55°C ~ 125°C Color -	•	
Category Circuit Protection Fuses Package 5mm x 20mm (Axial) Series 217 Fuse Type Cartridge, Glass Current Rating 40mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 0.00008 Approvals CCC, CE, CSA,KC, SEMKO, UL, VDE Operating Temperature -55°C ~ 125°C Color -	Manufacturer Part Number	0217.040MXEP
Fuses Package 5mm x 20mm (Axial) Series 217 Fuse Type Cartridge, Glass Current Rating 40mA Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 0.00008 Approvals CCC, CE, CSA,KC, SEMKO, UL, VDE Operating Temperature -55°C ~ 125°C Color	Manufacturer	Littelfuse Inc.
Package 5mm x 20mm (Axial) Series 217 Fuse Type Cartridge, Glass Current Rating 40mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 0.00008 Approvals CCC, CE, CSA,KC, SEMKO, UL, VDE Operating Temperature -55°C ~ 125°C Color -	Category	Circuit Protection
Series 217 Fuse Type Cartridge, Glass Current Rating 40mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 0.00008 Approvals CCC, CE, CSA,KC, SEMKO, UL, VDE Operating Temperature -55°C ~ 125°C Color -		Fuses
Fuse Type Current Rating 40mA Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Approvals CCC, CE, CSA,KC, SEMKO, UL, VDE Operating Temperature Color Cartridge, Glass 40mA Cartridge, Glass 40mA 40mA 250V Fast Fast Current Rating Annual Capacity Apact Color Cartridge, Glass 40mA 40ma	Package	5mm x 20mm (Axial)
Current Rating 40mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 0.00008 Approvals CCC, CE, CSA,KC, SEMKO, UL, VDE Operating Temperature -55°C ~ 125°C Color -	Series	217
Voltage Rating - AC Voltage Rating - DC Response Time Fast Package / Case Smm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature CCC, CE, CSA,KC, SEMKO, UL, VDE Operating Temperature -55°C ~ 125°C Color	Fuse Type	Cartridge, Glass
Voltage Rating - DC Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 0.00008 Approvals CCC, CE, CSA,KC, SEMKO, UL, VDE Operating Temperature -55°C ~ 125°C Color -	Current Rating	40mA
Response Time Fast Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 0.00008 Approvals CCC, CE, CSA,KC, SEMKO, UL, VDE Operating Temperature -55°C ~ 125°C Color -	Voltage Rating - AC	250V
Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 0.00008 Approvals CCC, CE, CSA,KC, SEMKO, UL, VDE Operating Temperature -55°C ~ 125°C Color -	Voltage Rating - DC	-
Mounting Type Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature Color Through Hole 35A 0.00008 CCC, CE, CSA,KC, SEMKO, UL, VDE -55°C ~ 125°C -	Response Time	Fast
Breaking Capacity @ Rated Voltage 35A Melting I2t 0.00008 Approvals CCC, CE, CSA,KC, SEMKO, UL, VDE Operating Temperature -55°C ~ 125°C Color -	Package / Case	5mm x 20mm (Axial)
Melting I2t 0.00008 ApprovalsCCC, CE, CSA,KC, SEMKO, UL, VDEOperating Temperature -55° C ~ 125° CColor-	Mounting Type	Through Hole
Approvals CCC, CE, CSA,KC, SEMKO, UL, VDE Operating Temperature -55°C ~ 125°C Color -	Breaking Capacity @ Rated Voltage	35A
Operating Temperature -55°C ~ 125°C Color -	Melting I2t	0.00008
Color -	Approvals	CCC, CE, CSA,KC, SEMKO, UL, VDE
	Operating Temperature	-55°C ~ 125°C
Circ / Dimension 0.226" Dia v. 0.996" I. (6.00mm v. 22.50mm)	Color	-
Size / Difficultion 0.256 Dia x 0.886 L (0.00fillin x 22.50fillin)	Size / Dimension	0.236" Dia x 0.886" L (6.00mm x 22.50mm)
Report errors?		Report errors?

0217.040MXEP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0217.040MXEP Payment Methods



















0217.040MXEP Shipping Methods













If you have any question about 0217.040MXEP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com