

### 0219.250MXAE Information



For Reference Only

Part Number 0219.250MXAE
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

**Description** FUSE GLASS 250MA 250VAC 5X20MM

Package 5mm x 20mm (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 0219.250MXAE Specifications

Manufacturer Part Number0219.250MXAEManufacturerLittelfuse Inc.CategoryCircuit ProtectionFusesFusesPackage5mm x 20mm (Axial)Series219XAFuse TypeCartridge, GlassCurrent Rating250mAVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowPackage / Case5mm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage150AMelting 12t0.54ApprovalsCCC, CE, CSA, SEMKO, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.228" Dia x 0.886" L (5.80mm x 22.50mm)	•	
Category         Circuit Protection           Fuses           Package         5mm x 20mm (Axial)           Series         219XA           Fuse Type         Cartridge, Glass           Current Rating         250mA           Voltage Rating - AC         250V           Voltage Rating - DC         -           Response Time         Slow           Package / Case         5mm x 20mm (Axial)           Mounting Type         Through Hole           Breaking Capacity @ Rated Voltage         150A           Melting I2t         0.54           Approvals         CCC, CE, CSA, SEMKO, UL, VDE           Operating Temperature         -55°C ~ 125°C           Color         -           Size / Dimension         0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Manufacturer Part Number	0219.250MXAE
Fuses           Package         5mm x 20mm (Axial)           Series         219XA           Fuse Type         Cartridge, Glass           Current Rating         250mA           Voltage Rating - AC         250V           Voltage Rating - DC         -           Response Time         Slow           Package / Case         5mm x 20mm (Axial)           Mounting Type         Through Hole           Breaking Capacity @ Rated Voltage         150A           Melting 12t         0.54           Approvals         CCC, CE, CSA, SEMKO, UL, VDE           Operating Temperature         -55°C ~ 125°C           Color         -           Size / Dimension         0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Manufacturer	Littelfuse Inc.
Package5mm x 20mm (Axial)Series219XAFuse TypeCartridge, GlassCurrent Rating250mAVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowPackage / Case5mm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage150AMelting I2t0.54ApprovalsCCC, CE, CSA, SEMKO, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Category	Circuit Protection
Series 219XA Fuse Type Cartridge, Glass Current Rating 250mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 150A Melting 12t 0.54 Approvals CCC, CE, CSA, SEMKO, UL, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)		Fuses
Fuse Type Current Rating 250mA  Voltage Rating - AC 250V  Voltage Rating - DC Response Time Slow Package / Case 5mm x 20mm (Axial)  Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature -55°C ~ 125°C  Color Size / Dimension  Cartridge, Glass Cartridge, Glass Canda  Coma  Coma  Coma  Cond  Color  Cartridge, Glass  Coma  Coma  Cond  Color  Color  Color  Color  Size / Dimension  Cartridge, Glass  Coma  Color  Col	Package	5mm x 20mm (Axial)
Current Rating  Voltage Rating - AC  250V  Voltage Rating - DC  Response Time  Slow  Package / Case  5mm x 20mm (Axial)  Mounting Type  Through Hole  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  Operating Temperature  CCC, CE, CSA, SEMKO, UL, VDE  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  250W  -  25	Series	219XA
Voltage Rating - AC  Voltage Rating - DC  Response Time  Slow  Package / Case  5mm x 20mm (Axial)  Mounting Type  Through Hole  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CCC, CE, CSA, SEMKO, UL, VDE  Operating Temperature  Color  Color  Size / Dimension  250V  250V	Fuse Type	Cartridge, Glass
Voltage Rating - DC  Response Time  Slow  Package / Case  5mm x 20mm (Axial)  Mounting Type  Through Hole  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CCC, CE, CSA, SEMKO, UL, VDE  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  -  Slow  5mm x 20mm (Axial)  Characteristics  5mm x 20mm (Axial)  Through Hole  150A  0.54  Approvals  CCC, CE, CSA, SEMKO, UL, VDE  Operating Temperature  -55°C ~ 125°C  Color  -  Size / Dimension	Current Rating	250mA
Response Time  Package / Case  5mm x 20mm (Axial)  Mounting Type  Through Hole  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CCC, CE, CSA, SEMKO, UL, VDE  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  Slow  5mm x 20mm (Axial)  Check CSA, SEMKO  5mm x 20mm (Axial)  CCC, CE, CSA, SEMKO  50.24  50.24  50.228" Dia x 0.886" L (5.80mm x 22.50mm)	Voltage Rating - AC	250V
Package / Case 5mm x 20mm (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage 150A  Melting I2t 0.54  Approvals CCC, CE, CSA, SEMKO, UL, VDE  Operating Temperature -55°C ~ 125°C  Color -  Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Voltage Rating - DC	-
Mounting Type  Breaking Capacity @ Rated Voltage  150A  Melting I2t  Approvals  CCC, CE, CSA, SEMKO, UL, VDE  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  Through Hole  150A  0.54  -55°C ~ 25A, SEMKO, UL, VDE  -55°C ~ 125°C  -55°C ~ 125°C	Response Time	Slow
Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CCC, CE, CSA, SEMKO, UL, VDE  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  150A  0.54  CCC, CE, CSA, SEMKO, UL, VDE  -55°C ~ 125°C  -55°C ~ 125°C  0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Package / Case	5mm x 20mm (Axial)
Melting I2t  Approvals  CCC, CE, CSA, SEMKO, UL, VDE  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Mounting Type	Through Hole
Approvals  CCC, CE, CSA, SEMKO, UL, VDE  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Breaking Capacity @ Rated Voltage	150A
Operating Temperature         -55°C ~ 125°C           Color         -           Size / Dimension         0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Melting I2t	0.54
Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Approvals	CCC, CE, CSA, SEMKO, UL, VDE
Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Operating Temperature	-55°C ~ 125°C
, , , , , , , , , , , , , , , , , , ,	Color	-
Report errors?	Size / Dimension	0.228" Dia x 0.886" L (5.80mm x 22.50mm)
		Report errors?

#### 0219.250MXAE Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 0219.250MXAE Payment Methods



















## 0219.250MXAE Shipping Methods













If you have any question about 0219.250MXAE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com