



0224.375DRT3P Information



For Reference Only

Part Number 0224.375DRT3P
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

Description FUSE GLASS 375MA 250VAC 125VDC

Package 2AG, 5mm x 15mm (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0224.375DRT3P Specifications

Manufacturer Part Number0224.375DRT3PManufacturerLittelfuse Inc.CategoryCircuit ProtectionFusesPackagePackage2AG, 5mm x 15mm (Axial)Series224Fuse TypeCartridge, GlassCurrent Rating375mAVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeFastPackage / Case2AG, 5mm x 15mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage35A AC, 10kA DCMelting 12t0.171ApprovalsCE, CSA, ULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.185" Dia x 0.570" L (4.70mm x 14.48mm)Report errors?	•	
Category Circuit Protection Fuses Package 2AG, 5mm x 15mm (Axial) Series 224 Fuse Type Cartridge, Glass Current Rating 375mA Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A AC, 10kA DC Melting I2t 0.171 Approvals CE, CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Manufacturer Part Number	0224.375DRT3P
Fuses Package 2AG, 5mm x 15mm (Axial) Series 224 Fuse Type Cartridge, Glass Current Rating 375mA Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A AC, 10kA DC Melting 12t 0.171 Approvals CE, CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Manufacturer	Littelfuse Inc.
Package 2AG, 5mm x 15mm (Axial) Series 224 Fuse Type Cartridge, Glass Current Rating 375mA Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A AC, 10kA DC Melting I2t 0.171 Approvals CE, CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Category	Circuit Protection
Series 224 Fuse Type Cartridge, Glass Current Rating 375mA Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A AC, 10kA DC Melting I2t 0.171 Approvals CE, CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)		Fuses
Fuse Type Current Rating 375mA Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CE, CSA, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension Cartridge, Glass 375mA Cartridge, Glass 375mA 250V 250V 250V 125V Fast 2AG, 5mm x 15mm (Axial) Axial) Chock and a Color Color Cartridge, Glass 375mA 250V 250V 125V Cartridge, Glass 375mA 125V 125V 125V Chock and a Color Cartridge, Glass 375mA 125V 125V 125V 125V 125°C	Package	2AG, 5mm x 15mm (Axial)
Current Rating 375mA Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A AC, 10kA DC Melting I2t 0.171 Approvals CE, CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Series	224
Voltage Rating - AC Voltage Rating - DC Response Time Fast Package / Case Package / Case Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CE, CSA, UL Operating Temperature Color Color Size / Dimension 250V 125V 24G, 5mm x 15mm (Axial) Through Hole 24G, 5mm x 15mm (Axial) 250V 250V 260, 5mm x 15mm (Axial) 270, 5mm x 15mm (Axial	Fuse Type	Cartridge, Glass
Voltage Rating - DC Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A AC, 10kA DC Melting I2t 0.171 Approvals CE, CSA, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension 125V 125V 125V 125V 125V 125V 125V 125V 1250	Current Rating	375mA
Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A AC, 10kA DC Melting I2t 0.171 Approvals CE, CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Voltage Rating - AC	250V
Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A AC, 10kA DC Melting I2t 0.171 Approvals CE, CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Voltage Rating - DC	125V
Mounting Type Breaking Capacity @ Rated Voltage 35A AC, 10kA DC Melting I2t Approvals CE, CSA, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension Through Hole 35A AC, 10kA DC 0.171 CE, CSA, UL -55°C ~ 125°C -125°C 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Response Time	Fast
Breaking Capacity @ Rated Voltage 35A AC, 10kA DC Melting I2t 0.171 Approvals CE, CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Package / Case	2AG, 5mm x 15mm (Axial)
Melting I2t 0.171 ApprovalsCE, CSA, ULOperating Temperature -55° C ~ 125° CColor-Size / Dimension $0.185''$ Dia x $0.570''$ L $(4.70 \text{mm x } 14.48 \text{mm})$	Mounting Type	Through Hole
Approvals CE, CSA, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension CE, CSA, UL -55°C ~ 125°C - 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Breaking Capacity @ Rated Voltage	35A AC, 10kA DC
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Color - Size / Dimension 0.185° Dia x 0.570° L $(4.70 \text{mm x } 14.48 \text{mm})$	Melting I2t	0.171
Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Approvals	CE, CSA, UL
Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Operating Temperature	-55°C ~ 125°C
	Color	-
Report errors?	Size / Dimension	0.185" Dia x 0.570" L (4.70mm x 14.48mm)
		Report errors?

0224.375DRT3P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0224.375DRT3P Payment Methods





















0224.375DRT3P Shipping Methods













If you have any question about 0224.375DRT3P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com