

0224.750HXW Information



For Reference Only

Part Number 0224.750HXW
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

Description FUSE GLASS 750MA 250VAC 2AG

Package 2AG, 5mm x 15mm (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0224.750HXW Specifications

Manufacturer Part Number 0224.750HXW Manufacturer Littelfuse Inc. Category Circuit Protection Fuses Package Package 2AG, 5mm x 15mm (Axial) Series 224 Fuse Type Cartridge, Glass Current Rating 750mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting 12t 1.05 Approvals CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	•	
Category Circuit Protection Fuses Package 2AG, 5mm x 15mm (Axial) Series 224 Fuse Type Cartridge, Glass Current Rating 750mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 1.05 Approvals CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Manufacturer Part Number	0224.750HXW
Fuses Package 2AG, 5mm x 15mm (Axial) Series 224 Fuse Type Cartridge, Glass Current Rating 750mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 1.05 Approvals CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Manufacturer	Littelfuse Inc.
Package 2AG, 5mm x 15mm (Axial) Series 224 Fuse Type Cartridge, Glass Current Rating 750mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 1.05 Approvals CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Category	Circuit Protection
Series 224 Fuse Type Cartridge, Glass Current Rating 750mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 1.05 Approvals CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)		Fuses
Fuse Type Current Rating 750mA Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 1.05 Approvals CSA, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension Cartridge, Glass Cass 750mA Cartridge, Glass 750mA 750mA Cartridge, Glass 750mA 750mA CSA CAG CAG CAG CAG CAG CAG CA	Package	2AG, 5mm x 15mm (Axial)
Current Rating 750mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 1.05 Approvals CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Series	224
Voltage Rating - AC Voltage Rating - DC Response Time Package / Case Package / Case Through Hole Breaking Capacity @ Rated Voltage Melting 12t Approvals CSA, UL Operating Temperature Color Size / Dimension 250V 250V - 250V 250V 100 - CSA, UL 250V 250V 260V 2	Fuse Type	Cartridge, Glass
Voltage Rating - DC Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 1.05 Approvals CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension Past CHAPTON AND AND AND AND AND AND AND AND AND AN	Current Rating	750mA
Response Time Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 1.05 Approvals CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension Fast CAG, 5mm x 15mm (Axial) Through Hole 35A CSA, UL 1.05 CSA, UL -55°C ~ 125°C	Voltage Rating - AC	250V
Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 1.05 Approvals CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Voltage Rating - DC	-
Mounting Type Breaking Capacity @ Rated Voltage Melting I2t Approvals CSA, UL Operating Temperature Color Size / Dimension Through Hole 35A 1.05 CSA, UL -55°C ~ 125°C -125°C -125°C -125°C -125°C -125°C -125°C -125°C -125°C -125°C	Response Time	Fast
Breaking Capacity @ Rated Voltage Melting I2t 1.05 Approvals CSA, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension 35A 1.05 CSA, UL -55°C ~ 125°C - 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Package / Case	2AG, 5mm x 15mm (Axial)
Melting I2t 1.05 ApprovalsCSA, ULOperating Temperature -55° C ~ 125° CColor-Size / Dimension 0.185 " Dia x 0.570 " L (4.70mm x 14.48 mm)	Mounting Type	Through Hole
Approvals CSA, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Breaking Capacity @ Rated Voltage	35A
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Melting I2t	1.05
Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Approvals	CSA, UL
Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Operating Temperature	-55°C ~ 125°C
· · · · · · · · · · · · · · · · · · ·	Color	-
Report errors?	Size / Dimension	0.185" Dia x 0.570" L (4.70mm x 14.48mm)
report offors.		Report errors?

0224.750HXW Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0224.750HXW Payment Methods



















0224.750HXW Shipping Methods













If you have any question about 0224.750HXW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com