

0224006.HXW Information



For Reference Only

Part Number 0224006.HXW
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

Description FUSE GLASS 6A 125VAC 2AG **Package** 2AG, 5mm x 15mm (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0224006.HXW Specifications

Manufacturer Part Number0224006.HXWManufacturerLittelfuse Inc.CategoryCircuit ProtectionFuses2AG, 5mm x 15mm (Axial)Series224Fuse TypeCartridge, GlassCurrent Rating6AVoltage Rating - AC125VVoltage Rating - DC-Response TimeFastPackage / Case2AG, 5mm x 15mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage10kAMelting 12t22.1ApprovalsCSA, METI, ULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.185" Dia x 0.570" L (4.70mm x 14.48mm)Report errors?	•	
Category Circuit Protection Fuses Package 2AG, 5mm x 15mm (Axial) Series 224 Fuse Type Cartridge, Glass Current Rating 6A Voltage Rating - AC 125V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 10kA Melting I2t 22.1 Approvals CSA, METI, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Manufacturer Part Number	0224006.HXW
Fuses Package 2AG, 5mm x 15mm (Axial) Series 224 Fuse Type Cartridge, Glass Current Rating 6A Voltage Rating - AC 125V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 10kA Melting 12t 22.1 Approvals CSA, METI, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Manufacturer	Littelfuse Inc.
Package 2AG, 5mm x 15mm (Axial) Series 224 Fuse Type Cartridge, Glass Current Rating 6A Voltage Rating - AC 125V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 10kA Melting I2t 22.1 Approvals CSA, METI, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Category	Circuit Protection
Series 224 Fuse Type Cartridge, Glass Current Rating 6A Voltage Rating - AC 125 V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 10kA Melting I2t 22.1 Approvals CSA, METI, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)		Fuses
Fuse Type Current Rating 6A Voltage Rating - AC 125V Voltage Rating - DC Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CSA, METI, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension Cartridge, Glass CAA Cartridge, Glass CAA CAA 125V CSV Cartridge, Glass CAA CAA 125V CSV Color 1050 Cartridge, Glass CAA CAA 125V CSA CSA Color Cartridge, Glass CAA 125V CSA Color Cartridge, Glass CAA 125V Color 1050 CAA CATION CAA CAA CAA CAA CAA CAA CAA C	Package	2AG, 5mm x 15mm (Axial)
Current Rating Voltage Rating - AC 125V Voltage Rating - DC Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 22.1 Approvals CSA, METI, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension 6A 125V 125V Color 125V Color 125V Color 125V Color 125V Color 125V 125V	Series	224
Voltage Rating - AC Voltage Rating - DC Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting 12t Approvals CSA, METI, UL Operating Temperature Color Color Size / Dimension 125V	Fuse Type	Cartridge, Glass
Voltage Rating - DC Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 10kA Melting I2t 22.1 Approvals CSA, METI, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Current Rating	6A
Response Time Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 10kA Melting I2t 22.1 Approvals CSA, METI, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension Fast 2AG, 5mm x 15mm (Axial) Characteristics CSA, METI, UL -55°C ~ 125°C -125°C -125°C -125°C -125°C -125°C -125°C -125°C	Voltage Rating - AC	125V
Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 10kA Melting I2t 22.1 Approvals CSA, METI, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Voltage Rating - DC	-
Mounting Type Breaking Capacity @ Rated Voltage 10kA Melting I2t 22.1 Approvals CSA, METI, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension Through Hole 10kA 22.1 22.1 APPROVA 10kA 10kA	Response Time	Fast
Breaking Capacity @ Rated Voltage Melting I2t Approvals CSA, METI, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension 10kA 22.1 CSA, METI, UL -55°C ~ 125°C - 125°C 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Package / Case	2AG, 5mm x 15mm (Axial)
Melting I2t 22.1 Approvals CSA, METI, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Mounting Type	Through Hole
Approvals CSA, METI, UL Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Breaking Capacity @ Rated Voltage	10kA
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Melting I2t	22.1
Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Approvals	CSA, METI, UL
Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Operating Temperature	-55°C ~ 125°C
· · · · · · · · · · · · · · · · · · ·	Color	-
Report errors?	Size / Dimension	0.185" Dia x 0.570" L (4.70mm x 14.48mm)
		Report errors?

0224006.HXW Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0224006.HXW Payment Methods



















0224006.HXW Shipping Methods













If you have any question about 0224006.HXW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com