

022402.5HXW Information



For Reference Only

Part Number 022402.5HXW
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

Description FUSE GLASS 2.5A 250VAC 2AG

Package 2AG, 5mm x 15mm (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









022402.5HXW Specifications

Manufacturer Part Number 022402.5HXW Manufacturer Littelfuse Inc. Category Circuit Protection Fuses Package Package 2AG, 5mm x 15mm (Axial) Series 224 Fuse Type Cartridge, Glass Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 2.68 Approvals CSA, METI, UL Operating Temperature -55°C ~ 125°C	*	
Category Circuit Protection Fuses Package 2AG, 5mm x 15mm (Axial) Series 224 Fuse Type Cartridge, Glass Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 2.68 Approvals CSA, METI, UL	Manufacturer Part Number	022402.5HXW
Fuses Package 2AG, 5mm x 15mm (Axial) Series 224 Fuse Type Cartridge, Glass Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 2.68 Approvals CSA, METI, UL	Manufacturer	Littelfuse Inc.
Package 2AG, 5mm x 15mm (Axial) Series 224 Fuse Type Cartridge, Glass Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 2.68 Approvals CSA, METI, UL	Category	Circuit Protection
Series 224 Fuse Type Cartridge, Glass Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting 12t 2.68 Approvals CSA, METI, UL		Fuses
Fuse Type Cartridge, Glass Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 2.68 Approvals CSA, METI, UL	Package	2AG, 5mm x 15mm (Axial)
Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 2.68 Approvals CSA, METI, UL	Series	224
Voltage Rating - AC Voltage Rating - DC Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CSA, METI, UL	Fuse Type	Cartridge, Glass
Voltage Rating - DC Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 2.68 Approvals CSA, METI, UL	Current Rating	2.5A
Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 2.68 Approvals CSA, METI, UL	Voltage Rating - AC	250V
Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 2.68 Approvals CSA, METI, UL	Voltage Rating - DC	-
Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 2.68 Approvals CSA, METI, UL	Response Time	Fast
Breaking Capacity @ Rated Voltage 100A Melting I2t 2.68 Approvals CSA, METI, UL	Package / Case	2AG, 5mm x 15mm (Axial)
Melting I2t 2.68 Approvals CSA, METI, UL	Mounting Type	Through Hole
Approvals CSA, METI, UL	Breaking Capacity @ Rated Voltage	100A
	Melting I2t	2.68
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Approvals	CSA, METI, UL
	Operating Temperature	-55°C ~ 125°C
Color -	Color	-
Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Size / Dimension	0.185" Dia x 0.570" L (4.70mm x 14.48mm)
Report errors?		Report errors?

022402.5HXW Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

022402.5HXW Payment Methods



















022402.5HXW Shipping Methods













If you have any question about 022402.5HXW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com