

### 0229.600VXSP Information



For Reference Only

Part Number 0229.600VXSP
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

**Description** FUSE GLASS 600MA 250VAC 125VDC

Package 2AG, 5mm x 15mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 0229.600VXSP Specifications

Manufacturer Part Number0229.600VXSPManufacturerLittelfuse Inc.CategoryCircuit ProtectionFusesPackagePackage2AG, 5mm x 15mmSeries229Fuse TypeCartridge, GlassCurrent Rating600mAVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowPackage / Case2AG, 5mm x 15mmMounting TypeHolderBreaking Capacity @ Rated Voltage35A AC, 10kA DCMelting 12t1.75ApprovalsCE, CSA, ULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.177" Dia x 0.570" L (4.50mm x 14.48mm)Report errors?	•		
Category         Circuit Protection           Fuses           Package         2AG, 5mm x 15mm           Series         229           Fuse Type         Cartridge, Glass           Current Rating         600mA           Voltage Rating - AC         250V           Voltage Rating - DC         125V           Response Time         Slow           Package / Case         2AG, 5mm x 15mm           Mounting Type         Holder           Breaking Capacity @ Rated Voltage         35A AC, 10kA DC           Melting I2t         1.75           Approvals         CE, CSA, UL           Operating Temperature         -55°C ~ 125°C           Color         -           Size / Dimension         0.177" Dia x 0.570" L (4.50mm x 14.48mm)	Manufacturer Part Number	0229.600VXSP	
Fuses           Package         2AG, 5mm x 15mm           Series         229           Fuse Type         Cartridge, Glass           Current Rating         600mA           Voltage Rating - AC         250V           Voltage Rating - DC         125V           Response Time         Slow           Package / Case         2AG, 5mm x 15mm           Mounting Type         Holder           Breaking Capacity @ Rated Voltage         35A AC, 10kA DC           Melting 12t         1.75           Approvals         CE, CSA, UL           Operating Temperature         -55°C ~ 125°C           Color         -           Size / Dimension         0.177" Dia x 0.570" L (4.50mm x 14.48mm)	Manufacturer	Littelfuse Inc.	
Package       2AG, 5mm x 15mm         Series       229         Fuse Type       Cartridge, Glass         Current Rating       600mA         Voltage Rating - AC       250V         Voltage Rating - DC       125V         Response Time       Slow         Package / Case       2AG, 5mm x 15mm         Mounting Type       Holder         Breaking Capacity @ Rated Voltage       35A AC, 10kA DC         Melting I2t       1.75         Approvals       CE, CSA, UL         Operating Temperature       -55°C ~ 125°C         Color       -         Size / Dimension       0.177" Dia x 0.570" L (4.50mm x 14.48mm)	Category	Circuit Protection	
Series         229           Fuse Type         Cartridge, Glass           Current Rating         600mA           Voltage Rating - AC         250V           Voltage Rating - DC         125V           Response Time         Slow           Package / Case         2AG, 5mm x 15mm           Mounting Type         Holder           Breaking Capacity @ Rated Voltage         35A AC, 10kA DC           Melting I2t         1.75           Approvals         CE, CSA, UL           Operating Temperature         -55°C ~ 125°C           Color         -           Size / Dimension         0.177" Dia x 0.570" L (4.50mm x 14.48mm)		Fuses	
Fuse Type  Current Rating  600mA  Voltage Rating - AC  250V  Voltage Rating - DC  Response Time  Slow  Package / Case  2AG, 5mm x 15mm  Mounting Type  Holder  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CE, CSA, UL  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  Cartridge, Glass  Cartridge, Glass  Cantridge, Glass  600mA  Cartridge, Glass  600mA  600mA  125V  Response  Slow  Package / Case  2AG, 5mm x 15mm  Holder  2AG, 5mm x 15mm  CE, CSA, UL  1.75  Approvals  CE, CSA, UL  Operating Temperature  -55°C ~ 125°C  Color  - Size / Dimension  0.177" Dia x 0.570" L (4.50mm x 14.48mm)	Package	2AG, 5mm x 15mm	
Current Rating  Voltage Rating - AC  250V  Voltage Rating - DC  125V  Response Time  Slow  Package / Case  2AG, 5mm x 15mm  Mounting Type  Holder  Breaking Capacity @ Rated Voltage  Melting I2t  1.75  Approvals  CE, CSA, UL  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  600mA  600m  600m	Series	229	
Voltage Rating - AC  Voltage Rating - DC  Response Time  Slow  Package / Case  Package / Case  Holder  Breaking Capacity @ Rated Voltage  Melting 12t  Approvals  CE, CSA, UL  Operating Temperature  Color  Color  Size / Dimension  250V  250V  125V  Algorithm According Slow  Algorithm According Slow  Algorithm According Slow  125V  Algorithm According Acco	Fuse Type	Cartridge, Glass	
Voltage Rating - DC  Response Time  Slow  Package / Case  2AG, 5mm x 15mm  Mounting Type  Holder  Breaking Capacity @ Rated Voltage  Melting I2t  1.75  Approvals  CE, CSA, UL  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  125V  1	Current Rating	600mA	
Response Time  Package / Case  2AG, 5mm x 15mm  Mounting Type  Holder  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CE, CSA, UL  Operating Temperature  Color  Size / Dimension  Slow  2AG, 5mm x 15mm  Holder  25 C Can  25 C Can  25 C Can  25 C Can  26 C Color  17 Dia x 0.570" L (4.50mm x 14.48mm)	Voltage Rating - AC	250V	
Package / Case  Mounting Type  Holder  Breaking Capacity @ Rated Voltage  35A AC, 10kA DC  Melting I2t  1.75  Approvals  CE, CSA, UL  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  2AG, 5mm x 15mm  Holder  35A AC, 10kA DC  1.75  -55°C ~ 125°C  -125°C  0.177" Dia x 0.570" L (4.50mm x 14.48mm)	Voltage Rating - DC	125V	
Mounting TypeHolderBreaking Capacity @ Rated Voltage35A AC, 10kA DCMelting I2t1.75ApprovalsCE, CSA, ULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.177" Dia x 0.570" L (4.50mm x 14.48mm)	Response Time	Slow	
Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CE, CSA, UL  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  35A AC, 10kA DC  1.75  CE, CSA, UL  -55°C ~ 125°C  - 125°C	Package / Case	2AG, 5mm x 15mm	
Melting I2t1.75ApprovalsCE, CSA, ULOperating Temperature $-55^{\circ}$ C ~ $125^{\circ}$ CColor-Size / Dimension $0.177''$ Dia x $0.570''$ L $(4.50 \text{mm x } 14.48 \text{mm})$	Mounting Type	Holder	
Approvals CE, CSA, UL  Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Color -  Size / Dimension 0.177" Dia x 0.570" L (4.50mm x 14.48mm)	Breaking Capacity @ Rated Voltage	35A AC, 10kA DC	
Operating Temperature         -55°C ~ 125°C           Color         -           Size / Dimension         0.177" Dia x 0.570" L (4.50mm x 14.48mm)	Melting I2t	1.75	
Color - Size / Dimension 0.177" Dia x 0.570" L (4.50mm x 14.48mm)	Approvals	CE, CSA, UL	
Size / Dimension 0.177" Dia x 0.570" L (4.50mm x 14.48mm)	Operating Temperature	-55°C ~ 125°C	
` '	Color	-	
Report errors?	Size / Dimension	0.177" Dia x 0.570" L (4.50mm x 14.48mm)	
		Repor	t errors?

### 0229.600VXSP Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 0229.600VXSP Payment Methods



















### 0229.600VXSP Shipping Methods













If you have any question about 0229.600VXSP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com