

0230.375HXSW Information



For Reference Only

Part Number 0230.375HXSW
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

Description FUSE GLASS 375MA 250VAC 2AG **Package** Cartridge, Non-Standard (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0230.375HXSW Specifications

Manufacturer Part Number Manufacturer Littelfuse Inc. Category Circuit Protection Fuses Package Cartridge, Non-Standard (Axial) Series Fuse Type Cartridge, Glass Current Rating Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case Cartridge, Non-Standard (Axial) Slow Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Operating Temperature -55°C ~ 125°C	*	
Category Circuit Protection Fuses Package Cartridge, Non-Standard (Axial) Series 230 Fuse Type Cartridge, Glass Current Rating 375mA Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Approvals CSA, UL Operating Temperature Cartridge, Non-Standard CSA, UL CSA, UL Coperating Temperature	Manufacturer Part Number	0230.375HXSW
Fuses Package Cartridge, Non-Standard (Axial) Series 230 Fuse Type Cartridge, Glass Current Rating 375mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 0.58 Approvals CSA, UL Operating Temperature -55°C ~ 125°C	Manufacturer	Littelfuse Inc.
Package Cartridge, Non-Standard (Axial) Series 230 Fuse Type Cartridge, Glass Current Rating 375mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 0.58 Approvals CSA, UL Operating Temperature -55°C ~ 125°C	Category	Circuit Protection
Series 230 Fuse Type Cartridge, Glass Current Rating 375mA Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 0.58 Approvals CSA, UL Operating Temperature -55°C ~ 125°C		Fuses
Fuse Type Current Rating 375mA Voltage Rating - AC 250V Voltage Rating - DC Response Time Slow Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature Cartridge, Non-Standard (Axial) Through Hole 35A CSA, UL Operating Temperature -55°C ~ 125°C	Package	Cartridge, Non-Standard (Axial)
Current Rating Voltage Rating - AC 250V Voltage Rating - DC Response Time Slow Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature 375mA 250V	Series	230
Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CSA, UL Operating Temperature 250V Cartridge, Non-Standard (Axial) Cartridge, Non-Standard (A	Fuse Type	Cartridge, Glass
Voltage Rating - DC Response Time Slow Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 0.58 Approvals CSA, UL Operating Temperature -55°C ~ 125°C	Current Rating	375mA
Response Time Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Operating Temperature Slow Cartridge, Non-Standard (Axial) Through Hole 35A CSA, UL -55°C ~ 125°C	Voltage Rating - AC	250V
Package / Case Cartridge, Non-Standard (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A Melting I2t 0.58 Approvals CSA, UL Operating Temperature Cartridge, Non-Standard (Axial) Through Hole 35A 0.58 CSA, UL	Voltage Rating - DC	-
Mounting Type Breaking Capacity @ Rated Voltage Melting I2t Approvals CSA, UL Operating Temperature Through Hole 35A 0.58 CSA, UL	Response Time	Slow
Breaking Capacity @ Rated Voltage 35A Melting I2t 0.58 Approvals CSA, UL Operating Temperature -55°C ~ 125°C	Package / Case	Cartridge, Non-Standard (Axial)
Melting I2t 0.58 ApprovalsCSA, ULOperating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Mounting Type	Through Hole
Approvals CSA, UL Operating Temperature -55°C ~ 125°C	Breaking Capacity @ Rated Voltage	35A
Operating Temperature -55°C ~ 125°C	Melting I2t	0.58
	Approvals	CSA, UL
Color	Operating Temperature	-55°C ~ 125°C
Color	Color	-
Size / Dimension 0.177" Dia x 0.571" L (4.50mm x 14.50mm)	Size / Dimension	0.177" Dia x 0.571" L (4.50mm x 14.50mm)
Report errors?		Report errors?

0230.375HXSW Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0230.375HXSW Payment Methods



















0230.375HXSW Shipping Methods













If you have any question about 0230.375HXSW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com