



## 02321.25MXWP Information

Heisener.com

For Reference Only

Part Number 02321.25MXWP
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

**Description** FUSE GLASS 1.25A 250VAC 5X20MM

Package 5mm x 20mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 02321.25MXWP Specifications

Manufacturer Part Number         02321.25MXWP           Manufacturer         Littelfuse Inc.           Category         Circuit Protection           Fuses         Fuses           Package         5mm x 20mm           Series         232           Fuse Type         Cartridge, Glass           Current Rating         1.25A           Voltage Rating - AC         250V           Voltage Rating - DC         -           Response Time         Medium           Package / Case         5mm x 20mm           Mounting Type         Holder           Breaking Capacity @ Rated Voltage         100A           Melting 12t         4.11           Approvals         CE, KC, PSE           Operating Temperature         -55°C ~ 125°C           Color         -           Size / Dimension         0.205" Dia x 0.787" L (5.20mm x 20.00mm)	•	
Category         Circuit Protection           Fuses           Package         5mm x 20mm           Series         232           Fuse Type         Cartridge, Glass           Current Rating         1.25A           Voltage Rating - AC         250V           Voltage Rating - DC         -           Response Time         Medium           Package / Case         5mm x 20mm           Mounting Type         Holder           Breaking Capacity @ Rated Voltage         100A           Melting I2t         4.11           Approvals         CE, KC, PSE           Operating Temperature         -55°C ~ 125°C           Color         -           Size / Dimension         0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Manufacturer Part Number	02321.25MXWP
Fuses   Fuses   Smm x 20mm   Series   232   Suse Type   Cartridge, Glass   Current Rating   1.25A   Voltage Rating - AC   250V   Cartridge, Glass   Curent Rating   DC   - Response Time   Medium   Medium   Medium   Mounting Type   Holder   Holder   Holder   Holder   Holder   Holder   Holder   Holder   Holder   CE, KC, PSE   Operating Temperature   -55°C ~ 125°C   Color   Size / Dimension   0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Manufacturer	Littelfuse Inc.
Package       5mm x 20mm         Series       232         Fuse Type       Cartridge, Glass         Current Rating       1.25A         Voltage Rating - AC       250V         Voltage Rating - DC       -         Response Time       Medium         Package / Case       5mm x 20mm         Mounting Type       Holder         Breaking Capacity @ Rated Voltage       100A         Melting I2t       4.11         Approvals       CE, KC, PSE         Operating Temperature       -55°C ~ 125°C         Color       -         Size / Dimension       0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Category	Circuit Protection
Series       232         Fuse Type       Cartridge, Glass         Current Rating       1.25A         Voltage Rating - AC       250V         Voltage Rating - DC       -         Response Time       Medium         Package / Case       5mm x 20mm         Mounting Type       Holder         Breaking Capacity @ Rated Voltage       100A         Melting I2t       4.11         Approvals       CE, KC, PSE         Operating Temperature       -55°C ~ 125°C         Color       -         Size / Dimension       0.205" Dia x 0.787" L (5.20mm x 20.00mm)		Fuses
Fuse Type  Current Rating  1.25A  Voltage Rating - AC  250V  Voltage Rating - DC  Response Time  Medium  Package / Case  5mm x 20mm  Mounting Type  Holder  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  Cartridge, Glass  1.25A  Cartridge, Glass  1.25A  Voltage Rating Capacity  4.11  CE, KC, PSE  Operating Temperature  -55°C ~ 125°C  Color  - Size / Dimension  O.205" Dia x 0.787" L (5.20mm x 20.00mm)	Package	5mm x 20mm
Current Rating Voltage Rating - AC 250V  Voltage Rating - DC Response Time Medium Package / Case 5mm x 20mm Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 4.11 Approvals CE, KC, PSE Operating Temperature -55°C ~ 125°C Color - Size / Dimension  1.25A 250V  Addition I2t - Color - Size / Dimension  1.25A 1.25N  Ce, KC, PSE  0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Series	232
Voltage Rating - AC  Voltage Rating - DC  Response Time  Medium  Package / Case  5mm x 20mm  Mounting Type  Holder  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CE, KC, PSE  Operating Temperature  Color  Size / Dimension  250V  Addium  -  CE, KC, PSE  COOmm  COOMM  250V  Addium  CE, KC, PSE  COOMM  CE, KC, PSE  COOMM  COOM	Fuse Type	Cartridge, Glass
Voltage Rating - DC  Response Time Medium  Package / Case 5mm x 20mm  Mounting Type Holder  Breaking Capacity @ Rated Voltage 100A  Melting I2t 4.11  Approvals CE, KC, PSE  Operating Temperature -55°C ~ 125°C  Color -  Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Current Rating	1.25A
Response Time  Medium  Package / Case  5mm x 20mm  Mounting Type  Holder  Breaking Capacity @ Rated Voltage  100A  Melting I2t  4.11  Approvals  CE, KC, PSE  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  Medium  5mm x 20mm  Holder  5mm x 20mm  CE, KC, PSE  0.00A	Voltage Rating - AC	250V
Package / Case  Mounting Type  Holder  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CE, KC, PSE  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  5mm x 20mm  Holder  5mm x 20mm  4.11  4.11  4.11  CE, KC, PSE  -55°C ~ 125°C  -125°C  -125°C  -125°C  -125°C  -125°C  -125°C	Voltage Rating - DC	-
Mounting Type  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CE, KC, PSE  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  Holder  100A  4.11  4.11  -55°C ~ 125°C	Response Time	Medium
Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CE, KC, PSE  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  100A  4.11  CE, KC, PSE  -55°C ~ 125°C  0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Package / Case	5mm x 20mm
Melting I2t       4.11         Approvals       CE, KC, PSE         Operating Temperature       -55°C ~ 125°C         Color       -         Size / Dimension       0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Mounting Type	Holder
Approvals         CE, KC, PSE           Operating Temperature         -55°C ~ 125°C           Color         -           Size / Dimension         0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Breaking Capacity @ Rated Voltage	100A
Operating Temperature       -55°C ~ 125°C         Color       -         Size / Dimension       0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Melting I2t	4.11
Color - Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Approvals	CE, KC, PSE
Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Operating Temperature	-55°C ~ 125°C
· · · · · · · · · · · · · · · · · · ·	Color	-
Report errors?	Size / Dimension	0.205" Dia x 0.787" L (5.20mm x 20.00mm)
		Report errors?

#### 02321.25MXWP Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 02321.25MXWP Payment Methods





















## 02321.25MXWP Shipping Methods













If you have any question about 02321.25MXWP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com