



023902.5MXEP Information



For Reference Only

Part Number 023902.5MXEP
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

Description FUSE GLASS 2.5A 250VAC 5X20MM

Package 5mm x 20mm (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









023902.5MXEP Specifications

| Manufacturer Part Number 023902.5MXEP Manufacturer Littelfuse Inc. Category Circuit Protection Fuses Fuses Package 5mm x 20mm (Axial) Series 239 Fuse Type Cartridge, Glass Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting 12t 79.705 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.217" Dia x 0.846" L (5.50mm x 21.50mm) | • | |
|---|-----------------------------------|--|
| Category Circuit Protection Fuses Package 5mm x 20mm (Axial) Series 239 Fuse Type Cartridge, Glass Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 79.705 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.217" Dia x 0.846" L (5.50mm x 21.50mm) | Manufacturer Part Number | 023902.5MXEP |
| Fuses Package 5mm x 20mm (Axial) Series 239 Fuse Type Cartridge, Glass Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting 12t 79.705 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.217" Dia x 0.846" L (5.50mm x 21.50mm) | Manufacturer | Littelfuse Inc. |
| Package 5mm x 20mm (Axial) Series 239 Fuse Type Cartridge, Glass Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 79.705 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.217" Dia x 0.846" L (5.50mm x 21.50mm) | Category | Circuit Protection |
| Series 239 Fuse Type Cartridge, Glass Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 79.705 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.217" Dia x 0.846" L (5.50mm x 21.50mm) | | Fuses |
| Fuse Type Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 79.705 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension Cartridge, Glass Cash Cartridge, Glass Cash Cash Cash Colox - Cartridge, Glass Cash Cash Cash Colox - Cathridge, Glass Cash Colox - Cash Colox Cash Colox - Cash Cash Colox | Package | 5mm x 20mm (Axial) |
| Current Rating Voltage Rating - AC 250V Voltage Rating - DC Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 79.705 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension 2.5A 250V 100A CE, CSA, KC, PSE, UL 0.217" Dia x 0.846" L (5.50mm x 21.50mm) | Series | 239 |
| Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting 12t Approvals CE, CSA, KC, PSE, UL Operating Temperature Color Color Size / Dimension 250V 250V 100A CE, CSA, KC, PSE, UL 0.217" Dia x 0.846" L (5.50mm x 21.50mm) | Fuse Type | Cartridge, Glass |
| Voltage Rating - DC Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 79.705 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.217" Dia x 0.846" L (5.50mm x 21.50mm) | Current Rating | 2.5A |
| Response Time Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 79.705 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension Slow 5mm x 20mm (Axial) Through Hole 100A CE, CSA, KC, PSE, UL -55°C ~ 125°C | Voltage Rating - AC | 250V |
| Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 79.705 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.217" Dia x 0.846" L (5.50mm x 21.50mm) | Voltage Rating - DC | - |
| Mounting Type Breaking Capacity @ Rated Voltage 100A Melting I2t 79.705 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension Through Hole 100A 79.705 CE, CSA, KC, PSE, UL -55°C ~ 125°C | Response Time | Slow |
| Breaking Capacity @ Rated Voltage Melting I2t 79.705 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension 100A 79.705 CE, CSA, KC, PSE, UL -55°C ~ 125°C - 125°C 0.217" Dia x 0.846" L (5.50mm x 21.50mm) | Package / Case | 5mm x 20mm (Axial) |
| Melting I2t 79.705 ApprovalsCE, CSA, KC, PSE, ULOperating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Color-Size / Dimension $0.217''$ Dia x $0.846''$ L $(5.50\text{mm x } 21.50\text{mm})$ | Mounting Type | Through Hole |
| Approvals CE, CSA, KC, PSE, UL Operating Temperature -55° C $\sim 125^{\circ}$ C Color - Size / Dimension 0.217" Dia x 0.846" L (5.50mm x 21.50mm) | Breaking Capacity @ Rated Voltage | 100A |
| Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.217" Dia x 0.846" L (5.50mm x 21.50mm) | Melting I2t | 79.705 |
| Color - Size / Dimension 0.217" Dia x 0.846" L (5.50mm x 21.50mm) | Approvals | CE, CSA, KC, PSE, UL |
| Size / Dimension 0.217" Dia x 0.846" L (5.50mm x 21.50mm) | Operating Temperature | -55°C ~ 125°C |
| | Color | - |
| Donat was 2 | Size / Dimension | 0.217" Dia x 0.846" L (5.50mm x 21.50mm) |
| Report errors? | | Report errors? |

023902.5MXEP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

023902.5MXEP Payment Methods



















023902.5MXEP Shipping Methods













If you have any question about 023902.5MXEP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com