



023903.5MXBP Information



For Reference Only

Part Number 023903.5MXBP
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

Description FUSE GLASS 3.5A 250VAC 5X20MM

Package 5mm x 20mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









023903.5MXBP Specifications

Manufacturer Part Number 023903.5MXBP Manufacturer Littelfuse Inc. Category Circuit Protection Fuses Fuses Package 5mm x 20mm Series 239 Fuse Type Cartridge, Glass Current Rating 3.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 5mm x 20mm Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 128.05 Approvals CE, PSE, UL Operating Temperature -55°C ~ 125°C Color -	•	
Category Circuit Protection Fuses Fuses Package 5mm x 20mm Series 239 Fuse Type Cartridge, Glass Current Rating 3.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 5mm x 20mm Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 128.05 Approvals CE, PSE, UL Operating Temperature -55°C ~ 125°C Color -	Manufacturer Part Number	023903.5MXBP
Fuses	Manufacturer	Littelfuse Inc.
Package 5mm x 20mm Series 239 Fuse Type Cartridge, Glass Current Rating 3.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 5mm x 20mm Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 128.05 Approvals CE, PSE, UL Operating Temperature -55°C ~ 125°C Color -	Category	Circuit Protection
Series 239 Fuse Type Cartridge, Glass Current Rating 3.5A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 5mm x 20mm Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 128.05 Approvals CE, PSE, UL Operating Temperature -55°C ~ 125°C Color -		Fuses
Fuse Type Current Rating 3.5A Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t Approvals CE, PSE, UL Operating Temperature Cartridge, Glass S.5A Value Stov Color Cartridge, Glass S.5A 250V Cartridge, Glass S.5A Package / Case Pown Color - Color Cartridge, Glass CARTRIDGE S.5A 250V - COLOR - COLOR C	Package	5mm x 20mm
Current Rating Voltage Rating - AC 250V Voltage Rating - DC Response Time Slow Package / Case Mounting Type Breaking Capacity @ Rated Voltage Melting I2t Approvals CE, PSE, UL Operating Temperature Color 3.5A 3.5A 3.5A 3.5A 250V - Land 100 - CE, PSE, UL Color - Color	Series	239
Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t Approvals CE, PSE, UL Operating Temperature -55°C ~ 125°C Color	Fuse Type	Cartridge, Glass
Voltage Rating - DC Response Time Slow Package / Case 5mm x 20mm Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 128.05 Approvals CE, PSE, UL Operating Temperature -55°C ~ 125°C Color -	Current Rating	3.5A
Response Time Package / Case Somm x 20mm Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t 128.05 Approvals CE, PSE, UL Operating Temperature -55°C ~ 125°C Color -	Voltage Rating - AC	250V
Package / Case 5mm x 20mm Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 128.05 Approvals CE, PSE, UL Operating Temperature -55°C ~ 125°C Color -	Voltage Rating - DC	-
Mounting Type Breaking Capacity @ Rated Voltage Melting I2t Approvals CE, PSE, UL Operating Temperature -55°C ~ 125°C Color Holder 100A CE, PSE, UL -55°C ~ 125°C	Response Time	Slow
Breaking Capacity @ Rated Voltage 100A Melting I2t 128.05 Approvals CE, PSE, UL Operating Temperature -55°C ~ 125°C Color -	Package / Case	5mm x 20mm
Melting I2t 128.05 ApprovalsCE, PSE, ULOperating Temperature -55° C ~ 125° CColor-	Mounting Type	Holder
Approvals CE, PSE, UL Operating Temperature -55°C ~ 125°C Color -	Breaking Capacity @ Rated Voltage	100A
Operating Temperature -55°C ~ 125°C Color -	Melting I2t	128.05
Color -	Approvals	CE, PSE, UL
	Operating Temperature	-55°C ~ 125°C
0.205 Diagram 0.205	Color	-
Size / Dimension 0.205" Dia x 0.787" L (5.20mm x 20.00mm)	Size / Dimension	0.205" Dia x 0.787" L (5.20mm x 20.00mm)
Report errors?		Report errors?

023903.5MXBP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

023903.5MXBP Payment Methods



















023903.5MXBP Shipping Methods













If you have any question about 023903.5MXBP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com