



0251002.PF009L Information



Part Number 0251002.PF009L
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

Description FUSE BRD MNT 2A 125VAC/VDC AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0251002.PF009L Specifications

| Manufacturer Part Number0251002.PF009LManufacturerLittelfuse Inc.CategoryCircuit ProtectionFusesPackagePackageAxialSeriesPICO? II 251Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating2AVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastPackage / CaseAxialMounting TypeThrough HoleBreaking Capacity @ Rated Voltage50A AC, 300A DCMelting 12t0.405ApprovalsCCC, CSA, PSE, TUV, UROperating Temperature-55°C ~ 125°CColor-Size / Dimension0.110" Dia x 0.280" L (2.80mm x 7.11mm)Report errors? | * | |
|--|-----------------------------------|---|
| Category Circuit Protection Fuses Package Axial Series PICO? II 251 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 2A Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A AC, 300A DC Melting I2t 0.405 Approvals CCC, CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm) | Manufacturer Part Number | 0251002.PF009L |
| Fuses Package Axial Series PICO? II 251 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 2A Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Son AC, 300A DC Melting 12t Approvals CCC, CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension Axial Axial Cartridge Style Excluded) 2A Package Style Excluded) 2A 125V 1 | Manufacturer | Littelfuse Inc. |
| Package Axial Series PICO? II 251 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 2A Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A AC, 300A DC Melting I2t 0.405 Approvals CCC, CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm) | Category | Circuit Protection |
| Series PICO? II 251 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 2A Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A AC, 300A DC Melting I2t 0.405 Approvals CCC, CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm) | | Fuses |
| Fuse Type Current Rating 2A Voltage Rating - AC 125V Voltage Rating - DC Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature Color Size / Dimension Board Mount (Cartridge Style Excluded) 2A Board Mount (Cartridge Style Excluded) 2A 2A 125V Fast Fast Axial Axial CCC, CSA Axial CCC, CSA CCC, CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C -15°C Color -15°C ~ 125°C Color Color | Package | Axial |
| Current Rating Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CCC, CSA, PSE, TUV, UR Operating Temperature Color Size / Dimension 2A 125V 125V 125V Axial Axial Axial Axial CCC, CSA, PSE, TUV, UR 0.405 -55°C ~ 125°C -125°C | Series | PICO? II 251 |
| Voltage Rating - AC Voltage Rating - DC Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting 12t Approvals CCC, CSA, PSE, TUV, UR Operating Temperature Color Size / Dimension 125V 125V 125V 125V 125V 125V Axial Axial Axial Axial CCC, CSA, 200A DC 0.405 CCC, CSA, PSE, TUV, UR -55°C ~ 125°C 0.110" Dia x 0.280" L (2.80mm x 7.11mm) | Fuse Type | Board Mount (Cartridge Style Excluded) |
| Voltage Rating - DC Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CCC, CSA, PSE, TUV, UR Operating Temperature Color Size / Dimension 125V 125 | Current Rating | 2A |
| Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A AC, 300A DC Melting I2t 0.405 Approvals CCC, CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm) | Voltage Rating - AC | 125V |
| Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A AC, 300A DC Melting I2t 0.405 Approvals CCC, CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm) | Voltage Rating - DC | 125V |
| Mounting Type Breaking Capacity @ Rated Voltage 50A AC, 300A DC Melting I2t 0.405 Approvals CCC, CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color Size / Dimension Through Hole 50A AC, 300A DC 0.405 -255°C ~ 125°C -350°C ~ 125°C -350°C ~ 125°C | Response Time | Fast |
| Breaking Capacity @ Rated Voltage 50A AC, 300A DC Melting I2t 0.405 Approvals CCC, CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm) | Package / Case | Axial |
| Melting I2t 0.405 ApprovalsCCC, CSA, PSE, TUV, UROperating Temperature -55° C $\sim 125^{\circ}$ CColor-Size / Dimension 0.110° Dia x 0.280° L $(2.80 \text{mm x } 7.11 \text{mm})$ | Mounting Type | Through Hole |
| Approvals CCC, CSA, PSE, TUV, UR Operating Temperature -55° C $\sim 125^{\circ}$ C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm) | Breaking Capacity @ Rated Voltage | 50A AC, 300A DC |
| Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm) | Melting I2t | 0.405 |
| Color - Color | Approvals | CCC, CSA, PSE, TUV, UR |
| Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm) | Operating Temperature | -55°C ~ 125°C |
| | Color | - |
| Report errors? | Size / Dimension | 0.110" Dia x 0.280" L (2.80mm x 7.11mm) |
| | | Report errors? |

0251002.PF009L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0251002.PF009L Payment Methods



















0251002.PF009L Shipping Methods













If you have any question about 0251002.PF009L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com