



025103.5PF001L Information



Part Number 025103.5PF001L
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

Description FUSE BOARD MOUNT 3.5A 125VAC/VDC

Package Axia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









025103.5PF001L Specifications

Manufacturer Part Number025103.5PF001LManufacturerLittelfuse Inc.CategoryCircuit ProtectionFusesPackagePackageAxialSeriesPICO? II 251Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating3.5AVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastPackage / CaseAxialMounting TypeThrough HoleBreaking Capacity @ Rated Voltage50A AC, 300A DCMelting 12t1.58ApprovalsCSA, PSE, TUV, UROperating Temperature-55°C ~ 125°CColor-Size / Dimension0.110" Dia x 0.280" L (2.80mm x 7.11mm)Report errors?	•	
Category Circuit Protection Fuses Package Axial Series PICO? II 251 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 3.5A Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A AC, 300A DC Melting I2t 1.58 Approvals CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Manufacturer Part Number	025103.5PF001L
Fuses Package Axial Series PICO? II 251 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 3.5A Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Breaking Capacity @ Rated Voltage Melting I2t Approvals CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension Axial Axial CSA, PSE, TUV, UR -55°C ~ 125°C - Size / Dimension Axial	Manufacturer	Littelfuse Inc.
Package Axial Series PICO? II 251 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 3.5A Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A AC, 300A DC Melting I2t 1.58 Approvals CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Category	Circuit Protection
Series PICO? II 251 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 3.5A Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A AC, 300A DC Melting 12t 1.58 Approvals CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm)		Fuses
Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 3.5A Voltage Rating - AC 125V Voltage Rating - DC Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 1.58 Approvals CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color Size / Dimension Board Mount (Cartridge Style Excluded) 3.5A Package Style Excluded) 3.5A 125V Package Case Axial Axial CSA, PSE, TUV, UR -50°C ~ 125°C -1010" Dia x 0.280" L (2.80mm x 7.11mm)	Package	Axial
Current Rating Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 1.58 Approvals CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color Size / Dimension 3.5A 125V 3.5A 125V 125V Fast Fast Axial Axial Axial CSA, AXial Axial CSA, SOA DC 1.58 CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C O.110" Dia x 0.280" L (2.80mm x 7.11mm)	Series	PICO? II 251
Voltage Rating - AC Voltage Rating - DC Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CSA, PSE, TUV, UR Operating Temperature Color Color Size / Dimension 125V 125V 125V 125V 125V Axial Axial Axial CSA, 200A DC 1.58 CSA, PSE, TUV, UR -55°C ~ 125°C -125°C 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Fuse Type	Board Mount (Cartridge Style Excluded)
Voltage Rating - DC Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CSA, PSE, TUV, UR Operating Temperature Color Size / Dimension 125V 125° 12	Current Rating	3.5A
Response Time Fast Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A AC, 300A DC Melting I2t 1.58 Approvals CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Voltage Rating - AC	125V
Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A AC, 300A DC Melting I2t 1.58 Approvals CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Voltage Rating - DC	125V
Mounting Type Breaking Capacity @ Rated Voltage 50A AC, 300A DC Melting I2t 1.58 Approvals CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color Size / Dimension Through Hole 50A AC, 300A DC 1.58 CSA, PSE, TUV, UR -55°C ~ 125°C 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Response Time	Fast
Breaking Capacity @ Rated Voltage 50A AC, 300A DC Melting I2t 1.58 Approvals CSA, PSE, TUV, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Package / Case	Axial
Melting I2t 1.58 ApprovalsCSA, PSE, TUV, UROperating Temperature -55° C $\sim 125^{\circ}$ CColor-Size / Dimension 0.110° Dia x 0.280° L $(2.80 \text{mm x } 7.11 \text{mm})$	Mounting Type	Through Hole
Approvals CSA, PSE, TUV, UR Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Breaking Capacity @ Rated Voltage	50A AC, 300A DC
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Melting I2t	1.58
Color - Color	Approvals	CSA, PSE, TUV, UR
Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Operating Temperature	-55°C ~ 125°C
	Color	-
Report errors?	Size / Dimension	0.110" Dia x 0.280" L (2.80mm x 7.11mm)
		Report errors?

025103.5PF001L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

025103.5PF001L Payment Methods



















025103.5PF001L Shipping Methods













If you have any question about 025103.5PF001L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com