

0259.500TX913 Information



For Reference Only

Part Number0259.500TX913ManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE BRD MNT 500MA 125VAC/VDC

PackageRadial, Can, Horizontal

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0259.500TX913 Specifications

Manufacturer Part Number 0259.500TX913 Manufacturer Littelfuse Inc. Category Circuit Protection Beckrical, Specialty Fuses Package Radial, Can, Horizontal Series PICO? 259-UL913 Fuse Type Board Mount Current Rating 500mA Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Baseefa, UR Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageRadial, Can, HorizontalSeriesPICO? 259-UL913Fuse TypeBoard MountCurrent Rating500mAVoltage Rating - AC125VVoltage Rating - DC125VResponse Time-ApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsBaseefa, UROperating Temperature-55°C ~ 90°CBreaking Capacity @ Rated Voltage50A AC, 300A DCMounting TypeThrough HolePackage / CaseRadial, Can, HorizontalSize / Dimension0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Manufacturer Part Number	0259.500TX913
PackageRadial, Can, HorizontalSeriesPICO? 259-UL913Fuse TypeBoard MountCurrent Rating500mAVoltage Rating - AC125VVoltage Rating - DC125VResponse Time-ApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsBaseefa, UROperating Temperature-55°C ~ 90°CBreaking Capacity @ Rated Voltage50A AC, 300A DCMounting TypeThrough HolePackage / CaseRadial, Can, HorizontalSize / Dimension0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Manufacturer	Littelfuse Inc.
PackageRadial, Can, HorizontalSeriesPICO? 259-UL913Fuse TypeBoard MountCurrent Rating500mAVoltage Rating - AC125 VVoltage Rating - DC125 VResponse Time-ApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsBaseefa, UROperating Temperature-55°C ~ 90°CBreaking Capacity @ Rated Voltage50A AC, 300A DCMounting TypeThrough HolePackage / CaseRadial, Can, HorizontalSize / Dimension0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Category	Circuit Protection
SeriesPICO? 259-UL913Fuse TypeBoard MountCurrent Rating500mAVoltage Rating - AC125VVoltage Rating - DC125VResponse Time-ApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsBaseefa, UROperating Temperature-55°C ~ 90°CBreaking Capacity @ Rated Voltage50A AC, 300A DCMounting TypeThrough HolePackage / CaseRadial, Can, HorizontalSize / Dimension0.315" Dia x 0.512" L (8.00mm x 13.00mm)		Electrical, Specialty Fuses
Fuse TypeBoard MountCurrent Rating500mAVoltage Rating - AC125VVoltage Rating - DC125VResponse Time-ApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsBaseefa, UROperating Temperature-55°C ~ 90°CBreaking Capacity @ Rated Voltage50A AC, 300A DCMounting TypeThrough HolePackage / CaseRadial, Can, HorizontalSize / Dimension0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Package	Radial, Can, Horizontal
Current Rating Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Operating Temperature Baseefa, UR Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 500mA 125V 125V Response Time - Hazardous Locations Hazardous Locations Hazardous Locations Features - Through Safe - Through Hole Radial, Can, Horizontal 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Series	PICO? 259-UL913
Voltage Rating - AC Voltage Rating - DC 125V Response Time Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Baseefa, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Size / Dimension 125V 125V	Fuse Type	Board Mount
Voltage Rating - DC Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Baseefa, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 125V 125V	Current Rating	500mA
Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Baseefa, UR Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Voltage Rating - AC	125V
Applications Features Intrinsically Safe Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension Hazardous Locations Hazardous Locations Intrinsically Safe - Sofe Sase Sase AC, 300A Through Hole Radial, Can, Horizontal 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Voltage Rating - DC	125V
Features Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension Intrinsically Safe - Intrinsically Safe - Intrinsically Safe Saseefa, UR -55°C ~ 90°C 50A AC, 300A DC Through Hole Radial, Can, Horizontal 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Response Time	-
Class - Approvals Baseefa, UR Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Applications	Hazardous Locations
Approvals Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension Baseefa, UR -55°C ~ 90°C Through Hole 100	Features	Intrinsically Safe
Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Class	-
Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Approvals	Baseefa, UR
Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Operating Temperature	-55°C ~ 90°C
Package / Case Radial, Can, Horizontal Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Breaking Capacity @ Rated Voltage	50A AC, 300A DC
Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Mounting Type	Through Hole
	Package / Case	Radial, Can, Horizontal
Report errors?	Size / Dimension	0.315" Dia x 0.512" L (8.00mm x 13.00mm)
		Report errors?

0259.500TX913 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0259.500TX913 Payment Methods



















0259.500TX913 Shipping Methods













If you have any question about 0259.500TX913, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com