

0259.750M Information



For Reference Only

Part Number 0259.750M

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE BRD MNT 750MA 125VAC/VDC

Package Radial, Can, Horizontal

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0259.750M Specifications

ManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageRadial, Can, HorizontalSeries259Fuse TypeBoard MountCurrent Rating750mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsBaseefa, UROperating Temperature-55°C ~ 90°CBreaking Capacity @ Rated Voltage50A AC, 300A DCMounting TypeThrough Hole		
Category Circuit Protection Electrical, Specialty Fuses Radial, Can, Horizontal Series 259 Fuse Type Board Mount Current Rating 750mA Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Operating Temperature Baseefa, UR Operating Temperature Foal AC, 300A DC Mounting Type Circuit Protection Electrical, Specialty Fuses Radial, Can, Horizontal Fast Approvals Fast Approvals - 55°C ~ 90°C Breaking Capacity @ Rated Voltage Mounting Type Through Hole	Manufacturer Part Number	0259.750M
Package Radial, Can, Horizontal Series 259 Fuse Type Board Mount Current Rating 750mA Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Baseefa, UR Operating Temperature 50A AC, 300A DC Mounting Type Through Hole	Manufacturer	Littelfuse Inc.
PackageRadial, Can, HorizontalSeries259Fuse TypeBoard MountCurrent Rating750mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsBaseefa, UROperating Temperature-55°C ~ 90°CBreaking Capacity @ Rated Voltage50A AC, 300A DCMounting TypeThrough Hole	Category	Circuit Protection
Series259Fuse TypeBoard MountCurrent Rating750mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsBaseefa, UROperating Temperature-55°C ~ 90°CBreaking Capacity @ Rated Voltage50A AC, 300A DCMounting TypeThrough Hole		Electrical, Specialty Fuses
Fuse Type Current Rating 750mA Voltage Rating - AC 125V Voltage Rating - DC Response Time Fast Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Board Mount 750mA 125V 125V Response Time Fast Fast Approvals Baseefa, UR -55°C ~ 90°C Through Hole	Package	Radial, Can, Horizontal
Current Rating 750mA Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Baseefa, UR Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole	Series	259
Voltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsBaseefa, UROperating Temperature-55°C ~ 90°CBreaking Capacity @ Rated Voltage50A AC, 300A DCMounting TypeThrough Hole	Fuse Type	Board Mount
Voltage Rating - DC125VResponse TimeFastApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsBaseefa, UROperating Temperature-55°C ~ 90°CBreaking Capacity @ Rated Voltage50A AC, 300A DCMounting TypeThrough Hole	Current Rating	750mA
Response Time Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Baseefa, UR Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage Mounting Type Fast Hazardous Locations Hazardous Locations Features Intrinsically Safe - Safe Through Hole	Voltage Rating - AC	125V
Applications Features Intrinsically Safe Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Hazardous Locations Intrinsically Safe - Soft Through Hole	Voltage Rating - DC	125V
Features Intrinsically Safe Class - Approvals Baseefa, UR Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole	Response Time	Fast
Class - Approvals Baseefa, UR Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole	Applications	Hazardous Locations
Approvals Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage Mounting Type Baseefa, UR -55°C ~ 90°C 50A AC, 300A DC Through Hole	Features	Intrinsically Safe
Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole	Class	-
Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole	Approvals	Baseefa, UR
Mounting Type Through Hole	Operating Temperature	-55°C ~ 90°C
	Breaking Capacity @ Rated Voltage	50A AC, 300A DC
Package / Case Radial Can Horizontal	Mounting Type	Through Hole
rudial, Call, Horizontal	Package / Case	Radial, Can, Horizontal
Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Size / Dimension	0.315" Dia x 0.512" L (8.00mm x 13.00mm)
Report errors?		Report errors?

0259.750M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0259.750M Payment Methods





















0259.750M Shipping Methods













If you have any question about 0259.750M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com