



0259005.TX913 Information



For Reference Only

Part Number 0259005.TX913

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE BRD MNT 5A 125VAC/63VDC RAD

Package Radial, Can, Horizontal

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0259005.TX913 Specifications

Manufacturer Part Number 0259005.TX913 Manufacturer Littelfuse Inc. Category Circuit Protection Beckage Radial, Can, Horizontal Series PICO? 259-UL913 Fuse Type Board Mount Current Rating 5A Voltage Rating - AC 125V Voltage Rating - DC 63V Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Baseefa, UR Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Radial, Can, Horizontal Series PICO? 259-UL913 Fuse Type Board Mount Current Rating 5A Voltage Rating - AC 125V Voltage Rating - DC 63V Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Baseefa, UR Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Manufacturer Part Number	0259005.TX913
PackageRadial, Can, HorizontalSeriesPICO? 259-UL913Fuse TypeBoard MountCurrent Rating5AVoltage Rating - AC125VVoltage Rating - DC63VResponse Time-ApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsBaseefa, UROperating Temperature-55°C ~ 90°CBreaking Capacity @ Rated Voltage50A AC, 300A DCMounting TypeThrough HolePackage / CaseRadial, Can, HorizontalSize / Dimension0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Manufacturer	Littelfuse Inc.
PackageRadial, Can, HorizontalSeriesPICO? 259-UL913Fuse TypeBoard MountCurrent Rating5AVoltage Rating - AC125VVoltage Rating - DC63VResponse Time-ApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsBaseefa, UROperating Temperature-55°C ~ 90°CBreaking Capacity @ Rated Voltage50A AC, 300A DCMounting TypeThrough HolePackage / CaseRadial, Can, HorizontalSize / Dimension0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Category	Circuit Protection
SeriesPICO? 259-UL913Fuse TypeBoard MountCurrent Rating5AVoltage Rating - AC125VVoltage Rating - DC63VResponse Time-ApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsBaseefa, UROperating Temperature-55°C ~ 90°CBreaking Capacity @ Rated Voltage50A AC, 300A DCMounting TypeThrough HolePackage / CaseRadial, Can, HorizontalSize / Dimension0.315" Dia x 0.512" L (8.00mm x 13.00mm)		Electrical, Specialty Fuses
Fuse TypeBoard MountCurrent Rating5AVoltage Rating - AC125VVoltage Rating - DC63VResponse Time-ApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsBaseefa, UROperating Temperature-55°C ~ 90°CBreaking Capacity @ Rated Voltage50A AC, 300A DCMounting TypeThrough HolePackage / CaseRadial, Can, HorizontalSize / Dimension0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Package	Radial, Can, Horizontal
Current Rating Current Rating Voltage Rating - AC 125V Voltage Rating - DC 63V Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Operating Temperature Baseefa, UR Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Size / Dimension 5A A25V A25V A37V A37V	Series	PICO? 259-UL913
Voltage Rating - AC Voltage Rating - DC 63V Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Baseefa, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Size / Dimension 125V 63V 63V 63V 63V 63V 63V 63V 6	Fuse Type	Board Mount
Voltage Rating - DC Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Baseefa, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 63V 63V 63V 63V 648 Faxion Fax	Current Rating	5A
Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Baseefa, UR Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Voltage Rating - AC	125V
Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Baseefa, UR Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Voltage Rating - DC	63V
Features Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension Intrinsically Safe - Intrinsically Safe Num - Sase Sase Sase Sase Sase Sase Sase Sase	Response Time	-
Class Approvals Baseefa, UR Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension -35°C ~ 90°C Through Hole 100 Through Hole	Applications	Hazardous Locations
Approvals Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension Baseefa, UR -55°C ~ 90°C Through Hole 100	Features	Intrinsically Safe
Operating Temperature -55°C ~ 90°C Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Class	-
Breaking Capacity @ Rated Voltage 50A AC, 300A DC Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Approvals	Baseefa, UR
Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Operating Temperature	-55°C ~ 90°C
Package / Case Radial, Can, Horizontal Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Breaking Capacity @ Rated Voltage	50A AC, 300A DC
Size / Dimension 0.315" Dia x 0.512" L (8.00mm x 13.00mm)	Mounting Type	Through Hole
	Package / Case	Radial, Can, Horizontal
Report errors?	Size / Dimension	0.315" Dia x 0.512" L (8.00mm x 13.00mm)
		Report errors?

0259005.TX913 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0259005.TX913 Payment Methods



















0259005.TX913 Shipping Methods













If you have any question about 0259005.TX913, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com