

02CO025.Z Information

Manufacturer Littelfuse Inc. Category Heisener.com

Circuit Protection Electrical, Specialty Fuses

Description FUSE CARTRIDGE 25A 600VAC/250VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

Part Number 02CO025.Z

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









02CO025.Z Specifications

Manufacturer Part Number02C0025.ZManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesHRCII-CFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeSlowApplicationsMotor ProtectionFeatures-Class-ApprovalsCSAOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 80kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.827" Dia x 2.205" L (21.00mm x 56.00mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series HRCII-C Fuse Type Cartridge Current Rating 25A Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Motor Protection Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Specialty Fuses Sive / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Specialty Fuses Selection Electrical, Specialty Electrical Electrical Electrical	Manufacturer Part Number	02CO025.Z
Beckage Cylindrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series HRCII-C Fuse Type Cartridge Current Rating 25A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Motor Protection Features - Class - Approvals CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 80kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.205" L (21.00mm x 56.00mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesHRCII-CFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeSlowApplicationsMotor ProtectionFeatures-Class-ApprovalsCSAOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 80kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.827" Dia x 2.205" L (21.00mm x 56.00mm)	Category	Circuit Protection
SeriesHRCII-CFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeSlowApplicationsMotor ProtectionFeatures-Class-ApprovalsCSAOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 80kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.827" Dia x 2.205" L (21.00mm x 56.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 25A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Motor Protection Features - Class - Approvals CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Canon Canon Cartridge Capacity @ Cartridge Capacity @ Cartridge Capacity @	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Motor Protection Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 250V Response Time Slow Anotor Protection CSA COSA CSA CSA Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.205" L (21.00mm x 56.00mm)	Series	HRCII-C
Voltage Rating - AC Voltage Rating - DC 250V Response Time Slow Applications Motor Protection Features - Class - Approvals CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 600V 6	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Motor Protection Features - Class - Approvals CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Slow Mounting Type Slow Advice Slow Slow Advice Slow Slow Advice Slow Slow Advice Slow Slow Slow Slow Acy 80kA DC Slow Slow Slow Slow Slow Slow Slow Slow	Current Rating	25A
Response Time Slow Applications Motor Protection Features - Class - Approvals CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 80kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.205" L (21.00mm x 56.00mm)	Voltage Rating - AC	600V
Applications Motor Protection Features - Class - Approvals CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 80kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.205" L (21.00mm x 56.00mm)	Voltage Rating - DC	250V
Features - Class - CSA Approvals CSA Operating Temperature - CSA Breaking Capacity @ Rated Voltage 200kA AC, 80kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.205" L (21.00mm x 56.00mm)	Response Time	Slow
Class - CSA Operating Temperature - Consider a Constant of the	Applications	Motor Protection
Approvals CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CSA CUSA CUSA	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.205" L (21.00mm x 56.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 80kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.205" L (21.00mm x 56.00mm)	Approvals	CSA
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.205" L (21.00mm x 56.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.827" Dia x 2.205" L (21.00mm x 56.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 80kA DC
Size / Dimension 0.827" Dia x 2.205" L (21.00mm x 56.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.827" Dia x 2.205" L (21.00mm x 56.00mm)
		Report errors?

02CO025.Z Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

02CO025.Z Payment Methods



















02CO025.Z Shipping Methods













If you have any question about 02CO025.Z, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com