

### 02CO060.Z Information

Part Number 02CO060.Z Manufacturer Littelfuse Inc. Category Circuit Protection Heisener.com

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 60A 600VAC/250VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 02CO060.Z Specifications

| Manufacturer Part Number02CO060.ZManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesHRCII-CFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeSlowApplicationsMotor ProtectionFeatures-Class-ApprovalsCSAOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 80kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.024" Dia x 2.244" L (26.00mm x 57.00mm)Report errors?   |                                   |   |
|--|-----------------------------------|---|
| Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cylindrical, Blade Terminal (Bolt)  Series  HRCII-C  Fuse Type  Cartridge  Current Rating  60A  Voltage Rating - AC  600V  Voltage Rating - DC  250V  Response Time  Slow  Applications  Motor Protection  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  1.024" Dia x 2.244" L (26.00mm x 57.00mm)  | Manufacturer Part Number          | 02CO060.Z                                 |
| Flectrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt) Series HRCII-C Fuse Type Cartridge Current Rating 60A Voltage Rating - AC Voltage Rating - DC Slow Applications Motor Protection Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Fleetures Cylindrical, Blade Terminal (Bolt) Size / Dimension  | Manufacturer                      | Littelfuse Inc.                           |
| Package Cylindrical, Blade Terminal (Bolt)  Series HRCII-C  Fuse Type Cartridge  Current Rating 60A  Voltage Rating - AC 600V  Voltage Rating - DC 250V  Response Time Slow  Applications Motor Protection  Features -  Class -  Approvals CSA  Operating Temperature -  Breaking Capacity @ Rated Voltage 200kA AC, 80kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.024" Dia x 2.244" L (26.00mm x 57.00mm)  | Category                          | Circuit Protection                        |
| Series HRCII-C Fuse Type Cartridge Current Rating 60A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Motor Protection Features - Class - Approvals CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 80kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.024" Dia x 2.244" L (26.00mm x 57.00mm)  |                                   | Electrical, Specialty Fuses               |
| Fuse Type Current Rating 60A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Motor Protection Features - Class - Approvals CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Current Rating 60A 60A 60B  Move CSOV  Response Time CSOV  Motor Protection  CSA  - CSA  CSA  Cylindrical, Blade Terminal (Bolt) Size / Dimension  Cartridge 60A  60A 60B  COV  60B  COV  80B  Cov   | Package                           | Cylindrical, Blade Terminal (Bolt)        |
| Current Rating  Voltage Rating - AC  600V  Voltage Rating - DC  250V  Response Time  Slow  Applications  Motor Protection  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  600A  600V  60 | Series                            | HRCII-C                                   |
| Voltage Rating - AC  Voltage Rating - DC  250V  Response Time  Slow  Applications  Motor Protection  Features  - Class  - Approvals  CSA  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  600V  250V  600V  250V  600V  6 | Fuse Type                         | Cartridge                                 |
| Voltage Rating - DC  Response Time Slow  Applications Motor Protection  Features - Class - Approvals CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Slow Motor Protection  CSA COMMOUNT Protection  - CSA CSA CYBA CSA CYBA CYBA CYBA CYBA CYBA CYBA CYBA CYB   | Current Rating                    | 60A                                       |
| Response Time Applications Motor Protection  Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Slow Motor Protection  CSA  | Voltage Rating - AC               | 600V                                      |
| Applications Motor Protection  Features - Class - Approvals CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 80kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.024" Dia x 2.244" L (26.00mm x 57.00mm)  | Voltage Rating - DC               | 250V                                      |
| Features - Class - CSA Approvals CSA Operating Temperature - CSA Breaking Capacity @ Rated Voltage 200kA AC, 80kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.024" Dia x 2.244" L (26.00mm x 57.00mm)   | Response Time                     | Slow                                      |
| Class - CSA Operating Temperature - Seraking Capacity @ Rated Voltage 200kA AC, 80kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.024" Dia x 2.244" L (26.00mm x 57.00mm)  | Applications                      | Motor Protection                          |
| Approvals  CSA  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  CSA  CUSA  CUSA | Features                          | -   |
| Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  1.024" Dia x 2.244" L (26.00mm x 57.00mm)   | Class                             | -   |
| Breaking Capacity @ Rated Voltage 200kA AC, 80kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.024" Dia x 2.244" L (26.00mm x 57.00mm)   | Approvals                         | CSA                                       |
| Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  1.024" Dia x 2.244" L (26.00mm x 57.00mm)   | Operating Temperature             | -   |
| Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.024" Dia x 2.244" L (26.00mm x 57.00mm)   | Breaking Capacity @ Rated Voltage | 200kA AC, 80kA DC                         |
| Size / Dimension 1.024" Dia x 2.244" L (26.00mm x 57.00mm)   | Mounting Type                     | Bolt Mount                                |
|  | Package / Case                    | Cylindrical, Blade Terminal (Bolt)        |
| Report errors?   | Size / Dimension                  | 1.024" Dia x 2.244" L (26.00mm x 57.00mm) |
|  |                                   | Report errors?                            |

#### 02CO060.Z Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 02CO060.Z Payment Methods



















### 02CO060.Z Shipping Methods













If you have any question about 02CO060.Z, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com