

0305.050M Information



For Reference Only

Part Number 0305.050M

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE BRD MNT 50MA 277VAC/VDC RAD

Package Radial, Can, Horizontal

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0305.050M Specifications

Manufacturer Part Number0305.050MManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageRadial, Can, HorizontalSeriesPICO? 305Fuse TypeBoard MountCurrent Rating50mAVoltage Rating - AC277VVoltage Rating - DC277VResponse Time-ApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsATEX, cURus, IECEXOperating Temperature-40°C ~ 50°CBreaking Capacity @ Rated Voltage1.5kAMounting TypeThrough HolePackage / CaseRadial, Can, HorizontalSize / Dimension0.354" Dia x 0.614" L (9.00mm x 15.60mm)Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Radial, Can, Horizontal Package Radial, Can, Horizontal PICO? 305 Fuse Type Board Mount Current Rating 50mA Voltage Rating - AC 277V Voltage Rating - DC 277V Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals ATEX, cURus, IECEX Operating Temperature Breaking Capacity @ Rated Voltage Nounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension Circuit Protection Electrical, Specialty Fuses Radial, Can, Horizontal Size / Dimension	Manufacturer Part Number	0305.050M
Electrical, Specialty Fuses Package Radial, Can, Horizontal PICO? 305 Fuse Type Board Mount Current Rating 50mA Voltage Rating - AC 277V Voltage Rating - DC 277V Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals ATEX, cURus, IECEx Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial, Can, Horizontal Electrical, Specialty Fuses Radial, Can, Horizontal Electrical, Specialty Fuses Radial, Can, Horizontal O.354" Dia x 0.614" L (9.00mm x 15.60mm)	Manufacturer	Littelfuse Inc.
PackageRadial, Can, HorizontalSeriesPICO? 305Fuse TypeBoard MountCurrent Rating50mAVoltage Rating - AC277VVoltage Rating - DC277VResponse Time-ApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsATEX, cURus, IECEXOperating Temperature-40°C ~ 50°CBreaking Capacity @ Rated Voltage1.5kAMounting TypeThrough HolePackage / CaseRadial, Can, HorizontalSize / Dimension0.354" Dia x 0.614" L (9.00mm x 15.60mm)	Category	Circuit Protection
SeriesPICO? 305Fuse TypeBoard MountCurrent Rating50mAVoltage Rating - AC277VVoltage Rating - DC277VResponse Time-ApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsATEX, cURus, IECExOperating Temperature-40°C ~ 50°CBreaking Capacity @ Rated Voltage1.5kAMounting TypeThrough HolePackage / CaseRadial, Can, HorizontalSize / Dimension0.354" Dia x 0.614" L (9.00mm x 15.60mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 50mA Voltage Rating - AC 277V Voltage Rating - DC 277V Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals ATEX, cURus, IECEX Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension Soma Soma Mount 50mA Mount 50mA ATEX 60mA ATEX 60mA 60m	Package	Radial, Can, Horizontal
Current Rating 50mA Voltage Rating - AC 277V Voltage Rating - DC 277V Response Time Applications Hazardous Locations Features Intrinsically Safe Class Approvals ATEX, cURus, IECEX Operating Temperature -40°C ~ 50°C Breaking Capacity @ Rated Voltage 1.5kA Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.354" Dia x 0.614" L (9.00mm x 15.60mm)	Series	PICO? 305
Voltage Rating - AC Voltage Rating - DC 277V Response Time Applications Hazardous Locations Features Intrinsically Safe Class - Approvals ATEX, cURus, IECEX Operating Temperature Breaking Capacity @ Rated Voltage Through Hole Package / Case Size / Dimension 277V 277V 277V ATRICAL STATE APPOVA ATEX, cURus, IECEX -40°C ~ 50°C Through Hole Radial, Can, Horizontal Size / Dimension 0.354" Dia x 0.614" L (9.00mm x 15.60mm)	Fuse Type	Board Mount
Voltage Rating - DC Response Time Applications Hazardous Locations Features Intrinsically Safe Class - Approvals ATEX, cURus, IECEX Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 277V ADA TO	Current Rating	50mA
Response Time Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension - Approvals -40°C ~ 50°C Through Hole Radial, Can, Horizontal 0.354" Dia x 0.614" L (9.00mm x 15.60mm)	Voltage Rating - AC	277V
Applications Features Intrinsically Safe Class - Approvals Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension Hazardous Locations Hazardous Locations Hazardous Locations Hazardous Locations Hazardous Locations Freatures Thrinisically Safe - The URus, IECEx -40°C ~ 50°C Through Hole 1.5kA Mounting Type Through Hole Package / Case Radial, Can, Horizontal 0.354" Dia x 0.614" L (9.00mm x 15.60mm)	Voltage Rating - DC	277V
Features Class - Approvals Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension Intrinsically Safe - Intrinsically Safe ATEX, cURus, IECEx -40°C ~ 50°C Through Hole 1.5kA Through Hole Package / Case Radial, Can, Horizontal 0.354" Dia x 0.614" L (9.00mm x 15.60mm)	Response Time	-
Class Approvals ATEX, cURus, IECEx Operating Temperature -40°C ~ 50°C Breaking Capacity @ Rated Voltage 1.5kA Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension -40°C ~ 50°C Through Hole 1.5kA Through Hole Package / Case Radial, Can, Horizontal 0.354" Dia x 0.614" L (9.00mm x 15.60mm)	Applications	Hazardous Locations
Approvals ATEX, cURus, IECEx Operating Temperature -40°C ~ 50°C Breaking Capacity @ Rated Voltage 1.5kA Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension O.354" Dia x 0.614" L (9.00mm x 15.60mm)	Features	Intrinsically Safe
Operating Temperature -40°C ~ 50°C Breaking Capacity @ Rated Voltage 1.5kA Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.354" Dia x 0.614" L (9.00mm x 15.60mm)	Class	-
Breaking Capacity @ Rated Voltage 1.5kA Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.354" Dia x 0.614" L (9.00mm x 15.60mm)	Approvals	ATEX, cURus, IECEx
Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.354" Dia x 0.614" L (9.00mm x 15.60mm)	Operating Temperature	-40°C ~ 50°C
Package / Case Radial, Can, Horizontal Size / Dimension 0.354" Dia x 0.614" L (9.00mm x 15.60mm)	Breaking Capacity @ Rated Voltage	1.5kA
Size / Dimension 0.354" Dia x 0.614" L (9.00mm x 15.60mm)	Mounting Type	Through Hole
	Package / Case	Radial, Can, Horizontal
Report errors?	Size / Dimension	0.354" Dia x 0.614" L (9.00mm x 15.60mm)
		Report errors?

0305.050M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0305.050M Payment Methods


































If you have any question about 0305.050M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com