

0305.100M Information



For Reference Only

Part Number 0305.100M
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE BRD MNT 100MA 277VAC/VDC

Package Radial, Can, Horizontal

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0305.100M Specifications

| Manufacturer Part Number Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Radial, Can, Horizontal Series PICO? 305 Fuse Type Board Mount Current Rating 100mA Voltage Rating - AC Voltage Rating - DC Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals ATEX, cURus, IECEx Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.354" Dia x 0.614" L (9.00mm x 15.60mm) | | |
|--|-----------------------------------|--|
| Category Circuit Protection Electrical, Specialty Fuses Radial, Can, Horizontal Series PICO? 305 Fuse Type Board Mount Current Rating 100mA Voltage Rating - AC 277V Voltage Rating - DC 277V Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals ATEX, cURus, IECEX Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension Circuit Protection Electrical, Specialty Fuses Radial, Can, Horizontal Size / Dimension | Manufacturer Part Number | 0305.100M |
| Beckage Radial, Can, Horizontal Series PICO? 305 Fuse Type Board Mount Current Rating 100mA Voltage Rating - AC 277V Voltage Rating - DC 277V Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - APPROVAIS ATEX, cURUS, IECEX Operating Temperature -40°C ~ 50°C Breaking Capacity @ Rated Voltage Ackage / Case Radial, Can, Horizontal Size / Dimension 0.354" Dia x 0.614" L (9.00mm x 15.60mm) | Manufacturer | Littelfuse Inc. |
| PackageRadial, Can, HorizontalSeriesPICO? 305Fuse TypeBoard MountCurrent Rating100mAVoltage Rating - AC277VVoltage Rating - DC277VResponse Time-ApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsATEX, cURus, IECEXOperating Temperature-40°C ~ 50°CBreaking Capacity @ Rated Voltage1.5kAMounting TypeThrough HolePackage / CaseRadial, Can, HorizontalSize / Dimension0.354" Dia x 0.614" L (9.00mm x 15.60mm) | Category | Circuit Protection |
| SeriesPICO? 305Fuse TypeBoard MountCurrent Rating100mAVoltage Rating - AC277VVoltage Rating - DC277VResponse Time-ApplicationsHazardous LocationsFeaturesIntrinsically SafeClass-ApprovalsATEX, cURus, IECExOperating Temperature-40°C ~ 50°CBreaking Capacity @ Rated Voltage1.5kAMounting TypeThrough HolePackage / CaseRadial, Can, HorizontalSize / Dimension0.354" Dia x 0.614" L (9.00mm x 15.60mm) | | Electrical, Specialty Fuses |
| Fuse Type Current Rating 100mA Voltage Rating - AC 277V Voltage Rating - DC 277V Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals ATEX, cURus, IECEX Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Size / Dimension Board Mount 100mA ATOMA ATOMA Mount 100mA Hazardous Locations Hazardous Locations Hazardous Locations ATEX current 100mA ATEX curren | Package | Radial, Can, Horizontal |
| Current Rating Voltage Rating - AC 277V Voltage Rating - DC 277V Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Size / Dimension 100mA 100m 100mA 100mA 100m 100mA 100m 100mA 100m | Series | PICO? 305 |
| Voltage Rating - AC Voltage Rating - DC 277V Response Time Applications Hazardous Locations Features Intrinsically Safe Class - Approvals ATEX, cURus, IECEX Operating Temperature Breaking Capacity @ Rated Voltage 1.5kA Mounting Type Through Hole Package / Case Size / Dimension 277V 277V ATRIVED AND ACC ACC ACC ACC ACC ACC ACC ACC ACC AC | Fuse Type | Board Mount |
| Voltage Rating - DC Response Time - Applications Hazardous Locations Features Intrinsically Safe Class - Approvals ATEX, cURus, IECEX Operating Temperature Breaking Capacity @ Rated Voltage 1.5kA Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 277V Aprovals - Class - ATEX, cURus, IECEX - AO°C ~ 50°C - Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.354" Dia x 0.614" L (9.00mm x 15.60mm) | Current Rating | 100mA |
| Response Time Applications Hazardous Locations Features Intrinsically Safe Class - Approvals Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension - Approvals - ATEX, cURus, IECEX - 40°C ~ 50°C Through Hole Radial, Can, Horizontal 0.354" Dia x 0.614" L (9.00mm x 15.60mm) | Voltage Rating - AC | 277V |
| Applications Hazardous Locations Features Intrinsically Safe Class - Approvals ATEX, cURus, IECEx Operating Temperature -40°C ~ 50°C Breaking Capacity @ Rated Voltage 1.5kA Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.354" Dia x 0.614" L (9.00mm x 15.60mm) | Voltage Rating - DC | 277V |
| Features Class -Approvals Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension Intrinsically Safe -40°C ~ 50°C ATEX, cURus, IECEx -40°C ~ 50°C Through Hole 1.5kA Through Hole Package / Case Radial, Can, Horizontal 0.354" Dia x 0.614" L (9.00mm x 15.60mm) | Response Time | - |
| Class - Approvals ATEX, cURus, IECEx Operating Temperature -40°C ~ 50°C Breaking Capacity @ Rated Voltage 1.5kA Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.354" Dia x 0.614" L (9.00mm x 15.60mm) | Applications | Hazardous Locations |
| Approvals ATEX, cURus, IECEx Operating Temperature -40°C ~ 50°C Breaking Capacity @ Rated Voltage 1.5kA Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension O.354" Dia x 0.614" L (9.00mm x 15.60mm) | Features | Intrinsically Safe |
| Operating Temperature -40°C ~ 50°C Breaking Capacity @ Rated Voltage 1.5kA Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.354" Dia x 0.614" L (9.00mm x 15.60mm) | Class | - |
| Breaking Capacity @ Rated Voltage 1.5kA Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.354" Dia x 0.614" L (9.00mm x 15.60mm) | Approvals | ATEX, cURus, IECEx |
| Mounting Type Through Hole Package / Case Radial, Can, Horizontal Size / Dimension 0.354" Dia x 0.614" L (9.00mm x 15.60mm) | Operating Temperature | -40°C ~ 50°C |
| Package / Case Radial, Can, Horizontal Size / Dimension 0.354" Dia x 0.614" L (9.00mm x 15.60mm) | Breaking Capacity @ Rated Voltage | 1.5kA |
| Size / Dimension 0.354" Dia x 0.614" L (9.00mm x 15.60mm) | Mounting Type | Through Hole |
| | Package / Case | Radial, Can, Horizontal |
| Report errors? | Size / Dimension | 0.354" Dia x 0.614" L (9.00mm x 15.60mm) |
| | | Report errors? |

0305.100M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0305.100M Payment Methods





















0305.100M Shipping Methods













If you have any question about 0305.100M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com