



0313003.VXIDP Information

Heisener.com

Part Number0313003.VXIDPManufacturerLittelfuse Inc.CategoryCircuit Protection

Fuses

Description FUSE GLASS 3A 250VAC 3AB 3AG

Package 3AB, 3AG, 1/4" x 1-1/4"

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0313003.VXIDP Specifications

Manufacturer Part Number 0313003.VXIDP Manufacturer Littelfuse Inc. Category Circuit Protection Package 3AB, 3AG, 1/4" x 1-1/4" Series 313 Fuse Type Cartridge, Glass Current Rating 3A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting 12t 200 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	•	
Category Circuit Protection Fuses Package 3AB, 3AG, 1/4" x 1-1/4" Series 313 Fuse Type Cartridge, Glass Current Rating 3A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting 12t 200 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Manufacturer Part Number	0313003.VXIDP
Fuses Package 3AB, 3AG, 1/4" x 1-1/4" Series 313 Fuse Type Cartridge, Glass Current Rating 3A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 200 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Manufacturer	Littelfuse Inc.
Package 3AB, 3AG, 1/4" x 1-1/4" Series 313 Fuse Type Cartridge, Glass Current Rating 3A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 200 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Category	Circuit Protection
Series 313 Fuse Type Cartridge, Glass Current Rating 3A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 200 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)		Fuses
Fuse Type Current Rating 3A Voltage Rating - AC 250V Voltage Rating - DC Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t 200 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension Cartridge, Glass 3A Cartridge, Glass CAB AB CAB CAB CAB CAB CAB CAB CAB CAB	Package	3AB, 3AG, 1/4" x 1-1/4"
Current Rating 3A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 200 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Series	313
Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 200 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Fuse Type	Cartridge, Glass
Voltage Rating - DC Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t 200 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension - Slow 3AB, 3AG, 1/4" x 1-1/4" Looperating Temperature -55°C ~ 125°C - Size / Dimension - Slow 3AB, 3AG, 1/4" x 1-1/4" Looperating Temperature -500	Current Rating	3A
Response Time Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t 200 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension Slow 3AB, 3AG, 1/4" x 1-1/4" Holder CE, CSA, KC, PSE, UL -55°C ~ 125°C	Voltage Rating - AC	250V
Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 100A Melting I2t 200 Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension 3AB, 3AG, 1/4" x 1-1/4" Holder 100A 200 CE, CSA, KC, PSE, UL -55°C ~ 125°C	Voltage Rating - DC	-
Mounting TypeHolderBreaking Capacity @ Rated Voltage100AMelting I2t200ApprovalsCE, CSA, KC, PSE, ULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Response Time	Slow
Breaking Capacity @ Rated Voltage Melting I2t Approvals CE, CSA, KC, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension 100A CE, CSA, KC, PSE, UL -55°C ~ 125°C - 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Package / Case	3AB, 3AG, 1/4" x 1-1/4"
Melting I2t200ApprovalsCE, CSA, KC, PSE, ULOperating Temperature -55° C $\sim 125^{\circ}$ CColor-Size / Dimension0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Mounting Type	Holder
Approvals CE, CSA, KC, PSE, UL Operating Temperature -55° C $\sim 125^{\circ}$ C Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Breaking Capacity @ Rated Voltage	100A
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Melting I2t	200
Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Approvals	CE, CSA, KC, PSE, UL
Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Operating Temperature	-55°C ~ 125°C
	Color	-
Report errors?	Size / Dimension	0.250" Dia x 1.250" L (6.35mm x 31.75mm)
		Report errors?

0313003.VXIDP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0313003.VXIDP Payment Methods



















0313003.VXIDP Shipping Methods













If you have any question about 0313003.VXIDP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com