



0313007.HXIDP Information



For Reference Only

Part Number 0313007.HXIDP
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

Description FUSE GLASS 7A 250VAC 3AB 3AG

Package 3AB, 3AG, 1/4" x 1-1/4"

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0313007.HXIDP Specifications

Manufacturer Part Number 0313007.HXIDP Manufacturer Littelfuse Inc. Category Circuit Protection Fuses 3AB, 3AG, 1/4" x 1-1/4" Series 313 Fuse Type Cartridge, Glass Current Rating 7A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 200A Melting 12t 347 Approvals CE, CSA, K-MARK, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	•	
Category Circuit Protection Fuses Package 3AB, 3AG, 1/4" x 1-1/4" Series 313 Fuse Type Cartridge, Glass Current Rating 7A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 200A Melting I2t 347 Approvals CE, CSA, K-MARK, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Manufacturer Part Number	0313007.HXIDP
Fuses Package 3AB, 3AG, 1/4" x 1-1/4" Series 313 Fuse Type Cartridge, Glass Current Rating 7A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 200A Melting 12t 347 Approvals CE, CSA, K-MARK, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Manufacturer	Littelfuse Inc.
Package 3AB, 3AG, 1/4" x 1-1/4" Series 313 Fuse Type Cartridge, Glass Current Rating 7A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 200A Melting I2t 347 Approvals CE, CSA, K-MARK, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Category	Circuit Protection
Series 313 Fuse Type Cartridge, Glass Current Rating 7A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 200A Melting I2t 347 Approvals CE, CSA, K-MARK, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)		Fuses
Fuse Type Current Rating 7A Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t Approvals CE, CSA, K-MARK, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension Cartridge, Glass 7A Cartridge, Glass 7A Cartridge, Glass 7A Cartridge, Glass 7A CE, CSA COV - Color - Size / Dimension Capacity @ Cartridge, Glass 7A CE, CSA Cartridge, Glass 7A CARTRIDATE CE, CSA COV Color Cattridge, Glass 7A CE, CSA Color Cattridge, Glass 7A CE, CSA Cattridge, Glass 7A CE, CSA Color Color Cattridge, Glass 7A CARTRIDATE COLOR Color Cattridge, Glass 7A CARTRIDATE COLOR COLOR COLOR COLOR CARTRIDATE CARTRIDATE CARTRIDATE COLOR COL	Package	3AB, 3AG, 1/4" x 1-1/4"
Current Rating 7A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 200A Melting I2t 347 Approvals CE, CSA, K-MARK, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Series	313
Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage Melting 12t Approvals CE, CSA, K-MARK, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension 250V ABOVE CINCOLUMN CE, CSA, K-MARK, PSE, UL COLOT COLOT COLOT O.250" Dia x 1.250" L (6.35mm x 31.75mm)	Fuse Type	Cartridge, Glass
Voltage Rating - DC Response Time Slow Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t Approvals CE, CSA, K-MARK, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension - Size / Dimension Slow - Slow 3AB, 3AG, 1/4" x 1-1/4" COOR 400 COOR - Slow - S	Current Rating	7A
Response Time Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage Melting I2t Approvals CE, CSA, K-MARK, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension Slow 3AB, 3AG, 1/4" x 1-1/4" Holder 200A CE, CSA, K-MARK, PSE, UL -55°C ~ 125°C	Voltage Rating - AC	250V
Package / Case 3AB, 3AG, 1/4" x 1-1/4" Mounting Type Holder Breaking Capacity @ Rated Voltage 200A Melting I2t Approvals CE, CSA, K-MARK, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension 3AB, 3AG, 1/4" x 1-1/4" Holder 200A 200A 347 CE, CSA, K-MARK, PSE, UL -55°C ~ 125°C - 125°C	Voltage Rating - DC	-
Mounting TypeHolderBreaking Capacity @ Rated Voltage200AMelting I2t347ApprovalsCE, CSA, K-MARK, PSE, ULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Response Time	Slow
Breaking Capacity @ Rated Voltage Melting I2t Approvals CE, CSA, K-MARK, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension 200A 347 CE, CSA, K-MARK, PSE, UL -55°C ~ 125°C 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Package / Case	3AB, 3AG, 1/4" x 1-1/4"
Melting I2t347ApprovalsCE, CSA, K-MARK, PSE, ULOperating Temperature -55° C ~ 125° CColor-Size / Dimension0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Mounting Type	Holder
Approvals CE, CSA, K-MARK, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension CE, CSA, K-MARK, PSE, UL -55°C ~ 125°C 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Breaking Capacity @ Rated Voltage	200A
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Melting I2t	347
Color - Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Approvals	CE, CSA, K-MARK, PSE, UL
Size / Dimension 0.250" Dia x 1.250" L (6.35mm x 31.75mm)	Operating Temperature	-55°C ~ 125°C
	Color	-
Report errors?	Size / Dimension	0.250" Dia x 1.250" L (6.35mm x 31.75mm)
		Report errors?

0313007.HXIDP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0313007.HXIDP Payment Methods



















0313007.HXIDP Shipping Methods













If you have any question about 0313007.HXIDP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com