



0324012.MXSPP Information

Heisener.com

For Reference Only

Part Number0324012.MXSPPManufacturerLittelfuse Inc.CategoryCircuit Protection

Fuses

Description FUSE 250V 3AB FA SINGLE PGT 12A

Package 3AB, 3AG, 1/4" x 1-1/4" (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0324012.MXSPP Specifications

Manufacturer Part Number 0324012.MXSPP Manufacturer Littelfuse Inc. Category Circuit Protection Fuses Package 3AB, 3AG, 1/4" x 1-1/4" (Axial) Series 324 Fuse Type Cartridge, Ceramic Current Rating 12A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 750A Melting 12t 570 Approvals CE, CSA, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm) Report errors?	•	
Category Circuit Protection Fuses Package 3AB, 3AG, 1/4" x 1-1/4" (Axial) Series 324 Fuse Type Cartridge, Ceramic Current Rating 12A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 750A Melting I2t 570 Approvals CE, CSA, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Manufacturer Part Number	0324012.MXSPP
Fuses 3AB, 3AG, 1/4" x 1-1/4" (Axial) Series 324 Fuse Type	Manufacturer	Littelfuse Inc.
Package 3AB, 3AG, 1/4" x 1-1/4" (Axial) Series 324 Fuse Type Cartridge, Ceramic Current Rating 12A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 750A Melting I2t 570 Approvals CE, CSA, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Category	Circuit Protection
Series 324 Fuse Type Cartridge, Ceramic Current Rating 12A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 750A Melting I2t 570 Approvals CE, CSA, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)		Fuses
Fuse Type Current Rating 12A Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 570 Approvals CE, CSA, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension Cartridge, Ceramic 12A Cartridge, Ceramic 12A 250V CHA Cartridge, Ceramic 12A 250V CE, CSA Color Cartridge, Ceramic 12A 12A 12A 12A 12A 12A 12B 12B	Package	3AB, 3AG, 1/4" x 1-1/4" (Axial)
Current Rating 12A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 750A Melting I2t 570 Approvals CE, CSA, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Series	324
Voltage Rating - AC Voltage Rating - DC Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 750A Melting 12t 570 Approvals CE, CSA, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension 250V - 250V ARA CE, CSA 250V - 250V	Fuse Type	Cartridge, Ceramic
Voltage Rating - DC Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 750A Melting I2t 570 Approvals CE, CSA, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension Past OAB, 3AG, 1/4" x 1-1/4" (Axial) Choose 1 Color -55°C ~ 125°C O.275" Dia x 1.288" L (6.99mm x 32.72mm)	Current Rating	12A
Response Time Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 750A Melting I2t 570 Approvals CE, CSA, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension Fast 0AB, 3AG, 1/4" x 1-1/4" (Axial) Chouse 1 CE, CSA, PSE, UL CE, CSA, PSE, UL CST, CSA	Voltage Rating - AC	250V
Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 750A Melting I2t 570 Approvals CE, CSA, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension 3AB, 3AG, 1/4" x 1-1/4" (Axial) Through Hole 750A 750A 62, CSA, PSE, UL 750 750 750 750 750 750 750 75	Voltage Rating - DC	-
Mounting Type Breaking Capacity @ Rated Voltage 750A Melting I2t 570 Approvals CE, CSA, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension Through Hole 750A 750A 750 628, PSE, UL 750°C 7	Response Time	Fast
Breaking Capacity @ Rated Voltage 750A Melting I2t 570 Approvals CE, CSA, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Package / Case	3AB, 3AG, 1/4" x 1-1/4" (Axial)
Melting I2t 570 Approvals CE, CSA, PSE, UL Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Mounting Type	Through Hole
Approvals CE, CSA, PSE, UL Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Breaking Capacity @ Rated Voltage	750A
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Melting I2t	570
Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Approvals	CE, CSA, PSE, UL
Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Operating Temperature	-55°C ~ 125°C
` '	Color	-
Report errors?	Size / Dimension	0.275" Dia x 1.288" L (6.99mm x 32.72mm)
		Report errors?

0324012.MXSPP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0324012.MXSPP Payment Methods



















0324012.MXSPP Shipping Methods













If you have any question about 0324012.MXSPP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com