



0388030.MXEP Information

Heisener.com

Part Number 0388030.MXEP
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

Description FUSE GLASS 30A 250VAC 3AB 3AG

Package 3AB, 3AG, 1/4" x 1-1/4" (Axial)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0388030.MXEP Specifications

Manufacturer Part Number 0388030.MXEP Manufacturer Littelfuse Inc. Category Circuit Protection Package 3AB, 3AG, 1/4" x 1-1/4" (Axial) Series 388 Fuse Type Cartridge, Glass Current Rating 30A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting 12t 7531 Approvals CE, K-MARK, PSE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)		
Category Circuit Protection Fuses Package 3AB, 3AG, 1/4" x 1-1/4" (Axial) Series 388 Fuse Type Cartridge, Glass Current Rating 30A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 7531 Approvals CE, K-MARK, PSE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Manufacturer Part Number	0388030.MXEP
Fuses Package 3AB, 3AG, 1/4" x 1-1/4" (Axial) Series 388 Fuse Type Cartridge, Glass Current Rating 30A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting 12t 7531 Approvals CE, K-MARK, PSE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Manufacturer	Littelfuse Inc.
Package 3AB, 3AG, 1/4" x 1-1/4" (Axial) Series 388 Fuse Type Cartridge, Glass Current Rating 30A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 7531 Approvals CE, K-MARK, PSE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Category	Circuit Protection
Series 388 Fuse Type Cartridge, Glass Current Rating 30A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 7531 Approvals CE, K-MARK, PSE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)		Fuses
Fuse Type Current Rating 30A Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 7531 Approvals Operating Temperature -55°C ~ 125°C Color Size / Dimension Cartridge, Glass AQA Cartridge, Glass 30A Cartridge, Glass 30A Cartridge, Glass 30A CE, W-MARK, PSE Color -250V Cartridge, Glass 30A CE, W-MARK, PSE -50V Cartridge, Glass Size / Dimension -250V Cartridge, Glass Size / Glass Size / Dimension -250V Color -2	Package	3AB, 3AG, 1/4" x 1-1/4" (Axial)
Current Rating 30A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 7531 Approvals CE, K-MARK, PSE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Series	388
Voltage Rating - AC Voltage Rating - DC Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting 12t Approvals CE, K-MARK, PSE Operating Temperature -55°C ~ 125°C Color Size / Dimension 250V - 250V Color - Size / Dimension Past 4AB, 3AG, 1/4" x 1-1/4" (Axial) Through Hole CE, K-MARK, PSE 00A - 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Fuse Type	Cartridge, Glass
Voltage Rating - DC Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 7531 Approvals CE, K-MARK, PSE Operating Temperature -55°C ~ 125°C Color - Size / Dimension Description:	Current Rating	30A
Response Time Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 7531 Approvals CE, K-MARK, PSE Operating Temperature -55°C ~ 125°C Color Size / Dimension Fast 3AB, 3AG, 1/4" x 1-1/4" (Axial) Characteristics Through Hole 100A Through Hole 100A 7531 7531 Approvals CE, K-MARK, PSE 0-55°C ~ 125°C	Voltage Rating - AC	250V
Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A Melting I2t 7531 Approvals CE, K-MARK, PSE Operating Temperature -55°C ~ 125°C Color Size / Dimension 3AB, 3AG, 1/4" x 1-1/4" (Axial) Through Hole 100A 7531 7531 CE, K-MARK, PSE -55°C ~ 125°C -55°C ~ 125°C	Voltage Rating - DC	-
Mounting Type Breaking Capacity @ Rated Voltage 100A Melting I2t 7531 Approvals CE, K-MARK, PSE Operating Temperature -55°C ~ 125°C Color Size / Dimension Through Hole 100A 7531 -55°L 7531 -55°C ~ 125°C -55°C ~ 125°C	Response Time	Fast
Breaking Capacity @ Rated Voltage Melting I2t Approvals CE, K-MARK, PSE Operating Temperature -55°C ~ 125°C Color Size / Dimension 100A CE, K-MARK, PSE -55°C ~ 125°C 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Package / Case	3AB, 3AG, 1/4" x 1-1/4" (Axial)
Melting I2t 7531 Approvals CE, K-MARK, PSE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Mounting Type	Through Hole
Approvals CE, K-MARK, PSE Operating Temperature -55°C ~ 125°C Color Size / Dimension CE, K-MARK, PSE -55°C ~ 125°C -55°C ~ 125°C -0275" Dia x 1.288" L (6.99mm x 32.72mm)	Breaking Capacity @ Rated Voltage	100A
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Melting I2t	7531
Color - Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Approvals	CE, K-MARK, PSE
Size / Dimension 0.275" Dia x 1.288" L (6.99mm x 32.72mm)	Operating Temperature	-55°C ~ 125°C
, , , , , , , , , , , , , , , , , , ,	Color	-
Report errors?	Size / Dimension	0.275" Dia x 1.288" L (6.99mm x 32.72mm)
		Report errors?

0388030.MXEP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0388030.MXEP Payment Methods





















0388030.MXEP Shipping Methods













If you have any question about 0388030.MXEP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com