

# 0395-5-15-01-07-27-10-0

### 0395-5-15-01-07-27-10-0 Information

Heisener.com	 0395-5-15-01-07-27-10-0 Mill-Max Manufacturing Corp. Connectors, Interconnects Terminals - PC Pin Receptacles, Socket Connectors CONN PIN RCPT .065082 SWAGE - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 0395-5-15-01-07-27-10-0 Specifications

ManufacturerMill-Max Manufacturing Corp.CategoryConnectors, InterconnectsTerminals - PC Pin Receptacles, Socket ConnectorsPackage-Series0395Tail TypeTurretTerminationSwageAccepts Pin Diameter0.065" ~ 0.082" (1.65mm ~ 2.08mm)Mounting Hole Diameter0.106" (2.44mm)Pin Hole Diameter0.107" (2.72mm)Fail Diameter0.375" (9.53mm)Socket Depth0.375" (9.53mm)Contact MaterialGold		
CategoryConnectors, Interconnects Terminals - PC Pin Receptacles, Socket ConnectorsPackage-Series0395Tail TypeTurretTerminationSwageLength - Overall0.762" (19.35mm)Accepts Pin Diameter0.065" ~ 0.082" (1.65mm ~ 2.08mm)Mounting Hole Diameter0.096" (2.44mm)Pin Hole Diameter0.107" (2.72mm)Flange Diameter0.147" (3.73mm)Socket Depth0.375" (9.53mm)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)	Manufacturer Part Number	0395-5-15-01-07-27-10-0
Terminals - PC Pin Receptacles, Socket ConnectorsPackage-Series0395Tail TypeTurretTerminationSwageLength - Overall0.762" (19.35mm)Accepts Pin Diameter0.065" ~ 0.082" (1.65mm ~ 2.08mm)Mounting Hole Diameter0.096" (2.44mm)Pin Hole Diameter0.107" (2.72mm)Flange Diameter0.147" (3.73mm)Tail Diameter-Socket Depth0.375" (9.53mm)Contact MaterialBeryllium CopperContact Finish Thickness30µin (0.76µm)	Manufacturer	Mill-Max Manufacturing Corp.
Package-Series0395Tail TypeTurretTerminationSwageLength - Overall0.762" (19.35mm)Accepts Pin Diameter0.065" ~ 0.082" (1.65mm ~ 2.08mm)Mounting Hole Diameter0.096" (2.44mm)Pin Hole Diameter0.107" (2.72mm)Flange Diameter0.147" (3.73mm)Tail Diameter0.375" (9.53mm)Socket Depth0.375" (9.53mm)Contact MaterialGoldContact Finish Thickness30µin (0.76µm)	Category	Connectors, Interconnects
Series0395Tail TypeTurretTerminationSwageLength - Overall0.762" (19.35mm)Accepts Pin Diameter0.065" ~ 0.082" (1.65mm ~ 2.08mm)Mounting Hole Diameter0.096" (2.44mm)Pin Hole Diameter0.107" (2.72mm)Flange Diameter0.147" (3.73mm)Tail Diameter0.375" (9.53mm)Socket Depth0.375" (9.53mm)Contact MaterialGoldContact Finish Thickness30µin (0.76µm)		Terminals - PC Pin Receptacles, Socket Connectors
Tail TypeTurretTerminationSwageLength - Overall0.762" (19.35mm)Accepts Pin Diameter0.065" ~ 0.082" (1.65mm ~ 2.08mm)Mounting Hole Diameter0.096" (2.44mm)Pin Hole Diameter0.107" (2.72mm)Flange Diameter0.147" (3.73mm)Tail Diameter0.375" (9.53mm)Socket DepthBeryllium CopperContact FinishGoldSource Finish Thickness30µin (0.76µm)	Package	-
Termination   Swage     Length - Overall   0.762" (19.35mm)     Accepts Pin Diameter   0.065" ~ 0.082" (1.65mm ~ 2.08mm)     Mounting Hole Diameter   0.096" (2.44mm)     Pin Hole Diameter   0.107" (2.72mm)     Flange Diameter   0.147" (3.73mm)     Tail Diameter   -     Socket Depth   0.375" (9.53mm)     Contact Material   Beryllium Copper     Contact Finish Thickness   30µin (0.76µm)	Series	0395
Length - Overall0.762" (19.35mm)Accepts Pin Diameter0.065" ~ 0.082" (1.65mm ~ 2.08mm)Mounting Hole Diameter0.096" (2.44mm)Pin Hole Diameter0.107" (2.72mm)Flange Diameter0.147" (3.73mm)Tail Diameter-Socket Depth0.375" (9.53mm)Contact MaterialBeryllium CopperContact FinishGoldSour Finish Thickness30µin (0.76µm)	Tail Type	Turret
Accepts Pin Diameter 0.065" ~ 0.082" (1.65mm ~ 2.08mm)   Mounting Hole Diameter 0.096" (2.44mm)   Pin Hole Diameter 0.107" (2.72mm)   Flange Diameter 0.147" (3.73mm)   Tail Diameter -   Socket Depth 0.375" (9.53mm)   Contact Material Beryllium Copper   Contact Finish Gold   South Finish Thickness 30µin (0.76µm)	Termination	Swage
Mounting Hole Diameter0.096" (2.44mm)Pin Hole Diameter0.107" (2.72mm)Flange Diameter0.147" (3.73mm)Tail Diameter-Socket Depth0.375" (9.53mm)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)	Length - Overall	0.762" (19.35mm)
Pin Hole Diameter0.107" (2.72mm)Flange Diameter0.147" (3.73mm)Tail Diameter-Socket Depth0.375" (9.53mm)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)	Accepts Pin Diameter	0.065" ~ 0.082" (1.65mm ~ 2.08mm)
Flange Diameter0.147" (3.73mm)Tail Diameter-Socket Depth0.375" (9.53mm)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)	Mounting Hole Diameter	0.096" (2.44mm)
Tail Diameter-Socket Depth0.375" (9.53mm)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)	Pin Hole Diameter	0.107" (2.72mm)
Socket Depth0.375" (9.53mm)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)	Flange Diameter	0.147" (3.73mm)
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)	Tail Diameter	-
Contact FinishGoldContact Finish Thickness30μin (0.76μm)	Socket Depth	0.375" (9.53mm)
Contact Finish Thickness 30µin (0.76µm)	Contact Material	Beryllium Copper
	Contact Finish	Gold
Report errors?	Contact Finish Thickness	30µin (0.76µm)
		Report errors?

#### 0395-5-15-01-07-27-10-0 Guarantees




**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.







If you have any question about 0395-5-15-01-07-27-10-0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com