

0400MD-1-004 Information

Heisener.com

Part Number 0400MD-1-004 Manufacturer Talema Group LLC

Category Transformers **Power Transformers**

Description XFMR TOROIDAL 400VA THRM PROTCT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0400MD-1-004 Specifications

Manufacturer Part Number 0400MD-1-004 Manufacturer Talema Group LLC Category Transformers Package - Series MD Type Toroidal Voltage - Primary 100V, 120V, 200V, 240V Voltage - Secondary (Full Load) Parallel 120V, Series 240V Current - Output (Max) Parallel 3.33A, Series 1.67A Primary Winding(s) Single, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 132.00mm Dia x 64.00mm W Height - Seated (Max) - Voltage - Isolation 5000Vrms Weight 7.5 lbs (3.4kg)		
CategoryTransformersPackage-SeriesMDTypeToroidalVoltage - Primary100V, 120V, 200V, 240VVoltage - Secondary (Full Load)Parallel 120V, Series 240VCurrent - Output (Max)Parallel 3.33A, Series 1.67APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max400 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension132.00mm Dia x 64.00mm WHeight - Seated (Max)-Voltage - Isolation5000VrmsWeight7.5 lbs (3.4kg)	Manufacturer Part Number	0400MD-1-004
Package - Series MD Type Toroidal Voltage - Primary Voltage - Secondary (Full Load) Parallel 120V, Series 240V Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Toroidal MD A MD A MO MD A MO MD A MO MD A MO A A Aultiple 120V, Series 240V A A Multiple Taps Single, Multiple Taps No Center Tap No Chassis Mount Wire Leads 132.00mm Dia x 64.00mm W Height - Seated (Max) Voltage - Isolation Toroidal MD Toroidal Parallel 120V, 200V, 240V Parallel 120V, Series 240V Parallel 120V, Series 240V Current - Output (Max) Parallel 120V, Series 240V Parallel 120V, Series 240V Parallel 120V, Series 240V Current - Output (Max) Parallel 120V, Series 240V Parallel 120V, Series 240V Parallel 120V, Series 240V Parallel 120V, 200V, 240V Parallel 120V, 20V, 20V Parallel 120V, 20V, 20V Parallel 120V, 20V Parallel 120V Parallel 120V, 20V Parallel 120V, 20V Parallel 120V Parallel 120V, 20V Parallel 120V, 20V Parallel 120V, 20V Parallel	Manufacturer	Talema Group LLC
Package - Series MD Type Toroidal Voltage - Primary 100V, 120V, 200V, 240V Voltage - Secondary (Full Load) Parallel 120V, Series 240V Current - Output (Max) Parallel 3.33A, Series 1.67A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 132.00mm Dia x 64.00mm W Height - Seated (Max) - Voltage - Isolation 5000Vrms Weight 7.5 lbs (3.4kg)	Category	Transformers
SeriesMDTypeToroidalVoltage - Primary100V, 120V, 200V, 240VVoltage - Secondary (Full Load)Parallel 120V, Series 240VCurrent - Output (Max)Parallel 3.33A, Series 1.67APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max400 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension132.00mm Dia x 64.00mm WHeight - Seated (Max)-Voltage - Isolation5000VrmsWeight7.5 lbs (3.4kg)		Power Transformers
Type Toroidal Voltage - Primary 100V, 120V, 200V, 240V Voltage - Secondary (Full Load) Parallel 120V, Series 240V Current - Output (Max) Parallel 3.33A, Series 1.67A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 132.00mm Dia x 64.00mm W Height - Seated (Max) - Voltage - Isolation 5000Vrms Weight 7.5 lbs (3.4kg)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 120V, Series 240V Current - Output (Max) Parallel 3.33A, Series 1.67A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Voltage - Isolation Voltage - Isolation Terminary No 100V, 120V, 200V, 240V Parallel 120V, Series 240V Parallel 120V, Series 240V Parallel 120V, Series 240V Parallel 120V, Series 240V Parallel 120V, 200V Parallel 120V, 200V Parallel 120V, Series 240V Parallel 120V, 200V Parallel 120V Parallel 120V, 200V Parallel 120V, 200V Parallel 120V Parallel 120V Parallel 120V, 200V Parallel 120V Parallel 1	Series	MD
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 3.33A, Series 240V Parallel 3.33A, Series 1.67A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Single, Multiple Taps No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Size / Dimension 132.00mm Dia x 64.00mm W Height - Seated (Max) Voltage - Isolation Wind (3.4kg)	Туре	Toroidal
Current - Output (Max) Parallel 3.33A, Series 1.67A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 132.00mm Dia x 64.00mm W Height - Seated (Max) Voltage - Isolation 5000Vrms Weight 7.5 lbs (3.4kg)	Voltage - Primary	100V, 120V, 200V, 240V
Primary Winding(s) Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 400 VA Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Winding Type 7.5 lbs (3.4kg)	Voltage - Secondary (Full Load)	Parallel 120V, Series 240V
Secondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max400 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension132.00mm Dia x 64.00mm WHeight - Seated (Max)-Voltage - Isolation5000VrmsWeight7.5 lbs (3.4kg)	Current - Output (Max)	Parallel 3.33A, Series 1.67A
Center TapNoPower - Max400 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension132.00mm Dia x 64.00mm WHeight - Seated (Max)-Voltage - Isolation5000VrmsWeight7.5 lbs (3.4kg)	Primary Winding(s)	Dual, Multiple Taps
Power - Max 400 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 132.00mm Dia x 64.00mm W Height - Seated (Max) - Voltage - Isolation 5000Vrms Weight 7.5 lbs (3.4kg)	Secondary Winding(s)	Single, Multiple Taps
Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 132.00mm Dia x 64.00mm W Height - Seated (Max) - Voltage - Isolation 5000Vrms Weight 7.5 lbs (3.4kg)	Center Tap	No
Termination Style Wire Leads Size / Dimension 132.00mm Dia x 64.00mm W Height - Seated (Max) - Voltage - Isolation 5000Vrms Weight 7.5 lbs (3.4kg)	Power - Max	400 VA
Size / Dimension 132.00mm Dia x 64.00mm W Height - Seated (Max) - Voltage - Isolation 5000Vrms Weight 7.5 lbs (3.4kg)	Mounting Type	Chassis Mount
Height - Seated (Max) Voltage - Isolation Source 5000Vrms Weight 7.5 lbs (3.4kg)	Termination Style	Wire Leads
Voltage - Isolation 5000Vrms Weight 7.5 lbs (3.4kg)	Size / Dimension	132.00mm Dia x 64.00mm W
Weight 7.5 lbs (3.4kg)	Height - Seated (Max)	-
	Voltage - Isolation	5000Vrms
Report errors?	Weight	7.5 lbs (3.4kg)
		Report errors?

0400MD-1-004 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0400MD-1-004 Payment Methods



















0400MD-1-004 Shipping Methods













If you have any question about 0400MD-1-004, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com