



0402YC103KA72A Information



For Reference Only

Part Number 0402YC103KA72A
Manufacturer AVX Corporation
Category Capacitors

Ceramic Capacitors

Description CAP CER 10000PF 16V X7R 0402

Package 0402 (1005 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0402YC103KA72A Specifications

Manufacturer Part Number 0402YC103KA72A Manufacturer AVX Corporation Category Capacitors Package 0402 (1005 Metric) Series - Capacitance 10000pF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.56mm) Lead Spacing - Lead Style -		
Category Capacitors Package 0402 (1005 Metric) Series - Capacitance 10000pF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.56mm) Lead Spacing - Lead Style -	Manufacturer Part Number	0402YC103KA72A
Package 0402 (1005 Metric) Series - Capacitance 10000pF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.56mm) Lead Spacing - Lead Style -	Manufacturer	AVX Corporation
Package 0402 (1005 Metric) Series - Capacitance 10000pF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.56mm) Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 10000pF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.56mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 10000pF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.56mm) Lead Spacing - Lead Style -	Package	0402 (1005 Metric)
Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.56mm) Lead Spacing - Lead Style -	Series	-
Voltage - Rated Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.56mm) Lead Spacing - Lead Style -	Capacitance	10000pF
Temperature Coefficient A7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) Thickness (Max) 0.022" (0.56mm) Lead Spacing - Lead Style - X7R A7R A7R A7R A7R A7R A7R A7R	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.039" L x 0.020" W (1.00mm x 0.50mm)Height - Seated (Max)-Thickness (Max)0.022" (0.56mm)Lead Spacing-Lead Style-	Voltage - Rated	16V
Features Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.56mm) Lead Spacing - Lead Style -	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.56mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.56mm) Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.56mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.56mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.56mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.56mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	0402 (1005 Metric)
Thickness (Max) 0.022" (0.56mm) Lead Spacing - Lead Style -	Size / Dimension	0.039" L x 0.020" W (1.00mm x 0.50mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.022" (0.56mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

0402YC103KA72A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0402YC103KA72A Payment Methods

































If you have any question about 0402YC103KA72A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com