



0402YD222KAT2A Information



For Reference Only

Part Number 0402YD222KAT2A Manufacturer AVX Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 2200PF 16V X5R 0402

Package 0402 (1005 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0402YD222KAT2A Specifications

Manufacturer Part Number 0402YD222KAT2A Manufacturer AVX Corporation Category Capacitors Package 0402 (1005 Metric) Series - Capacitance 2200pF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X5R Operating Temperature -5°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style - Report errors?		
Category Capacitors Package 0402 (1005 Metric) Series - Capacitance 2200pF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Manufacturer Part Number	0402YD222KAT2A
Package 0402 (1005 Metric) Series - Capacitance 2200pF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.002" (0.55mm) Lead Spacing - Lead Style -	Manufacturer	AVX Corporation
Package 0402 (1005 Metric) Series - Capacitance 2200pF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 2200pF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 2200pF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Package	0402 (1005 Metric)
Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X5R Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Series	-
Voltage - Rated16VTemperature CoefficientX5ROperating Temperature-55°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.039" L x 0.020" W (1.00mm x 0.50mm)Height - Seated (Max)-Thickness (Max)0.022" (0.55mm)Lead Spacing-Lead Style-	Capacitance	2200pF
Temperature Coefficient Operating Temperature -55°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style X5R Comeral Purpose General Purpose Universe (Max) Surface Mount, MLCC Output (1.00mm x 0.50mm) Autput (1.00mm x 0.50mm) - Comerating (1.00mm x 0.50mm)	Tolerance	±10%
Operating Temperature-55°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.039" L x 0.020" W (1.00mm x 0.50mm)Height - Seated (Max)-Thickness (Max)0.022" (0.55mm)Lead Spacing-Lead Style-	Voltage - Rated	16V
Features Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Temperature Coefficient	X5R
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style - Surface Mount, MLCC	Operating Temperature	-55°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	0402 (1005 Metric)
Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Size / Dimension	0.039" L x 0.020" W (1.00mm x 0.50mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.022" (0.55mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

0402YD222KAT2A Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0402YD222KAT2A Payment Methods



















0402YD222KAT2A Shipping Methods













If you have any question about 0402YD222KAT2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com