

0451.100MR

0451.100MR Information



Part Number	0451.100MR	
Manufacturer	Littelfuse Inc.	
Category	Circuit Protection Fuses	
Description	FUSE BOARD MNT 100MA 125VAC/VDC	
Package	2-SMD, Square End Block	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



0451.100MR Specifications

Manufacturer Part Number0451.100MRManufacturerLittelfuse Inc.CategoryCircuit ProtectionFusesFusesPackage2-SMD, Square End BlockSeriesNANO2? 451Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating100mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.00138Operating Temperature55% C a 125% C			
CategoryCircuit ProtectionFusesPackage2-SMD, Square End BlockSeriesNANO2? 451Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating100mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.00138ApprovalsCSA, UL	Manufacturer Part Number	0451.100MR	
FusesPackage2-SMD, Square End BlockSeriesNANO2? 451Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating100mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.00138ApprovalsCSA, UL	Manufacturer	Littelfuse Inc.	
Package2-SMD, Square End BlockSeriesNANO2? 451Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating100mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting 12t0.00138ApprovalsCSA, UL	Category	Circuit Protection	
SeriesNANO2? 451Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating100mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.00138ApprovalsCSA, UL		Fuses	
Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating100mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.00138ApprovalsCSA, UL	Package	2-SMD, Square End Block	
Current Rating100mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.00138ApprovalsCSA, UL	Series	NANO2? 451	
Voltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.00138ApprovalsCSA, UL	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC125VResponse TimeFastPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.00138ApprovalsCSA, UL	Current Rating	100mA	
Response TimeFastPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.00138ApprovalsCSA, UL	Voltage Rating - AC	125V	
Package / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.00138ApprovalsCSA, UL	Voltage Rating - DC	125V	
Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.00138ApprovalsCSA, UL	Response Time	Fast	
Breaking Capacity @ Rated Voltage50AMelting I2t0.00138ApprovalsCSA, UL	Package / Case	2-SMD, Square End Block	
Melting I2t0.00138ApprovalsCSA, UL	Mounting Type	Surface Mount	
Approvals CSA, UL	Breaking Capacity @ Rated Voltage	50A	
	Melting I2t	0.00138	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Approvals	CSA, UL	
operating reinperature 55 C 125 C	Operating Temperature	-55°C ~ 125°C	
Color -	Color	-	
Size / Dimension 0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm x 2.69mm)	Size / Dimension	0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm x 2.69mm)	
Report error			Report errors?

0451.100MR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

If you have any question about 0451.100MR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com