

## 045402.5NR

#### 045402.5NR Information



Part Number	045402.5NR	
Manufacturer	Littelfuse Inc.	
Category	Circuit Protection Fuses	
Description	FUSE BRD MNT 2.5A 125VAC/VDC SMD	
Package	2-SMD, Square End Block	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



#### 045402.5NR Specifications

ManufacturerLittelfuse Inc.CategoryCircuit ProtectionFusesFusesPackage2-SMD, Square End BlockSeriesNANO2? 454Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating2.5AVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeSlowPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting 12t15ApprovalsCSA, PSE, ULOperating Temperature-55°C ~ 125°CColor-			
CategoryCircuit ProtectionFusesPackage2-SMD, Square End BlockSeriesNANO2? 454Fuse TypeBoard Mount (Cattridge Style Excluded)Current Rating2.5AVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeSlowPackage / Case2.SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage50AApprovalsCSA, PSE, ULApprovalscSA, PSE, ULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.240" L x 0.106" H (6.10mm x 2.69mm x 2.69mm)	Manufacturer Part Number	045402.5NR	
FusesPackage2-SMD, Square End BlockSeriesNANO2? 454Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating2.5AVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeSlowPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting 12t15ApprovalsCSA, PSE, ULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm)	Manufacturer	Littelfuse Inc.	
Package   SMD, Square End Block     Series   NANO2? 454     Fuse Type   Board Mount (Cartridge Style Excluded)     Current Rating   2.5A     Voltage Rating - AC   125V     Voltage Rating - DC   125V     Response Time   Slow     Package / Case   Slow     Mounting Type   Surface Mount     Breaking Capacity @ Rated Voltage   50A     Approvals   CSA, PSE, UL     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm)	Category	Circuit Protection	
SeriesNANO2? 454Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating2.5AVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeSlowPackage / Case2.SMD, Square End BlockMounting Type50ABreaking Capacity @ Rated Voltage50AMelting I2t15ApprovalsCSA, PSE, ULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm)		Fuses	
Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating2.5AVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeSlowPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t15ApprovalsCSA, PSE, ULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm x 2.69mm)	Package	2-SMD, Square End Block	
Current Rating   2.5A     Voltage Rating - AC   125V     Voltage Rating - DC   125V     Response Time   Slow     Package / Case   2-SMD, Square End Block     Mounting Type   Surface Mount     Breaking Capacity @ Rated Voltage   50A     Approvals   CSA, PSE, UL     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm) x 2.69mm)	Series	NANO2? 454	
Voltage Rating - AC   125V     Voltage Rating - DC   125V     Response Time   Slow     Package / Case   Slow     Nounting Type   2-SMD, Square End Block     Mounting Type   Surface Mount     Breaking Capacity @ Rated Voltage   50A     Melting I2t   15     Approvals   CSA, PSE, UL     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm x 2.69mm)	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC125VResponse TimeSlowPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t15ApprovalsCSA, PSE, ULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm x 2.69mm)	Current Rating	2.5A	
Response TimeSlowPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t15ApprovalsCSA, PSE, ULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm x 2.69mm)	Voltage Rating - AC	125V	
Package / Case 2-SMD, Square End Block   Mounting Type Surface Mount   Breaking Capacity @ Rated Voltage 50A   Melting I2t 15   Approvals CSA, PSE, UL   Operating Temperature -55°C ~ 125°C   Color -   Size / Dimension 0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm x 2.69mm)	Voltage Rating - DC	125V	
Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t15ApprovalsCSA, PSE, ULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm x 2.69mm)	Response Time	Slow	
Breaking Capacity @ Rated Voltage   50A     Melting I2t   15     Approvals   CSA, PSE, UL     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm x 2.69mm)	Package / Case	2-SMD, Square End Block	
Melting I2t   15     Approvals   CSA, PSE, UL     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm x 2.69mm)	Mounting Type	Surface Mount	
Approvals   CSA, PSE, UL     Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm x 2.69mm)	Breaking Capacity @ Rated Voltage	50A	
Operating Temperature   -55°C ~ 125°C     Color   -     Size / Dimension   0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm x 2.69mm)	Melting I2t	15	
Color   -     Size / Dimension   0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm x 2.69mm)	Approvals	CSA, PSE, UL	
Size / Dimension 0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm x 2.69mm)	Operating Temperature	-55°C ~ 125°C	
	Color	-	
Report errors?	Size / Dimension	0.240" L x 0.106" W x 0.106" H (6.10mm x 2.69mm x 2.69mm)	
			Report errors?

#### 045402.5NR Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE ELARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 045402.5NR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com