



0471001.PF010L Information

Heisener.com

Part Number0471001.PF010LManufacturerLittelfuse Inc.CategoryCircuit Protection

Fuses

Description FUSE BRD MNT 1A 125VAC/VDC AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0471001.PF010L Specifications

Manufacturer Part Number0471001.PF010LManufacturerLittelfuse Inc.CategoryCircuit ProtectionFusesPackagePackageAxialSeriesPICO? II 471Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating1AVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeSlowPackage / CaseAxialMounting TypeThrough HoleBreaking Capacity @ Rated Voltage50AMelting 12t0.722ApprovalsCSA, PSE, UROperating Temperature-55°C ~ 125°CColor-Size / Dimension0.110" Dia x 0.280" L (2.80mm x 7.11mm)Report errors?	•	
Category Circuit Protection Fuses Package Axial Series PICO? II 471 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 1A Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Slow Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 0.722 Approvals CSA, PSE, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Manufacturer Part Number	0471001.PF010L
Fuses Package Axial Series PICO? II 471 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 1A Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Slow Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting 12t Approvals Operating Temperature -55°C ~ 125°C Color - Size / Dimension Fuse Said Axial	Manufacturer	Littelfuse Inc.
Package Axial Series PICO? II 471 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 1A Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Slow Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting 12t 0.722 Approvals CSA, PSE, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Category	Circuit Protection
Series PICO? II 471 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 1A Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Slow Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 0.722 Approvals CSA, PSE, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm)		Fuses
Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 1A Voltage Rating - AC 125V Voltage Rating - DC Response Time Slow Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature CSA, PSE, UR Operating Temperature -55°C ~ 125°C Color Size / Dimension Board Mount (Cartridge Style Excluded) 1A 1A 125V 125V 125V Slow Axial Axial Axial On-22 CSA, PSE, UR -50A On-722 CSA, PSE, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension On-110" Dia x 0.280" L (2.80mm x 7.11mm)	Package	Axial
Current Rating Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Slow Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature CSA, PSE, UR Operating Temperature -55°C ~ 125°C Color Size / Dimension 1A 125V 125V 125V 125V 125V 125V 125V 125V	Series	PICO? II 471
Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting 12t Approvals CSA, PSE, UR Operating Temperature Color Color Size / Dimension 125V 125V 125V 125V 125V 125V Axial Axial Axial 0.722 CSA, PSE, UR -55°C ~ 125°C -125°C 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Fuse Type	Board Mount (Cartridge Style Excluded)
Voltage Rating - DC Response Time Slow Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature CSA, PSE, UR Operating Temperature -55°C ~ 125°C Color Size / Dimension 125V Axial Axial Axial 0.722 CSA, PSE, UR -50.722 CSA, PSE, UR -10.722 CSA, PSE, UR -10.725°C -10.700 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Current Rating	1A
Response Time Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CSA, PSE, UR Operating Temperature -55°C ~ 125°C Color Size / Dimension Slow Axial Characteristics Axial Characteristics Axial Characteristics Axial Characteristics Axial Characteristics Axial CSA, PSE, UR 0.722 CSA, PSE, UR -55°C ~ 125°C Color - Size / Dimension O.110" Dia x 0.280" L (2.80mm x 7.11mm)	Voltage Rating - AC	125V
Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 0.722 Approvals CSA, PSE, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Voltage Rating - DC	125V
Mounting Type Breaking Capacity @ Rated Voltage Melting I2t Approvals CSA, PSE, UR Operating Temperature -55°C ~ 125°C Color Size / Dimension Through Hole Through Hole 50A 0.722 0.722 CSA, PSE, UR -55°C ~ 125°C -1010" Dia x 0.280" L (2.80mm x 7.11mm)	Response Time	Slow
Breaking Capacity @ Rated Voltage 50A Melting I2t 0.722 Approvals CSA, PSE, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Package / Case	Axial
Melting I2t 0.722 ApprovalsCSA, PSE, UROperating Temperature -55° C $\sim 125^{\circ}$ CColor-Size / Dimension $0.110''$ Dia x $0.280''$ L $(2.80 \text{mm x } 7.11 \text{mm})$	Mounting Type	Through Hole
Approvals CSA, PSE, UR Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Breaking Capacity @ Rated Voltage	50A
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Melting I2t	0.722
Color - Color	Approvals	CSA, PSE, UR
Size / Dimension 0.110" Dia x 0.280" L (2.80mm x 7.11mm)	Operating Temperature	-55°C ~ 125°C
,	Color	-
Report errors?	Size / Dimension	0.110" Dia x 0.280" L (2.80mm x 7.11mm)
		Report errors?

0471001.PF010L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0471001.PF010L Payment Methods



















0471001.PF010L Shipping Methods













If you have any question about 0471001.PF010L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com