



0473007.HAT1L Information



Part Number 0473007.HAT1L
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

Description FUSE BRD MNT 7A 125VAC/VDC AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0473007.HAT1L Specifications

Manufacturer Part Number0473007.HAT1LManufacturerLittelfuse Inc.CategoryCircuit ProtectionFusesPackagePackageAxialSeriesPICO? II 473Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating7AVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeSlowPackage / CaseAxialMounting TypeThrough HoleBreaking Capacity @ Rated Voltage50AMelting 12t105ApprovalsCSA, UROperating Temperature-55°C ~ 125°CColor-Size / Dimension0.135" Dia x 0.280" L (3.43mm x 7.11mm)Report errors?	•	
Category Circuit Protection Fuses Package Axial Series PICO? II 473 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 7A Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Slow Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CESA, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension Circuit Protection Fuses Fuses Axial Active Type Through Hole Fuses CSA, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension Circuit Protection Fuses Fuses Axial Active Type Cartridge Style Excluded) 7A 125V 125V	Manufacturer Part Number	0473007.HAT1L
Fuses Package Axial Series PICO? II 473 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 7A Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Slow Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 105 Approvals CSA, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension Axial Axial CAA, UR O.135" Dia x 0.280" L (3.43mm x 7.11mm)	Manufacturer	Littelfuse Inc.
Package Axial Series PICO? II 473 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 7A Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Slow Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 105 Approvals CSA, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.135" Dia x 0.280" L (3.43mm x 7.11mm)	Category	Circuit Protection
Series PICO? II 473 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 7A Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Slow Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting 12t 105 Approvals CSA, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.135" Dia x 0.280" L (3.43mm x 7.11mm)		Fuses
Fuse Type Current Rating 7A Voltage Rating - AC 125V Voltage Rating - DC Response Time Slow Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature -55°C ~ 125°C Color Size / Dimension Board Mount (Cartridge Style Excluded) 7A 125V 125V Slow Axial Axial Axial Characteristic Solow Axial Characteristic Solow 125	Package	Axial
Current Rating Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Slow Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 105 Approvals CSA, UR Operating Temperature -55°C ~ 125°C Color Size / Dimension 7A 125V 105 105 Axial Axial 105 CSA, UR 0-105 -55°C ~ 125°C	Series	PICO? II 473
Voltage Rating - AC Voltage Rating - DC Response Time Slow Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CSA, UR Operating Temperature Color Color Size / Dimension 125V 105V 105V 105 CSA, UR 105 -55°C ~ 125°C 0.135" Dia x 0.280" L (3.43mm x 7.11mm)	Fuse Type	Board Mount (Cartridge Style Excluded)
Voltage Rating - DC Response Time Slow Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature CSA, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 125V Axial Axial Axial 105 CNA, UR -55°C ~ 125°C -125°C	Current Rating	7A
Response Time Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals CSA, UR Operating Temperature -55°C ~ 125°C Color Size / Dimension Slow Axial Characteristics Axial Through Hole 50A CSA 0.135" Dia x 0.280" L (3.43mm x 7.11mm)	Voltage Rating - AC	125V
Package / Case Axial Mounting Type Through Hole Breaking Capacity @ Rated Voltage 50A Melting I2t 105 Approvals CSA, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.135" Dia x 0.280" L (3.43mm x 7.11mm)	Voltage Rating - DC	125V
Mounting Type Breaking Capacity @ Rated Voltage Melting I2t Approvals CSA, UR Operating Temperature Color Size / Dimension Through Hole Through Hole 50A CSA 0.105 105 -55°C ~ 125°C -125°C -125°C -125°C -125°C -125°C	Response Time	Slow
Breaking Capacity @ Rated Voltage 50A Melting I2t 105 Approvals CSA, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.135" Dia x 0.280" L (3.43mm x 7.11mm)	Package / Case	Axial
Melting I2t 105 Approvals CSA, UR Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.135" Dia x 0.280" L (3.43mm x 7.11mm)	Mounting Type	Through Hole
Approvals CSA, UR Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Color - Size / Dimension 0.135" Dia x 0.280" L (3.43mm x 7.11mm)	Breaking Capacity @ Rated Voltage	50A
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Color - Size / Dimension $0.135''$ Dia x $0.280''$ L $(3.43\text{mm x } 7.11\text{mm})$	Melting I2t	105
Color - Color	Approvals	CSA, UR
Size / Dimension 0.135" Dia x 0.280" L (3.43mm x 7.11mm)	Operating Temperature	-55°C ~ 125°C
` '	Color	-
Report errors?	Size / Dimension	0.135" Dia x 0.280" L (3.43mm x 7.11mm)
		Report errors?

0473007.HAT1L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0473007.HAT1L Payment Methods



















0473007.HAT1L Shipping Methods













If you have any question about 0473007.HAT1L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com