



0477004.MXEP Information



For Reference Only

Part Number 0477004.MXEP
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

Description FUSE CERM 4A 500VAC 400VDC 5X20

Package 5mm x 20mm (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0477004.MXEP Specifications

Manufacturer Part Number0477004.MXEPManufacturerLittelfuse Inc.CategoryCircuit ProtectionFusesFasesPackage5mm x 20mm (Axial)Series477Fuse TypeCartridge, CeramicCurrent Rating4AVoltage Rating - AC500VVoltage Rating - DC400VResponse TimeSlowPackage / Case5mm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage100A AC, 500A DCMelting 12t52.48ApprovalscULus, PSE, SEMKOOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.228" Dia x 0.886" L (5.80mm x 22.50mm)	•	
Category Circuit Protection Fuses Package 5mm x 20mm (Axial) Series 477 Fuse Type Cartridge, Ceramic Current Rating 4A Voltage Rating - AC 500V Voltage Rating - DC 400V Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 500A DC Melting I2t 52.48 Approvals cULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Manufacturer Part Number	0477004.MXEP
Package 5mm x 20mm (Axial) Series 477 Fuse Type Cartridge, Ceramic Current Rating 4A Voltage Rating - AC 500V Voltage Rating - DC 400V Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 500A DC Melting 12t 52.48 Approvals cULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Manufacturer	Littelfuse Inc.
Package5mm x 20mm (Axial)Series477Fuse TypeCartridge, CeramicCurrent Rating4AVoltage Rating - AC500VVoltage Rating - DC400VResponse TimeSlowPackage / Case5mm x 20mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage100A AC, 500A DCMelting I2t52.48ApprovalscULus, PSE, SEMKOOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Category	Circuit Protection
Series 477 Fuse Type Cartridge, Ceramic Current Rating 4A Voltage Rating - AC 500V Voltage Rating - DC 400V Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 500A DC Melting I2t 52.48 Approvals cULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)		Fuses
Fuse Type Current Rating 4A Voltage Rating - AC 500V Voltage Rating - DC 400V Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 52.48 Approvals CuLus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color Size / Dimension Cartridge, Ceramic 4A Cartridge, Ceramic AB Culvi Cartridge, Ceramic Cartridge, Ceramic Cartridge, Ceramic AB Culvi Colov 500V 400V Acounting Through Hole 100A AC, 500A DC Culvi 52.48 Culvi Culvi Color Color Color Color Color Color Size / Dimension Cartridge, Ceramic 4A An Cartridge, Ceramic 4A An Culvi Colov Cartridge, Ceramic 500V Colov 500V Colov Color Co	Package	5mm x 20mm (Axial)
Current Rating Voltage Rating - AC 500V Voltage Rating - DC 400V Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 52.48 Approvals CuLus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color Size / Dimension 4A 4A 4A 4D 4A 4A 500V 500V 400V 400V 400V 400V 400V 400V 400V 400V 5low 5uh 5uh 5uh 5uh 5uh 5uh 5uh 5u	Series	477
Voltage Rating - AC Voltage Rating - DC 400V Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 500A DC Melting I2t 52.48 Approvals cULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color Size / Dimension 500V 400V 400V 400V 400V 5low 5low 5mm x 20mm (Axial) Through Hole 5cuther 5cuth	Fuse Type	Cartridge, Ceramic
Voltage Rating - DC Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 500A DC Melting I2t 52.48 Approvals CULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color - Size / Dimension 400V 400V 400V 400V 400V 400V 400V 5low 5mm x 20mm (Axial) Through Hole 100A AC, 500A DC 100A AC, 500A DC 40A 52.48 40B 52.48 40B 60B 60B 60B 60B 60B 60B 60B	Current Rating	4A
Response Time Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 500A DC Melting I2t 52.48 Approvals cULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color Size / Dimension Slow 5mm x 20mm (Axial) Cultus, PSE, SEMKO -500A DC -500	Voltage Rating - AC	500V
Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 500A DC Melting I2t 52.48 Approvals cULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Voltage Rating - DC	400V
Mounting Type Breaking Capacity @ Rated Voltage 100A AC, 500A DC Melting I2t 52.48 Approvals CULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color Size / Dimension Through Hole 100A AC, 500A DC 52.48 CULus, PSE, SEMKO -55°C ~ 125°C -55°C ~ 125°C	Response Time	Slow
Breaking Capacity @ Rated Voltage 100A AC, 500A DC Melting I2t 52.48 Approvals cULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Package / Case	5mm x 20mm (Axial)
Melting I2t 52.48 ApprovalscULus, PSE, SEMKOOperating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Color-Size / Dimension $0.228''$ Dia x $0.886''$ L $(5.80 \text{mm x } 22.50 \text{mm})$	Mounting Type	Through Hole
Approvals cULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Breaking Capacity @ Rated Voltage	100A AC, 500A DC
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Melting I2t	52.48
Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Approvals	cULus, PSE, SEMKO
Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Operating Temperature	-55°C ~ 125°C
, , , , , , , , , , , , , , , , , , ,	Color	-
Report errors?	Size / Dimension	0.228" Dia x 0.886" L (5.80mm x 22.50mm)
		Report errors?

0477004.MXEP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0477004.MXEP Payment Methods



















0477004.MXEP Shipping Methods













If you have any question about 0477004.MXEP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com