

0481.200HXL

0481.200HXL Information

Contact and contact they	Part Number Manufacturer Category Description Package	0481.200HXL Littelfuse Inc. Circuit Protection Electrical, Specialty Fuses FUSE INDICATING 200MA 125VAC/VDC Alarm Indicator For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



0481.200HXL Specifications

Manufacturer Littelfuse Inc. Category Circuit Protection Category Electrical, Specialty Fuses Package Alarn Indicator Series 481 Fuse Type Indicating Fuse Current Rating 200mA Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Applications Telecom Features Indicating Approvals CSA, UR Operating Temperature 50°C ~ 125°C Breaking Capacity @ Rated Voltage 300A Manufactures Guota Apportage Capacity @ Rated Voltage Alarn Indicator		
CategoryCircuit Protection Electrical, Specialty FusesPackageAlarm IndicatorPackageAlarm IndicatorSeries481Fuse TypeIndicating FuseCurrent Rating200mAVoltage Rating - AC125VVoltage Rating - DCI25VResponse TimeFastApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Manufacturer Part Number	0481.200HXL
ConstraintElectrical, Specialty FusesPackageAlarm IndicatorSeries481Fuse TypeIndicating FuseCurrent Rating200mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Manufacturer	Littelfuse Inc.
PackageAlarm IndicatorSeries481Fuse TypeIndicating FuseCurrent Rating200mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Category	Circuit Protection
Series 481 Fuse Type Indicating Fuse Current Rating 200mA Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Applications Telecom Class - Approvals CSA, UR Operating Temperature 55°C ~ 125°C Breaking Capacity @ Rated Voltage 300A Mounting Type Holder Package / Case Alarm Indicator Size / Dimension 665°L x 0.228°W x 0.772°'' H (16.90mm x 5.80mm x 19.60mm)		Electrical, Specialty Fuses
Fuse TypeIndicating FuseFuse TypeIndicating FuseCurrent Rating200mAVoltage Rating - AC125VVoltage Rating - DCFastResponse TimeFastApplicationsTelecomFeaturesIndicating FuseClass-ApprovalsCSA, UROperating Temperature300ABreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Package	Alarm Indicator
Current Rating 200mA Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Applications Telecom Features Indicating Class - Approvals CSA, UR Operating Temperature 50°C ~ 125°C Breaking Capacity @ Rated Voltage 300A Mounting Type Holder Package / Case Alarm Indicator Size / Dimension 0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Series	481
Voltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature300ABreaking Capacity @ Rated VoltageHolderMounting TypeHolderPackage / Case.Size / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 19.60mm x 19.60mm)	Fuse Type	Indicating Fuse
Voltage Rating - DC125VResponse TimeFastApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlam IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Current Rating	200mA
Response TimeFastApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Voltage Rating - AC	125V
ApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Voltage Rating - DC	125V
IndicatingFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Response Time	Fast
Class-ApprovalsCSA, UROperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Applications	Telecom
ApprovalsCSA, UROperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Features	Indicating
Operating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Class	-
Breaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Approvals	CSA, UR
Mounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Operating Temperature	-55°C ~ 125°C
Package / Case Alarm Indicator Size / Dimension 0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Breaking Capacity @ Rated Voltage	300A
Size / Dimension 0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Mounting Type	Holder
	Package / Case	Alarm Indicator
Report errors?	Size / Dimension	0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)
		Report errors?

0481.200HXL Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

0481.200HXL Payment Methods



0481.200HXL Shipping Methods



If you have any question about 0481.200HXL, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com