

## 0481.250V

## 0481.250V Information

Heisener.com	Part Number Manufacturer Category Description Package	0481.250V Littelfuse Inc. Circuit Protection Electrical, Specialty Fuses FUSE INDICATING 250MA 125VAC/VDC Alarm Indicator For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 0481.250V Specifications

Manufacturer Part Number0481.250VManufacturerLitelfuse Inc.CategoryCircuit ProtectionPackageAlarn IndicatorPackageAlarn IndicatorSeries481Fuse TypeIndicating FuseCurrent Rating250mAVoltage Rating + AC125VVoltage Rating + DC125VResponse TimeFaceApplicationsTelecomClass-ApprovalsSch QLOperating TemperatureSch QLOperating TemperatureSch QLApprovalsSch QLApprovalsSch QLApprovalsSch QLApprovalsSch QLApprovalsSch QLApprovalsSch QLApprovalsGodAAutomiting TypeHolderApprovalsGodAApprovalsGodAApprovalsSch QLApprovalsSch QLApprovalsSch QLApprovalsGodAApprovalsGodAApprovalsSch QLApprovalsSch CL Sch QLAppr		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageAlarm IndicatorSeries481Fuse TypeIndicating FuseCurrent Rating250mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Manufacturer Part Number	0481.250V
ConstructionElectrical, Specialty FusesPackageAlarm IndicatorSeries481Fuse TypeIndicating FuseCurrent Rating250mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Manufacturer	Littelfuse Inc.
PackageAlarm IndicatorSeries481Fuse TypeIndicating FuseCurrent Rating250mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.655" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Category	Circuit Protection
Series 481   Fuse Type Indicating Fuse   Current Rating 250mA   Voltage Rating - AC 125V   Voltage Rating - DC 125V   Response Time Fast   Applications Telecom   Features Indicating   Class -   Approvals CSA, UR   Operating Temperature 55°C ~ 125°C   Breaking Capacity @ Rated Voltage 300A   Mounting Type Holder   Package / Case Alarm Indicator   Size / Dinnension 665° L x 0.228° W x 0.772° H (16.90mm x 5.80mm x 19.60mm)		Electrical, Specialty Fuses
Fuse TypeIndicating FuseFuse TypeIndicating FuseCurrent Rating250mAVoltage Rating - AC125VVoltage Rating - DCFastResponse TimeFastApplicationsTelecomFeaturesIndicating FuseClass-ApprovalsCSA, UROperating Temperature300ABreaking Capacity @ Rated VoltageJohaMounting TypeAlarm IndicatorPackage / Case0.665" L x 0.228" W x 0.772" H (16.90mm x 19.60mm)	Package	Alarm Indicator
Current Rating 250mA   Voltage Rating - AC 125V   Voltage Rating - DC 125V   Response Time Fast   Applications Telecom   Features Indicating   Class -   Approvals CSA, UR   Operating Temperature 300A   Breaking Capacity @ Rated Voltage 300A   Mounting Type Holder   Package / Case Alarm Indicator   Size / Dimension 0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Series	481
Voltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 19.60mm)	Fuse Type	Indicating Fuse
Voltage Rating - DC125VResponse TimeFastApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature50°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlam IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Current Rating	250mA
Response TimeFastApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Voltage Rating - AC	125V
ApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Voltage Rating - DC	125V
InFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Response Time	Fast
Class-ApprovalsCSA, UROperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Applications	Telecom
ApprovalsCSA, UROperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Features	Indicating
Operating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Class	-
Breaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Approvals	CSA, UR
Mounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Operating Temperature	-55°C ~ 125°C
Package / Case Alarm Indicator   Size / Dimension 0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Breaking Capacity @ Rated Voltage	300A
Size / Dimension 0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Mounting Type	Holder
	Package / Case	Alarm Indicator
Report errors?	Size / Dimension	0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)
		Report errors?

#### 0481.250V Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 0481.250V, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com