

#### 0481002.H Information



For Reference Only

Part Number 0481002.H
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE INDICATING 2A 125VAC/VDC

Package Alarm Indicator

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 0481002.H Specifications

Manufacturer Part Number0481002.HManufacturerLittelfuse Inc.CategoryCircuit ProtectionBeckageAlarm IndicatorSeries481Fuse TypeIndicating FuseCurrent Rating2AVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageAlarm IndicatorSeries481Fuse TypeIndicating FuseCurrent Rating2AVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Manufacturer Part Number	0481002.H
PackageAlarm IndicatorSeries481Fuse TypeIndicating FuseCurrent Rating2AVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Manufacturer	Littelfuse Inc.
PackageAlarm IndicatorSeries481Fuse TypeIndicating FuseCurrent Rating2AVoltage Rating - AC125 VVoltage Rating - DC125 VResponse TimeFastApplicationsTelecomFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage300AMounting TypeHolderPackage / CaseAlarm IndicatorSize / Dimension0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Category	Circuit Protection
Series         481           Fuse Type         Indicating Fuse           Current Rating         2A           Voltage Rating - AC         125 V           Voltage Rating - DC         125 V           Response Time         Fast           Applications         Telecom           Features         Indicating           Class         -           Approvals         CSA, UR           Operating Temperature         -55°C ~ 125°C           Breaking Capacity @ Rated Voltage         300A           Mounting Type         Holder           Package / Case         Alarm Indicator           Size / Dimension         0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)		Electrical, Specialty Fuses
Fuse Type Indicating Fuse  Current Rating 2A  Voltage Rating - AC 125V  Voltage Rating - DC 125V  Response Time Fast  Applications Telecom  Features Indicating  Class -  Approvals CSA, UR  Operating Temperature -55°C ~ 125°C  Breaking Capacity @ Rated Voltage 300A  Mounting Type Holder  Package / Case Alarm Indicator  Size / Dimension 0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Package	Alarm Indicator
Current Rating 2A  Voltage Rating - AC 125V  Voltage Rating - DC 125V  Response Time Fast  Applications Telecom  Features Indicating  Class -  Approvals CSA, UR  Operating Temperature -55°C ~ 125°C  Breaking Capacity @ Rated Voltage 300A  Mounting Type Holder  Package / Case Alarm Indicator  Size / Dimension 0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Series	481
Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Applications  Telecom  Features  Indicating  Class  - Approvals  CSA, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  125V  125V  125V  125V  125V  Fast  Fast  CRA, UR  - 55°C ~ 125°C	Fuse Type	Indicating Fuse
Voltage Rating - DC  Response Time Fast  Applications Telecom  Features Indicating  Class - Approvals Operating Temperature  Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Alarm Indicator  Size / Dimension  125V  Fast Fast Fast Fast  CSA, UR  CSA, UR  -55°C ~ 125°C  300A  Alarm Indicator  Size / Dimension  125V  Fast Fast Fast Fast  Approvals  - CSA, UR  -55°C ~ 125°C  Alarm Indicator  0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Current Rating	2A
Response Time Applications Telecom Features Indicating Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Alarm Indicator Size / Dimension  Fast Fast Fast Fast  Fast  Approvals CSA, UR CSA, UR  -55°C ~ 125°C  300A Holder Fackage / Case Alarm Indicator  0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Voltage Rating - AC	125V
Applications Features Indicating Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  Telecom Telecom Telecom Indicating Capacity CSA, UR -55°C ~ 125°C 300A Holder Holder Holder Size / Dimension  Telecom  Indicating	Voltage Rating - DC	125V
Features Indicating  Class -  Approvals CSA, UR  Operating Temperature -55°C ~ 125°C  Breaking Capacity @ Rated Voltage 300A  Mounting Type Holder  Package / Case Alarm Indicator  Size / Dimension 0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Response Time	Fast
Class - Approvals CSA, UR  Operating Temperature -55°C ~ 125°C  Breaking Capacity @ Rated Voltage 300A  Mounting Type Holder  Package / Case Alarm Indicator  Size / Dimension 0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Applications	Telecom
Approvals  CSA, UR  Operating Temperature  -55°C ~ 125°C  Breaking Capacity @ Rated Voltage  300A  Mounting Type  Holder  Package / Case  Alarm Indicator  Size / Dimension  CSA, UR  -55°C ~ 125°C  Holder  Holder  Holder  Alarm Indicator  0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Features	Indicating
Operating Temperature  -55°C ~ 125°C  Breaking Capacity @ Rated Voltage  300A  Mounting Type  Holder  Package / Case  Alarm Indicator  Size / Dimension  0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Class	-
Breaking Capacity @ Rated Voltage 300A  Mounting Type Holder  Package / Case Alarm Indicator  Size / Dimension 0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Approvals	CSA, UR
Mounting Type Holder Package / Case Alarm Indicator Size / Dimension 0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Operating Temperature	-55°C ~ 125°C
Package / Case         Alarm Indicator           Size / Dimension         0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Breaking Capacity @ Rated Voltage	300A
Size / Dimension 0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)	Mounting Type	Holder
	Package / Case	Alarm Indicator
D	Size / Dimension	0.665" L x 0.228" W x 0.772" H (16.90mm x 5.80mm x 19.60mm)
Report errors?		Report errors?

#### 0481002.H Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 0481002.H Payment Methods



















## 0481002.H Shipping Methods













If you have any question about 0481002.H, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com