

## 0494001.NR

Request a Quote

#### 0494001.NR Information

	Part Number Manufacturer	
www.heisener.com	Category	Circuit Protection Fuses
	Description	FUSE BOARD MNT 1A 32VAC/VDC 0603
	Package	0603 (1608 Metric)
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 0494001.NR Specifications

ManufacturerLittelfuse Inc.CategoryCircuit ProtectionFusesFusesPackage0603 (1608 Metric)Series494Fuse TypeBoard Mount (Catridge Style Excluded)Current RatingIAVoltage Rating - AC32VVoltage Rating - DCSo3 (1608 Metric)Response TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMetring L20.0212ApprovalsCSA, UROperating Temperature-50°C ~ 90°CColor-			
CategoryCircuit ProtectionFusesPackage6603 (1608 Metric)Series494Fuse TypeBoard Mount (Catridge Style Excluded)Fuse TypeBoard Mount (Catridge Style Excluded)Current Rating1AVoltage Rating - AC32VVoltage Rating - DC32VResponse TimeFastPackage / Case6003 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AApprovalsCSA, URApprovalsCSA, UROperating Temperature-50°C ~ 00°CColor-Size / Dimension0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Manufacturer Part Number	0494001.NR	
Fuses   Package 0603 (1608 Metric)   Series 494   Fuse Type Board Mount (Cartridge Style Excluded)   Current Rating 1A   Voltage Rating - AC 32V   Voltage Rating - DC 32V   Response Time Fast   Package / Case 0603 (1608 Metric)   Mounting Type Surface Mount   Breaking Capacity @ Rated Voltage 50A   Approvals CSA, UR   Operating Temperature -50°C ~ 90°C   Color -   Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Manufacturer	Littelfuse Inc.	
Package 0603 (1608 Metric)   Series 494   Fuse Type Board Mount (Cartridge Style Excluded)   Fuse Type IA   Current Rating 1A   Voltage Rating - AC 32V   Voltage Rating - DC 32V   Response Time Fast   Package / Case 6003 (1608 Metric)   Mounting Type Surface Mount   Breaking Capacity @ Rated Voltage 50A   Approvals CSA, UR   Operating Temperature -50°C ~ 90°C   Color -   Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Category	Circuit Protection	
Series494Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating1AVoltage Rating - AC32VVoltage Rating - DC32VResponse TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0212ApprovalsCSA, UROperating Temperature-50°C ~ 90°CColor-Size / Dimension0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)		Fuses	
Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating1AVoltage Rating - AC32VVoltage Rating - DC32VResponse TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0212ApprovalsCSA, UROperating Temperature-50°C ~ 90°CColor-Size / Dimension0.063" L x 0.032" W x 0.012" H (1.60mm x 0.31mm)	Package	0603 (1608 Metric)	
Current Rating1AVoltage Rating - AC32VVoltage Rating - DC32VResponse TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting 12t0.0212ApprovalsCSA, UROperating Temperature-50°C ~ 90°CColor-Size / Dimension0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Series	494	
Voltage Rating - AC32VVoltage Rating - DC32VResponse TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0212ApprovalsCSA, UROperating Temperature-50°C ~ 90°CColor-Size / Dimension0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC32VResponse TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0212ApprovalsCSA, UROperating Temperature-50°C ~ 90°CColor-Size / Dimension0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Current Rating	1A	
Response Time Fast   Package / Case 0603 (1608 Metric)   Mounting Type Surface Mount   Breaking Capacity @ Rated Voltage 50A   Melting I2t 0.0212   Approvals CSA, UR   Operating Temperature -50°C ~ 90°C   Color -   Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Voltage Rating - AC	32V	
Package / Case 0603 (1608 Metric)   Mounting Type Surface Mount   Breaking Capacity @ Rated Voltage 50A   Melting I2t 0.0212   Approvals CSA, UR   Operating Temperature -50°C ~ 90°C   Color -   Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Voltage Rating - DC	32V	
Mounting Type Surface Mount   Breaking Capacity @ Rated Voltage 50A   Melting I2t 0.0212   Approvals CSA, UR   Operating Temperature -50°C ~ 90°C   Color -   Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Response Time	Fast	
Breaking Capacity @ Rated Voltage 50A   Melting I2t 0.0212   Approvals CSA, UR   Operating Temperature -50°C ~ 90°C   Color -   Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Package / Case	0603 (1608 Metric)	
Melting I2t 0.0212   Approvals CSA, UR   Operating Temperature -50°C ~ 90°C   Color -   Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Mounting Type	Surface Mount	
Approvals CSA, UR   Operating Temperature -50°C ~ 90°C   Color -   Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Breaking Capacity @ Rated Voltage	50A	
Operating Temperature -50°C ~ 90°C   Color -   Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Melting I2t	0.0212	
Color -   Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Approvals	CSA, UR	
Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Operating Temperature	-50°C ~ 90°C	
	Color	-	
Report errors?	Size / Dimension	0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	
			Report errors?

#### 0494001.NR Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### 

If you have any question about 0494001.NR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com