

0496060.Z Information

Heisener.com

Part Number 0496060.Z

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE LINK 60A 32VDC IN LINE

Package In-Line

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0496060.Z S	pecifications
-------------	---------------

Manufacturer Part Number 0496060.Z Manufacturer Littelfuse Inc. Category Circuit Protection Package In-Line Series CABLEPRO? Fuse Type Fuse Link Current Rating 60A Voltage Rating - AC - Voltage Rating - DC 32V Response Time - Applications Automotive Features - Class - Approvals UL Operating Temperature -40°C ~ 125°C Breaking Capacity @ Rated Voltage 2kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 2.394" L x 0.729" W x 0.661" H (60.80mm x 18.30mm x 16.80mm)			
Category Circuit Protection Package In-Line Series CABLEPRO? Fuse Type Fuse Link Current Rating 60A Voltage Rating - AC - Voltage Rating - DC 32V Response Time - Applications Automotive Features - Class - Approvals UL Operating Temperature -40°C ~ 125°C Breaking Capacity @ Rated Voltage 2kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 2.394" L x 0.729" W x 0.661" H (60.80mm x 18.30mm x 16.80mm)	Manufacturer Part Number	0496060.Z	
Package In-Line Series CABLEPRO? Fuse Type Fuse Link Current Rating 60A Voltage Rating - AC - Voltage Rating - DC 32V Response Time - Applications Automotive Features - Class - Approvals UL Operating Temperature 40°C ~ 125°C Breaking Capacity @ Rated Voltage 2kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 2.394" L x 0.729" W x 0.661" H (60.80mm x 18.30mm x 16.80mm)	Manufacturer	Littelfuse Inc.	
Package In-Line Series CABLEPRO? Fuse Type Fuse Link Current Rating 60A Voltage Rating - AC - Voltage Rating - DC 32V Response Time - Applications Automotive Features - Class - Approvals UL Operating Temperature -40°C ~ 125°C Breaking Capacity @ Rated Voltage 2kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 2.394" L x 0.729" W x 0.661" H (60.80mm x 18.30mm x 16.80mm)	Category	Circuit Protection	
Series CABLEPRO? Fuse Type Fuse Link Current Rating 60A Voltage Rating - AC - Voltage Rating - DC 32V Response Time - Applications Automotive Features - Class - Approvals UL Operating Temperature -40°C ~ 125°C Breaking Capacity @ Rated Voltage 2kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension CABAC Fuse Link CABLEPRO? Fuse Link Approvals Operating Temperature Wire Lead In-Line Size / Dimension 2.394" L x 0.729" W x 0.661" H (60.80mm x 18.30mm x 16.80mm)		Electrical, Specialty Fuses	
Fuse Type Current Rating 60A Voltage Rating - AC - Voltage Rating - DC 32V Response Time - Applications Automotive Features - Class - Approvals UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case Size / Dimension Fuse Link 60A - UL	Package	In-Line	
Current Rating 60A Voltage Rating - AC - Voltage Rating - DC 32V Response Time - Applications Automotive Features - Class - Approvals UL Operating Temperature -40°C ~ 125°C Breaking Capacity @ Rated Voltage 2kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 232V AUTOMOTIVE AUTO	Series	CABLEPRO?	
Voltage Rating - AC Voltage Rating - DC 32V Response Time - Applications Automotive Features - Class - Approvals UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case Size / Dimension - Size / Dimension - Size / Six	Fuse Type	Fuse Link	
Voltage Rating - DC Response Time - Applications Automotive Features - Class - Approvals UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Vire Lead Package / Case Size / Dimension 32V 32V 32V 32V 32V 32V 32V 32V 32V 32	Current Rating	60A	
Response Time - Applications Automotive Features - Class - Class - Approvals UL Operating Temperature -40°C ~ 125°C Breaking Capacity @ Rated Voltage 2kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 2.394" L x 0.729" W x 0.661" H (60.80mm x 18.30mm x 16.80mm)	Voltage Rating - AC	-	
Applications Automotive Features - Class - Approvals UL Operating Temperature -40°C ~ 125°C Breaking Capacity @ Rated Voltage 2kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 2.394" L x 0.729" W x 0.661" H (60.80mm x 18.30mm x 16.80mm)	Voltage Rating - DC	32V	
Features - Class - Approvals UL Operating Temperature -40°C ~ 125°C Breaking Capacity @ Rated Voltage 2kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 2.394" L x 0.729" W x 0.661" H (60.80mm x 18.30mm x 16.80mm)	Response Time	-	
Class - Approvals UL Operating Temperature -40°C ~ 125°C Breaking Capacity @ Rated Voltage 2kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 2.394" L x 0.729" W x 0.661" H (60.80mm x 18.30mm x 16.80mm)	Applications	Automotive	
Approvals Operating Temperature -40°C ~ 125°C Breaking Capacity @ Rated Voltage 2kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension UL -40°C ~ 125°C Wire Lead 1	Features	-	
Operating Temperature -40°C ~ 125°C Breaking Capacity @ Rated Voltage 2kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 2.394" L x 0.729" W x 0.661" H (60.80mm x 18.30mm x 16.80mm)	Class	-	
Breaking Capacity @ Rated Voltage 2kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 2.394" L x 0.729" W x 0.661" H (60.80mm x 18.30mm x 16.80mm)	Approvals	UL	
Mounting Type Wire Lead Package / Case In-Line Size / Dimension 2.394" L x 0.729" W x 0.661" H (60.80mm x 18.30mm x 16.80mm)	Operating Temperature	-40°C ~ 125°C	
Package / Case In-Line Size / Dimension 2.394" L x 0.729" W x 0.661" H (60.80mm x 18.30mm x 16.80mm)	Breaking Capacity @ Rated Voltage	2kA	
Size / Dimension 2.394" L x 0.729" W x 0.661" H (60.80mm x 18.30mm x 16.80mm)	Mounting Type	Wire Lead	
	Package / Case	In-Line	
Report errors?	Size / Dimension	2.394" L x 0.729" W x 0.661" H (60.80mm x 18.30mm x 16.80mm)	
		Report errors?	

0496060.Z Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0496060.Z Payment Methods



















0496060.Z Shipping Methods













If you have any question about 0496060.Z, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com