

## 0581050.X Information

Heisener.com

Part Number0581050.XManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE STRIP 50A 48VAC/VDC BLT MNT

Package Rectangular, Blade

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0581050.X Specifications
--------------------------

Manufacturer Part Number         0581050.X           Manufacturer         Littelfuse Inc.           Category         Circuit Protection           Package         Rectangular, Blade           Series         POWR-GARD? HAZGARD           Fuse Type         Fuse Strip           Current Rating         50A           Voltage Rating - AC         48V           Voltage Rating - DC         48V           Response Time         Fast           Applications         Lift Trucks           Features         -           Class         -           Approvals         UR           Operating Temperature         -           Breaking Capacity @ Rated Voltage         2.5kA           Mounting Type         Bolt Mount           Package / Case         Rectangular, Blade           Size / Dimension         3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)		
CategoryCircuit ProtectionPackageRectangular, BladeSeriesPOWR-GARD? HAZGARDFuse TypeFuse StripCurrent Rating50AVoltage Rating - AC48VVoltage Rating - DC48VResponse TimeFastApplicationsLift TrucksFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage2.5kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Manufacturer Part Number	0581050.X
Bectrical, Specialty Fuses Package Rectangular, Blade Series POWR-GARD? HAZGARD Fuse Type Fuse Strip Current Rating 50A Voltage Rating - AC 48V Voltage Rating - DC 48V Response Time Fast Applications Lift Trucks Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension	Manufacturer	Littelfuse Inc.
PackageRectangular, BladeSeriesPOWR-GARD? HAZGARDFuse TypeFuse StripCurrent Rating50AVoltage Rating - AC48VVoltage Rating - DC48VResponse TimeFastApplicationsLift TrucksFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage2.5kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Category	Circuit Protection
SeriesPOWR-GARD? HAZGARDFuse TypeFuse StripCurrent Rating50AVoltage Rating - AC48VVoltage Rating - DC48VResponse TimeFastApplicationsLift TrucksFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage2.5kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 50A Voltage Rating - AC 48V Voltage Rating - DC 48V Response Time Fast Applications Lift Trucks Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension Fuse Strip 50A 48V  48V  48V  48V  48V  48V  48V  48V	Package	Rectangular, Blade
Current Rating 50A  Voltage Rating - AC 48V  Voltage Rating - DC 48V  Response Time Fast  Applications Lift Trucks  Features - Class - Approvals UR  Operating Temperature - Breaking Capacity @ Rated Voltage 2.5kA  Mounting Type Bolt Mount  Package / Case Rectangular, Blade Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Series	POWR-GARD? HAZGARD
Voltage Rating - AC  Voltage Rating - DC  48V  Response Time Fast  Applications Lift Trucks  Features - Class - Approvals UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension  48V  48V  48V  48V  48V  48V  48V  48	Fuse Type	Fuse Strip
Voltage Rating - DC  Response Time Fast  Applications Lift Trucks  Features - Class - Approvals UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension  48V  48V  48V  48V  48V  48V  48V  48	Current Rating	50A
Response Time Fast  Applications Lift Trucks  Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 2.5kA  Mounting Type Bolt Mount  Package / Case Rectangular, Blade Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Voltage Rating - AC	48V
Applications  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Rectangular, Blade  Size / Dimension  Lift Trucks  - Braking Capacity @ Lift Trucks  - Bolt Mount  Rectangular, Blade  3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Voltage Rating - DC	48V
Features - Class - Approvals UR Operating Temperature - Eraking Capacity @ Rated Voltage 2.5kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Response Time	Fast
Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 2.5kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Applications	Lift Trucks
Approvals  Operating Temperature  - Breaking Capacity @ Rated Voltage  Bolt Mount  Package / Case  Rectangular, Blade  Size / Dimension  UR  - Bolt Mount  - Bolt Mount  Rectangular, Blade  3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  2.5kA  Mounting Type  Bolt Mount  Package / Case  Rectangular, Blade  Size / Dimension  3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Class	-
Breaking Capacity @ Rated Voltage 2.5kA  Mounting Type Bolt Mount  Package / Case Rectangular, Blade  Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Approvals	UR
Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Operating Temperature	-
Package / Case         Rectangular, Blade           Size / Dimension         3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Breaking Capacity @ Rated Voltage	2.5kA
Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
	Size / Dimension	3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)
Report errors?		Report errors?

### 0581050.X Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 0581050.X Payment Methods





















## 0581050.X Shipping Methods













If you have any question about 0581050.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com