

0581500.X Information

Heisener.com

Part Number 0581500.X

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE STRIP 500A 48VAC/VDC BOLT

Package Rectangular, Blade

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0581500.X Specifications

Manufacturer Part Number 0581500.X Manufacturer Littelfuse Inc. Category Circuit Protection Package Rectangular, Blade Series POWR-GARD? HAZGARD Fuse Type Fuse Strip Current Rating 500A Voltage Rating - AC 48V Voltage Rating - DC 48V Response Time Fast Applications Lift Trucks Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 2.5kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm) Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Rectangular, Blade Series POWR-GARD? HAZGARD Fuse Type Fuse Strip Current Rating 500A Voltage Rating - AC 48V Voltage Rating - DC 48V Response Time Fast Applications Lift Trucks Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 2.5kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Manufacturer Part Number	0581500.X
PackageRectangular, BladeSeriesPOWR-GARD? HAZGARDFuse TypeFuse StripCurrent Rating500AVoltage Rating - AC48VVoltage Rating - DC48VResponse TimeFastApplicationsLift TrucksFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage2.5kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Manufacturer	Littelfuse Inc.
Package Rectangular, Blade Series POWR-GARD? HAZGARD Fuse Type Fuse Strip Current Rating 500A Voltage Rating - AC 48V Voltage Rating - DC 48V Response Time Fast Applications Lift Trucks Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 2.5kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Category	Circuit Protection
SeriesPOWR-GARD? HAZGARDFuse TypeFuse StripCurrent Rating500AVoltage Rating - AC48VVoltage Rating - DC48VResponse TimeFastApplicationsLift TrucksFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage2.5kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)		Electrical, Specialty Fuses
Fuse TypeFuse StripCurrent Rating500AVoltage Rating - AC48VVoltage Rating - DC48VResponse TimeFastApplicationsLift TrucksFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage2.5kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Package	Rectangular, Blade
Current Rating 500A Voltage Rating - AC 48V Voltage Rating - DC 48V Response Time Fast Applications Lift Trucks Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 2.5kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Series	POWR-GARD? HAZGARD
Voltage Rating - AC Voltage Rating - DC 48V Response Time Fast Applications Lift Trucks Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 48V 48V 48V 48V 48V 48V 48V 48	Fuse Type	Fuse Strip
Voltage Rating - DC Response Time Fast Applications Lift Trucks Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 48V 48V 48V 48V 48V 48V 48V 48	Current Rating	500A
Response Time Fast Applications Lift Trucks Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 2.5kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Voltage Rating - AC	48V
Applications Lift Trucks Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 2.5kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Voltage Rating - DC	48V
Features - Class - Approvals UR Operating Temperature - Service - UR Breaking Capacity @ Rated Voltage 2.5kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Response Time	Fast
Class - UR Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 2.5kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Applications	Lift Trucks
Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage Bolt Mount Package / Case Rectangular, Blade Size / Dimension UR - - 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 2.5kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Class	-
Breaking Capacity @ Rated Voltage 2.5kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Approvals	UR
Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Breaking Capacity @ Rated Voltage	2.5kA
Size / Dimension 3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	3.228" L x 1.195" W x 0.683" H (82.00mm x 30.35mm x 17.35mm)
		Report errors?

0581500.X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0581500.X Payment Methods


































If you have any question about 0581500.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com