



06035A270GAT9A Information



For Reference Only

Part Number 06035A270GAT9A
Manufacturer AVX Corporation
Category Capacitors

Ceramic Capacitors

Description CAP CER 27PF 50V C0G/NP0 0603

Package 0603 (1608 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









06035A270GAT9A Specifications

Manufacturer Part Number 06035A270GAT9A Manufacturer AVX Corporation Category Capacitors Package 0603 (1608 Metric) Scries - Capacitance 27pF Tolerance ±2% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style - Report errors?		
Category Capacitors Package 0603 (1608 Metric) Series - Capacitance 27pF Tolerance ±2% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Manufacturer Part Number	06035A270GAT9A
Package 0603 (1608 Metric) Series - Capacitance 27pF Tolerance ±2% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Manufacturer	AVX Corporation
Package 0603 (1608 Metric) Series - Capacitance 27pF Tolerance ±2% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 27pF Tolerance ±2% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 27pF Tolerance ±2% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Package	0603 (1608 Metric)
Tolerance ±2% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Series	-
Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.81mm)Height - Seated (Max)-Thickness (Max)0.035" (0.90mm)Lead Spacing-Lead Style-	Capacitance	27pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.81mm)Height - Seated (Max)-Thickness (Max)0.035" (0.90mm)Lead Spacing-Lead Style-	Tolerance	±2%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.032" W (1.60mm x 0.81mm)Height - Seated (Max)-Thickness (Max)0.035" (0.90mm)Lead Spacing-Lead Style-	Voltage - Rated	50V
Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.063" L x 0.032" W (1.60mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	0603 (1608 Metric)
Thickness (Max) 0.035" (0.90mm) Lead Spacing - Lead Style -	Size / Dimension	0.063" L x 0.032" W (1.60mm x 0.81mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.035" (0.90mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

06035A270GAT9A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

06035A270GAT9A Payment Methods





















06035A270GAT9A Shipping Methods













If you have any question about 06035A270GAT9A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com