



0603J0104P70DCT Information

Heisener.com

Part Number 0603J0104P70DCT
Manufacturer Knowles Syfer
Category Capacitors

Ceramic Capacitors

Description CAP CER 4.7PF 10V C0G/NP0 0603

Package 0603 (1608 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0603J0104P70DCT Specifications

Manufacturer Part Number 0603J0104P70DCT Manufacturer Knowles Syfer Category Capacitors Package 0603 (1608 Metric) Series - Capacitance 4.7pF Tolerance ±0.5pF Voltage - Rated 10V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Spacing - Lead Style -		
Category Capacitors Package 0603 (1608 Metric) Series - Capacitance 4.7pF Tolerance ±0.5pF Voltage - Rated 10V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Manufacturer Part Number	0603J0104P70DCT
Package 0603 (1608 Metric) Series - Capacitance 4.7pF Tolerance ±0.5pF Voltage - Rated 10V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 0603 (1608 Metric) Series - Capacitance 4.7pF Tolerance ±0.5pF Voltage - Rated 10V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 4.7pF Tolerance ±0.5pF Voltage - Rated 10V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 4.7pF Tolerance ±0.5pF Voltage - Rated 10V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Package	0603 (1608 Metric)
Tolerance ±0.5pF Voltage - Rated 10V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Series	-
Voltage - Rated10VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.031" (0.80mm)Lead Spacing-Lead Style-	Capacitance	4.7pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Tolerance	±0.5pF
Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.031" (0.80mm)Lead Spacing-Lead Style-	Voltage - Rated	10V
Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Features	Epoxy Mountable
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	0603 (1608 Metric)
Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Size / Dimension	0.063" L x 0.031" W (1.60mm x 0.80mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.031" (0.80mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

0603J0104P70DCT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0603J0104P70DCT Payment Methods

































If you have any question about 0603J0104P70DCT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com