



## 0603J0630122KDR Information

Heisener.com

Part Number 0603J0630122KDR
Manufacturer Knowles Syfer
Category Capacitors

Ceramic Capacitors

**Description** CAP CER 1200PF 63V X7R 0603

**Package** 0603 (1608 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 0603J0630122KDR Specifications

Manufacturer Part Number         0603J0630122KDR           Manufacturer         Knowles Syfer           Category         Capacitors           Package         0603 (1608 Metric)           Series         -           Capacitance         1200pF           Tolerance         ±10%           Voltage - Rated         63V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         High Temperature           Ratings         -           Applications         High Reliability           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.031" W (1.60mm x 0.80mm)           Height - Seated (Max)         -           Thickness (Max)         0.031" (0.80mm)           Lead Spacing         -           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         0603 (1608 Metric)           Series         -           Capacitance         1200pF           Tolerance         ±10%           Voltage - Rated         63V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         High Temperature           Ratings         -           Applications         High Reliability           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.031" W (1.60mm x 0.80mm)           Height - Seated (Max)         -           Thickness (Max)         0.031" (0.80mm)           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	0603J0630122KDR
Package         0603 (1608 Metric)           Series         -           Capacitance         1200pF           Tolerance         ±10%           Voltage - Rated         63V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         High Temperature           Ratings         -           Applications         High Reliability           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.031" W (1.60mm x 0.80mm)           Height - Seated (Max)         -           Thickness (Max)         0.031" (0.80mm)           Lead Spacing         -           Lead Style         -	Manufacturer	Knowles Syfer
Package         0603 (1608 Metric)           Series         -           Capacitance         1200pF           Tolerance         ±10%           Voltage - Rated         63V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         High Temperature           Ratings         -           Applications         High Reliability           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.031" W (1.60mm x 0.80mm)           Height - Seated (Max)         -           Thickness (Max)         0.031" (0.80mm)           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         -           Capacitance         1200pF           Tolerance         ±10%           Voltage - Rated         63V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         High Temperature           Ratings         -           Applications         High Reliability           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.031" W (1.60mm x 0.80mm)           Height - Seated (Max)         -           Thickness (Max)         0.031" (0.80mm)           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         1200pF           Tolerance         ±10%           Voltage - Rated         63V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         High Temperature           Ratings         -           Applications         High Reliability           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.031" W (1.60mm x 0.80mm)           Height - Seated (Max)         -           Thickness (Max)         0.031" (0.80mm)           Lead Spacing         -           Lead Style         -	Package	0603 (1608 Metric)
Tolerance         ±10%           Voltage - Rated         63V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         High Temperature           Ratings         -           Applications         High Reliability           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.031" W (1.60mm x 0.80mm)           Height - Seated (Max)         -           Thickness (Max)         0.031" (0.80mm)           Lead Spacing         -           Lead Style         -	Series	-
Voltage - Rated  Temperature Coefficient  X7R  Operating Temperature  -55°C ~ 125°C  Features  High Temperature  Ratings  - Applications  High Reliability  Failure Rate  Mounting Type  Surface Mount, MLCC  Package / Case  0603 (1608 Metric)  Size / Dimension  0.063" L x 0.031" W (1.60mm x 0.80mm)  Height - Seated (Max)  - Thickness (Max)  0.031" (0.80mm)  Lead Spacing  - Lead Style	Capacitance	1200pF
Temperature Coefficient  ATR  Operating Temperature  -55°C ~ 125°C  Features  High Temperature  Ratings  -  Applications  High Reliability  Failure Rate  -  Mounting Type  Surface Mount, MLCC  Package / Case  0603 (1608 Metric)  Size / Dimension  0.063" L x 0.031" W (1.60mm x 0.80mm)  Height - Seated (Max)  Thickness (Max)  0.031" (0.80mm)  Lead Spacing  -  Lead Style	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.031" (0.80mm)Lead Spacing-Lead Style-	Voltage - Rated	63V
Features High Temperature  Ratings -  Applications High Reliability  Failure Rate -  Mounting Type Surface Mount, MLCC  Package / Case 0603 (1608 Metric)  Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm)  Height - Seated (Max) -  Thickness (Max) 0.031" (0.80mm)  Lead Spacing -  Lead Style -	Temperature Coefficient	X7R
Ratings - High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Features	High Temperature
Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0603 (1608 Metric)           Size / Dimension         0.063" L x 0.031" W (1.60mm x 0.80mm)           Height - Seated (Max)         -           Thickness (Max)         0.031" (0.80mm)           Lead Spacing         -           Lead Style         -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Applications	High Reliability
Package / Case       0603 (1608 Metric)         Size / Dimension       0.063" L x 0.031" W (1.60mm x 0.80mm)         Height - Seated (Max)       -         Thickness (Max)       0.031" (0.80mm)         Lead Spacing       -         Lead Style       -	Failure Rate	-
Size / Dimension       0.063" L x 0.031" W (1.60mm x 0.80mm)         Height - Seated (Max)       -         Thickness (Max)       0.031" (0.80mm)         Lead Spacing       -         Lead Style       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  -  -  -  -  -  -  -  -  -  -  -  -	Package / Case	0603 (1608 Metric)
Thickness (Max) 0.031" (0.80mm)  Lead Spacing -  Lead Style -	Size / Dimension	0.063" L x 0.031" W (1.60mm x 0.80mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.031" (0.80mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

### 0603J0630122KDR Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 0603J0630122KDR Payment Methods



















## 0603J0630122KDR Shipping Methods













If you have any question about 0603J0630122KDR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com