



0603J5001P00BCR Information

Heisener.com

Part Number 0603J5001P00BCR Manufacturer Knowles Syfer Category Capacitors

Ceramic Capacitors

Description CAP CER 1PF 500V C0G/NP0 0603

0603 (1608 Metric) **Package**

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0603J5001P00BCR Specifications

Manufacturer Part Number 0603J5001P00BCR Manufacturer Knowles Syfer Category Capacitors Package 0603 (1608 Metric) Series - Capacitance 1pF Tolerance ±0.1pF Voltage - Rated 500V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Spacing - Lead Style -		
Category Capacitors Package 0603 (1608 Metric) Series - Capacitance 1pF Tolerance ±0.1pF Voltage - Rated 500V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Manufacturer Part Number	0603J5001P00BCR
Package 0603 (1608 Metric) Series - Capacitance 1pF Tolerance ±0.1pF Voltage - Rated 500V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 0603 (1608 Metric) Series - Capacitance 1pF Tolerance ±0.1pF Voltage - Rated 500V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 1pF Tolerance ±0.1pF Voltage - Rated 500V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 1pF Tolerance ±0.1pF Voltage - Rated 500V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Package	0603 (1608 Metric)
Tolerance ±0.1pF Voltage - Rated 500V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Series	-
Voltage - Rated500VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.031" (0.80mm)Lead Spacing-Lead Style-	Capacitance	1pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.031" (0.80mm)Lead Spacing-Lead Style-	Tolerance	±0.1pF
Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)-Thickness (Max)0.031" (0.80mm)Lead Spacing-Lead Style-	Voltage - Rated	500V
Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Features	Epoxy Mountable
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 0603 (1608 Metric) Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height - Seated (Max) - Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	0603 (1608 Metric)
Thickness (Max) 0.031" (0.80mm) Lead Spacing - Lead Style -	Size / Dimension	0.063" L x 0.031" W (1.60mm x 0.80mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.031" (0.80mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

0603J5001P00BCR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0603J5001P00BCR Payment Methods



















0603J5001P00BCR Shipping Methods













If you have any question about 0603J5001P00BCR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com